

tesa® Professional 4363



Product Information

Plastering Cloth Tape PV2

With the tesa® 4363 Plastering Cloth Tape you get the right tool to protect large areas during painting and plastering work. The rubber adhesive works perfectly on nearly all surfaces, even rough ones. The blue fabric tape offers improved UV resistance over its predecessor. Now the robust tape lasts for up to three weeks, allowing you to tackle longer-term projects. Its water-repellant backing protects it from inclement weather – the right combination for outdoor plastering jobs. That way, you can tackle bigger tasks, without having to worry about the plastering. The tape can be removed without residue within 21 days. Easy to tear off by hand, the dense mesh offers good hand tear ability

Main Application

Perfect masking tape for outdoor use during plastering and painting at construction site

- Water-repellant – rain won't loosen its adhesion
- Good in the sun – UV-resistant for up to 3 weeks
- Easy to tear off by hand, thus easy to use
- Masks and protects large areas
- Safeguards door or window frames as well as sensitive parts
- The blue tape adheres well even to rough surfaces or metal
- Tape composition: cloth backing material with rubber adhesive
- Available sizes: 25m:30mm, 25m:38mm, 25m:50mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

· Backing material	cloth	· Tensile strength	60 N/cm
· Total thickness	310 µm	· UV-resistance	3 weeks
· Type of adhesive	natural rubber	· Mesh	65 count per square inch
· Elongation at break	11 %		

Adhesion to

- steel 3.6 N/cm

Properties

- | | | | |
|-----------------------------------|------|-------------------------------|------|
| · Hand tearability | ●●●● | · Suitable for rough surfaces | ●●●● |
| · Suitable for sensitive surfaces | ●●● | · Conformability | ●●●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

tesa® Professional 4363



Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04363>