



Product data sheet

Status: 13.01.2021 | 00:53

Item no. 1132

Beschichtungsseite
coated side | côté du revêtement



Designation	Stop profile for dry lining 15 mm PB
Line of Business	Plaster
Productclass	Accessory profiles for drylining purposes
Productgroup	Render stops / Architave beads
Plaster thickness	1,0 mm
Material	Galvanised steel
GK/Plate	15,0 mm
Standard EN	EN 14353
Product length	250,0 cm, 300,0 cm
Reaction to fire (R2F)	A1
Packaging Unit	25 BAR / 80 BUN

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general. Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!

PROTEKTORWERK
Florenz Maisch GmbH & Co. KG
Postfach 1420, D-76554 Gaggenau
Viktoriastr. 58, D-76571 Gaggenau

Tel. +49 7225 977 - 0
Fax +49 7225 9 77 - 111
info@protektor.com
www.protektor.com

