

Designation	Stop profile for insulating 50 mm
Description	Render stops made of galvanised steel with PVC coating for thermal insulation plaster. Ideally suited for installing in pairs to create movement joints. Visible joints are closed using a backfill profile and permanent flexible material at the front. Only to be installed vertically on damp or wet surfaces. Centre can only plastered over in certain cases.
Line of Business	Plaster
Productclass	Thermal insulation rendering
Productgroup	Render stops / Architave beads
Plaster thickness	50,0 mm
Material	Galvanised steel, with PVC coating
Standard EN	EN 13658-2
Product length	300,0 cm
Productcolor	wei8 (10)
Reaction to fire (R2F)	E
Packaging Unit	15 BAR / 55 BUN

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general. Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!

PROTEKTORWERK

Florenz Maisch GmbH & Co. KG Postfach 1420, D-76554 Gaggenau Viktoriastr. 58, D-76571 Gaggenau Tel. +49 7225 977 - 0 Fax +49 7225 9 77 - 111 info@protektor.com www.protektor.com

