

Product data sheet

Status: 18.01.2021 | 21:13

Item no. 2263

Beschichtungsseite coated side | côté du revêtement





| Designation | Connecting profile for dry lining 12,5 mm PB |
|------------------------|--|
| Description | PROTEKTOR Stainless steel shadow joint profile for plasterboard panels of 12.5 mm and thicker. Shadow joint (e.g. on wooden block frames, half-timber constructions, etc.) available in various widths. Stop profiles for connecting exposed plastering surfaces. |
| Line of Business | Plaster |
| Productclass | Accessory profiles for drylining purposes |
| Productgroup | Render stops / Architave beads |
| Material | Stainless steel |
| GK/Plate | 12,5 mm |
| Standard EN | EN 13658-1 |
| Product length | 250,0 cm |
| Reaction to fire (R2F) | A1 |
| Application Areas | Ideally suited for damp and wet areas. |
| Treatment | Do not set the profile too deep in the groove when creating connections, e.g. to wooden block frames, and maintain a distance of 2-3 mm. |
| Packaging Unit | 15 BAR / 69 BUN |
| | Please observe the following data sheets: *Data sheet Planning and Application of Metallic Plaster Profiles; published by: The European Association of Bead and Lath Producers, www.europrofiles.com *Data sheet Plaster and Dry Construction in Damp Environments; published by: Zentralverband des Deutschen Baugewerbes, www.zdb.de *Data sheet Winter Construction Sites; published by: Bundesverband der Gipsindustrie e.V., www.gips.de. |



Product data sheet

Status: 18.01.2021 | 21:13

Item no. 2263

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general. Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!

PROTEKTORWERK

Florenz Maisch GmbH & Co. KG Postfach 1420, D-76554 Gaggenau Viktoriastr. 58, D-76571 Gaggenau Tel. +49 7225 977 - 0 Fax +49 7225 9 77 - 111 info@protektor.com www.protektor.com

