

Designation	Corner bead for interior plaster and exterior render 15 mm, rounded edge
Line of Business	Plaster
Productgroup	Corner beads
Plaster thickness	15,0 mm
Material	Stainless steel
Standard EN	EN 13658-1
Standard	EN 13658-2
Product length	250,0 cm, 300,0 cm
Rounding off radius	2,5 mm
Reaction to fire (R2F)	A1
Application Areas	Ideally suited for damp and wet areas.  Specially developed for schools and kindergartens. Satisfies the german guidelines and requirements of the statutory accident prevention regulations. See technical information.
Packaging Unit	25 BAR / 24 BUN
	Please observe the following data sheets:  *Data sheet Planning and Application of Metallic Plaster Profiles; published by: The European Association of Bead and Lath Producers, www.europrofiles.com  *Data sheet Plaster and Dry Construction in Damp Environments; published by: Zentralverband des Deutschen Baugewerbes, www.zdb.de  *Data sheet Winter Construction Sites; published by: Bundesverband der Gipsindustrie e.V., www.gips.de.

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general. Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!

## **PROTEKTORWERK**

Florenz Maisch GmbH & Co. KG Postfach 1420, D-76554 Gaggenau Viktoriastr. 58, D-76571 Gaggenau Tel. +49 7225 977 - 0 Fax +49 7225 9 77 - 111 info@protektor.com www.protektor.com

