Technical Data Sheet



Highly supple and strong premium duct tape with a very good adhesive strength. For work where good isn't good enough.

Properties

- Duct tape consisting of fabric with natural rubber adhesive
- PE-laminated, therefore water-repellent
- Very good adhesive strength and high tensile strength

Area of Use

- Covering work on rough substrates, primarily plaster and stone
- Sandblast and repair work
- Waterproof sealing of containers, safe packaging of transport goods and asbestos disposal
- Take care with lacquered surfaces!

Technical Data

- Backing: Cloth, PE-laminated
- Thickness: 0,23 mm
- Adhesive: Natural Rubber
- Adhesion to Stainless Steel: 5,47 N / 10 mm
- Tensile: 43,8 N / 10 mm
- Elongation: 19%





short-term

Application	Fitness
Indoor	•••
Outdoor	•••
Sensitive Surfaces	
Finished wood	
PVC	
Finery, Stone, Concrete*	•••
Remarks	

90 °C



* Do not use on marble, natural stone and terra-cotta..

● good ●● better ●●● best

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual roles may vary slightly from these averages. The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.