

White Spirit

Product description:

MEGA 901 White Spirit is a tax-deductible mineral oil product to dilute oil and synthetic resin varnish paints and to clean work equipment.

Application:

Among other things, MEGA 901 White Spirit can be used to dilute oil and synthetic resin varnish paints and clear varnishes, wood stains, rust prevention oils and undercoat paints. MEGA 901 White Spirit is also extremely suitable for cleaning work equipment and for removing paint and stains and smudges on linoleum, parquet flooring and other surfaces.

Properties:

Slow evaporation time; therefore, smooth running varnishing is ensured. Does not cause any delay in drying in the case of oxidative curing varnishes. MEGA 901 White Spirit evaporates without leaving behind any residue. Therefore, the coating cannot be affected after drying. No occurrences of boiling due to the retention of solvents for open drying varnishes because of the well-balanced boiling characteristics.

Packaging size:

1 l, 3 l, 6 l, 12 l, 30 l and 500ml

Application:

MEGA 901 White Spirit is primarily used to dilute paints and varnishes in an immersion process because of its slow volatility. However, please observe that MEGA 901 White Spirit is mixed in accordance with the painting requirements.

Technical specifications

Spec. weight:

0.785 g/cm³

Evaporation rate:

46 (ether = 1)

Consistency:

liquid

Storage:

Keep the container tightly closed and store in a cool, well ventilated place. Please observe the legal storage requirements.

Information on disposal:

Only give fully empty containers to recycling. Material residues can be disposed of according to the legal provisions.

Hazard class:

RID/ADR: Class 3, code F1
UN no.: 1300

Hazard warnings and safety instructions:

Liquid and vapour are flammable. Can be fatal if swallowed or if airways are penetrated. Can cause drowsiness and light-headedness. Harmful to aquatic organisms, with long-term effect. Can irritate the respiratory tract. Keep out of the reach of children. If a physician needs to be consulted, have packaging or identification label at hand. Keep away from heat, hot surfaces, sparks, open flames as well as other sources of ignition. Do not smoke. Avoid inhaling dust/smoke/gas/fog/vapour/aerosols. IF SWALLOWED: Immediately call the POISON CONTROL CENTRE/physician. DO NOT initiate vomiting. Keep shut away. Dispose of the content/container in accordance with local regulations.

IN CASE OF SKIN CONTACT (or with hair):

Immediately take off all soiled, saturated pieces of clothing. Wash/shower skin using water. Keep shut away. Dispose of the content/container in accordance with local regulations. Repeated contact can lead to chapped skin or skin fissures. Only give fully empty cans to recycling. Bring cans with remains to the collection point for old paints/varnishes.

Gisbau code:

M-VM02, UN 1300

Contains:

Hydrocarbons, C9-C12, N-alkanes, ISO-alkanes, cyclic compounds, < 2 % aromatic compounds; hydrocarbons, C9 aromatic compounds

Index no.:

649-330-00-2

ASN: 070104

Observe the safety data sheet!

