

Cleaning Diluent

Product description:

MEGA 903 Cleaning Diluent is a semi-volatile solvent mixture with extremely strong dissolving power for all kinds of coating materials.

Application:

MEGA 903 Cleaning Diluent is used as a cleaner, to remove coating materials and degreasing agents from spray guns, pressure hoses, templates as well as similar work equipment prior to paintwork. Furthermore, it is also suitable for degreasing parts prior to paintwork due to its special combination of solvents. To dissolve pyroxlin and synthetic resin varnish as well as chlorinated rubber paint.

Properties:

Extremely strong dissolving power, semi-volatile. Even dissolves varnishes that have become touch dry, excellent grease-dissolving properties. Evaporates without leaving behind any residue and therefore, does not have a negative impact on a later coating of the parts.

Packaging size:

6 l, 12 l, 30 l and 58 l

Application:

MEGA 903 Cleaning Diluent can be used in cleaning, immersion, spraying and flooding applications.

Technical specifications

Spec. weight:

0.847 g/cm³

Evaporation rate:

8 (ether = 1)

Consistency:

liquid

Storage:

Keep the container tightly closed and store in a cool, well ventilated place. Please observe the legal storage requirements.

Information on disposal:

Only give fully empty containers to recycling. Material residues can be disposed of according to the legal provisions.

Product code:

M-VM 03

ASN: 070104

Hazard class:

RID/ADR: Class 3, code F1
UN no.: 1993

Hazard warnings and safety instructions:

Liquid and vapour are flammable. Can be fatal if swallowed or if airways are penetrated. Causes severe damage to the eyes. Causes skin irritations. Can cause drowsiness and light-headedness. Harmful to aquatic organisms, with long-term effect. Keep out of the reach of children. If a physician needs to be consulted, have packaging or identification label at hand.

Keep away from heat, hot surfaces, sparks, open flames as well as other sources of ignition. Do not smoke. Only use outdoors or in well ventilated rooms. Wear safety gloves/protective clothing/protective goggles/face shield. IF SWALLOWED: Immediately call the POISON CONTROL CENTRE/physician. DO NOT initiate vomiting.

Contains: Hydrocarbons, C9, aromatic compounds; butan-1-ol; 2-Methyl-1-propanol; ethyl lactate. Contains ≥ 30 % aromatic hydrocarbons, ester, ketones, alcohols VOC

threshold value: 850 g/l VOC content: 847 g/l.

Observe the safety data sheet!

