

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Product name : Aton Sperrgrund

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use, Professional use  
Use of the substance/mixture : Primer

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Knauf Bauprodukte GmbH & Co. KG  
Am Bahnhof 7  
97346 Iphofen - Germany  
[www.knauf-bauprodukte.de](http://www.knauf-bauprodukte.de)  
E-mail address of competent person responsible for the SDS : [sds-info@knauf.de](mailto:sds-info@knauf.de)

#### Technical information

Technical information service Knauf Bauprodukte  
T +49 (0) 1805/31-9000 (0,14 €/Min. aus dem deutschen Festnetz,  
Mobilfunk max. 0,42€/Min. möglich)  
[KnaufBP-Direkt@Knauf-Bauprodukte.de](mailto:KnaufBP-Direkt@Knauf-Bauprodukte.de)

### 1.4. Emergency telephone number

No additional information available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP] Extra labelling to display Extra classification(s) to display

Precautionary statements (CLP) : P102 - Keep out of reach of children.  
P260 - Do not breathe dusts or mists.  
P262 - Do not get in eyes, on skin, or on clothing.

EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one (2634-33-5), 2-methyl-2H-isothiazol-3-one (2682-20-4), mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9). May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.  
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Extra phrases : Treated article according to Regulation (EU) No 528/2012 to ensure the stability and shelf life.  
Contains pyridine-2-thiol 1-oxide, sodium salt (3811-73-2)  
MAXIMUM VOC CONTENT LIMIT VALUES FOR PAINTS AND VARNISHES. Product Subcategory: g (Type: WB): 30 g/l  
VOC content: <= 0,1 % (≤ 1 g/L)

### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
quartz, conc respirable crystalline silica < 1% substance with a Community workplace exposure limit	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	< 20	Not classified
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	< 0,05	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation), H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5	< 0,0015	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	( 0,05 ≤ C < 100) Skin Sens. 1, H317
mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5	( 0,0015 ≤ C ≤ 100) Skin Sens. 1A, H317 ( 0,06 ≤ C < 0,6) Skin Irrit. 2, H315 ( 0,06 ≤ C < 0,6) Eye Irrit. 2, H319 ( 0,6 ≤ C ≤ 100) Eye Dam. 1, H318 ( 0,6 ≤ C ≤ 100) Skin Corr. 1C, H314

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. Do not use solvents or thinners.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Drink plenty of water. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: The product is not flammable. Adapt extinguishing media to the environment for surrounding fires. Water spray. Foam. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Protection during firefighting : Self-contained breathing apparatus. Complete protective clothing.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate air ventilation.

#### **6.1.1. For non-emergency personnel**

No additional information available

#### **6.1.2. For emergency responders**

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Disposal must be done according to official regulations.

Other information : Spill area may be slippery.

### 6.4. Reference to other sections

7.1. Precautions for safe handling. 8. Exposure controls/personal protection. For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray. When spraying avoid inhalation of the aerosol. Ventilate the area thoroughly. Prohibit unauthorized persons.

Hygiene measures : Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feeding stuffs. Wash contaminated clothing before reuse. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in original container. Keep out of frost. Protect from sunlight. Store in a well-ventilated place.

Storage temperature : 5 – 25 °C

### 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

quartz, conc respirable crystalline silica<1% (14808-60-7)		
EU	Local name	Silica crystalline (Quartz)
EU	IOEL TWA	0,1 mg/m <sup>3</sup> (Respirable fraction)
EU	Notes	OEL limit below 0.05 mg/m <sup>3</sup> of respirable silica dust. (Year of adoption 2003)

### 8.2. Exposure controls

#### **Personal protective equipment:**

Wear suitable protective clothing.

#### **Hand protection:**

Protective gloves

# Aton Sperrgrund

## Safety Data Sheet



according to Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR), Butyl rubber				

### Eye protection:

Use splash goggles when eye contact due to splashing is possible

Type	Field of application	Characteristics	Standard
Safety glasses with side shields			

### Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols. During spraying wear suitable respiratory equipment



### Consumer exposure controls:

Other protection measures such as segregation of activity, minimisation of personnel, respiratory protection, impervious suits and face shields should also be considered for high dispersion activities which are likely to lead to substantial aerosol or vapour release, e.g. spraying.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: slight.
Odour threshold	: No data available
pH	: $\approx 9$ (20 °C)
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: $\approx 100$ °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: $\approx 1,3$ g/cm <sup>3</sup>
Solubility	: completely miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: $\leq 0,1$ % ( $\leq 1$ g/L)
-------------	--------------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

None under normal use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	1020 mg/kg (Rat, Literature study, Oral)

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
LD50 oral rat	53 mg/kg (Rat, Literature study, Oral)
LD50 dermal	200 – 1000 mg/kg bodyweight (Literature study, Dermal)

Skin corrosion/irritation : Not classified  
pH: ≈ 9 (20 °C)

Serious eye damage/irritation : Not classified  
pH: ≈ 9 (20 °C)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
LC50 - Fish [1]	0,28 mg/l (96 h, Lepomis macrochirus, Literature)
EC50 - Crustacea [1]	0,16 mg/l (48 h, Daphnia magna, Literature)
EC50 72h - Algae [1]	0,018 mg/l (Pseudokirchneriella subcapitata, Literature)

### 12.2. Persistence and degradability

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Persistence and degradability	Not readily biodegradable in water.

quartz, conc respirable crystalline silica<1% (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

### 12.3. Bioaccumulative potential

# Aton Sperrgrund

## Safety Data Sheet



according to Regulation (EU) 2015/830

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
BCF - Fish [1]	1,313 – 3,162 (BCFBAF v3.01, Calculated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1,3 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
Bioaccumulative potential	No test data of component(s) available.

<b>quartz, conc respirable crystalline silica&lt;1% (14808-60-7)</b>	
Bioaccumulative potential	No bioaccumulation data available.

### 12.4. Mobility in soil

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
Ecology - soil	Adsorbs into the soil.

<b>mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)</b>	
Ecology - soil	No (test)data on mobility of the components available.

<b>quartz, conc respirable crystalline silica&lt;1% (14808-60-7)</b>	
Ecology - soil	Low potential for mobility in soil.

### 12.5. Results of PBT and vPvB assessment

<b>Component</b>	
quartz, conc respirable crystalline silica<1% (14808-60-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Handle cured product residues as dust-free as possible.
Product/Packaging disposal recommendations	: Do not dispose of the packaging without first carrying out the necessary cleaning. Disposal must be done according to official regulations. Entrust the thoroughly decontaminated packaging to a licensed waste-contractor.
European List of Waste (LoW) code	: 08 01 20 - aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

# Aton Sperrgrund

## Safety Data Sheet



according to Regulation (EU) 2015/830

### 14.6. Special precautions for user

#### - Overland transport

Not applicable

#### - Transport by sea

Not applicable

#### - Air transport

Not applicable

#### - Inland waterway transport

Not applicable

#### - Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content :  $\leq 0,1\%$  ( $\leq 1$  g/L)

Other information, restriction and prohibition regulations : DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products. MAXIMUM VOC CONTENT LIMIT VALUES FOR PAINTS AND VARNISHES. Product Subcategory: h (Type: WB): 30 g/L.

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

This safety data sheet replaces the previous version of 2019/12/19. The following changes were made:

Indication of changes:			
Section	Changed item	Change	Comments
2.2	Precautionary statements (CLP)	Modified	
2.2	EUH-statements	Modified	
3	Composition/information on ingredients	Modified	
7.1	Precautions for safe handling	Modified	
8.2	Respiratory protection	Modified	
8.2	Consumer exposure controls	Added	
13.1	Waste treatment methods	Added	

Full text of H- and EUH-statements:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1

# Aton Sperrgrund

## Safety Data Sheet



according to Regulation (EU) 2015/830

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains 1,2-benzisothiazol-3(2H)-one (2634-33-5), 2-methyl-2H-isothiazol-3-one (2682-20-4), mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Knauf SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*