according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : L-66 Tiefengrund

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings

stance/Mixture

Recommended restrictions

on use

within adequate application - none

1.3 Details of the supplier of the safety data sheet

Company : Alligator Farbwerke GmbH

Markstraße 203 32130 Enger : +4952249300

Telephone : +4952249300 Telefax : +4952247881

E-mail address Responsi-

ble/issuing person

: produktsicherheit@alligator.de

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

15.09.2021 1.0 06.09.2021 Date of first issue: 06.09.2021

Hazard pictograms







Signal Word Danger

Hazard Statements Flammable liquid and vapor. H226

> H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

P101 If medical advice is needed, have product container or **Precautionary Statements**

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if pre-

sent and easy to do. Continue rinsing. Immediately call a

POISON CENTER/ doctor.

Storage:

P405 Store locked up.

Hazardous ingredients which must be listed on the label:

propan-1-ol

2-methylpropan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature Primer based on alkyd resin linseed oil, solvent-containing

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

	Registration number		
propan-1-ol	71-23-8	Flam. Liq. 2; H225	>= 50 - < 70
	200-746-9	Eye Dam. 1; H318	
	603-003-00-0	STOT SE 3; H336	
	01-2119486761-29		
2-methylpropan-1-ol	78-83-1	Flam. Liq. 3; H226	>= 3 - < 10
	201-148-0	Skin Irrit. 2; H315	
	603-108-00-1	Eye Dam. 1; H318	
	01-2119484609-23	STOT SE 3; H336	
		STOT SE 3; H335	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : Never give anything by mouth to an unconscious person.

If you feel unwell, seek medical advice (show the label where

possible).

Move out of dangerous area. First aider needs to protect himself.

If inhaled : Call a physician.

If breathing is irregular or stopped, administer artificial respira-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

Move to fresh air.

In case of skin contact : Do NOT use solvents or thinners.

In case of contact, immediately flush skin with soap and plenty

of water.

Take off all contaminated clothing immediately.

In case of eye contact : If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If swallowed : Seek medical advice.

Clean mouth with water and drink afterwards plenty of water.

If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

None known.

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Cool closed containers exposed to fire with water spray. In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Non-sparking tools should be used.

For personal protection see section 8.

Avoid exceeding the given occupational exposure limits (see

section 8).

Provide sufficient air exchange and/or exhaust in work rooms.

In addition, the current technical information for this product and its application on www.alligator.de/en must be observed.

Advice on protection against

fire and explosion

Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from

heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before

eating, drinking, or smoking. Do not eat, drink or smoke when

using this product.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be

carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3, Flammable liquids

7.3 Specific end use(s)

Specific use(s) : This information is not available.

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methylpropan-1-	78-83-1	AGW	100 ppm	DE TRGS
ol			310 mg/m3	900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of expo- Potential health ef-		Value
		sure	fects	
propan-1-ol	Consumers	Inhalation	Long-term systemic effects	80,00 mg/m3
	Consumers	Ingestion	Long-term systemic effects	61,00 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	1036,00 mg/m3
	Consumers	Skin contact	Long-term systemic effects	81,00 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	1723,00 mg/m3
	Workers	Inhalation	Long-term systemic effects	268,00 mg/m3
	Workers	Skin contact	Long-term systemic effects	136,00 mg/kg bw/day
2-methylpropan-1-ol	Consumers	Inhalation	Long-term local effects	55,00 mg/m3
	Workers	Inhalation	Long-term local ef- fects	310,00 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

		•
Substance name	Environmental Compartment	Value
propan-1-ol	Fresh water sediment	22,8 mg/kg dry weight (d.w.)
	Intermittent use/release	10 mg/l
	Sea sediment	2,28 mg/kg dry weight (d.w.)
	Sewage treatment plant	96 mg/l
	Fresh water	10 mg/l
	Sea water	1 mg/l
	Soil	2,2 mg/kg dry

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

		weight (d.w.)
2-methylpropan-1-ol	Fresh water	0,4 mg/l
	Sea water	0,04 mg/l
	Soil	0,0699 mg/kg dry weight (d.w.)
	Intermittent use/release	11 mg/l
	Fresh water sediment	1,52 mg/kg dry weight (d.w.)
	Sea sediment	0,152 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye protection : German trade association rules - BGR 192 Eye protection

Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suita-

ble gloves tested to EN374.

German trade association leaflet: Carry gloves (ZH 1/706)

Skin and body protection : Safety shoes

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

Remove and wash contaminated clothing before re-use.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be

used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to

standard EN 14387) is used.

German trade association rules - BGR 190 Breathing protec-

tion

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

During spray application: Do not breathe spray dust. Use

A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : No data available

Odor : No data available

Odor Threshold : Not relevant

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower

flammability limit

not determined

Flash point : ca. 23 °C

Autoignition temperature : not determined

Decomposition temperature : Not applicable

pH : 6,95

Concentration: 10 %

Viscosity

Viscosity, dynamic : No data available

Flow time : ca. 15 s

Cross section: 4 mm

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

not determined

Vapor pressure : not determined

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

Relative density : not determined

Density : 0,8700 g/cm3

Relative vapor density : not determined

9.2 Other information

Explosives : Not applicable

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Hazardous decomposition products formed under fire condi-

tions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.

Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Based on available data, the classification criteria

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

are not met.

Components:

propan-1-ol:

Acute oral toxicity : LD50 Oral (Rat): 8.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 33,8 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 4.032 mg/kg

2-methylpropan-1-ol:

Acute oral toxicity : LD50 Oral (Rat): 2.460 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 4.200 mg/kg

Skin corrosion/irritation

Product:

Remarks : According to the classification criteria of the European Union,

the product is not considered as being a skin irritant.

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Product:

Remarks : No data available

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version **Revision Date:** Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste should not be disposed of via wastewater.

Only completely emptied containers should be given for recy-Contaminated packaging

cling.

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

Waste Code : used product

080112, waste paint and varnish other than those mentioned

in 08 01 11*

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL

IATA : Paint related material

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

lowing entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorization (Article 59).

 This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses

have to be defined and no chemical safety assessment has to be gener-

ated.

REACH - List of substances subject to authorisation

(Annex XIV)

None

Seveso III: Directive 2012/18/EU of the Euro-P5c FLAMMABLE LIQUIDS pean Parliament and of the Council on the

control of major-accident hazards involving dangerous substances.

Water hazard class (Germa:

1 slightly water endangering

Classification according to AwSV, Annex 1 (5.2)

Product code for laquers and

paints / Giscode

ny)

: M-GF02 Solvent-based primers, colourless, aromatics re-

moved

. : BSL40 Coating materials, strongly solvent-based, aromatic-

free, classified

Volatile organic compounds : Directive 2004/42/EC

< 73 % < 630 g/l

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapor. H226 : Flammable liquid and vapor.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

Eye Dam. : Serious eye damage

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

Flam. Liq. : Flammable liquids Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada), ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Coil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISAL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for Maritime Dangerous Goods; IMO - International Convention for the Prevention to 50 % of a test population; LO50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention to 50 % of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention to 50 % of a test p

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture: Classification procedure:

Flam. Liq. 3 H226 Based on product data or assessment

Eye Dam. 1 H318 Calculation method STOT SE 3 H336 Calculation method

according to Regulation (EC) No. 1907/2006



L-66 Tiefengrund

Version Revision Date: Print Date Date of last issue: -

1.0 06.09.2021 15.09.2021 Date of first issue: 06.09.2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN