

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **DELTA-TINT® Decorative HP-S WEISS / WHITE 311**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Stainer

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG
Wetterstr. 58
58313 Herdecke
Germany
www.doerkencoatings.de

Phone: +49 2330 63 243

Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Australia: 61-290372994

United Kingdom: 44-870-8200418 and 44-2038073798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

DÖRKEN

COATINGS

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

Hazard pictograms

(Contd. of page 1)



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

Aliphatic polyether esterified with maleic acid
maleic anhydride

Hazard statements

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist/vapours/spray.
P280 Wear protective gloves.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	50-75%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	1-10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

DÖRKEN

COATINGS

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

		(Contd. of page 2)
CAS: 709014-50-6	Aliphatic polyether esterified with maleic acid Skin Sens. 1, H317	≥1-<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥1-<2.5%
	Polyolefin amide alkeneamine sulfide Aquatic Acute 1, H400	≥0.25-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.1%

Additional information:
All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

DE/EN

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

DÖRKEN

COATINGS

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 3)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NO_x). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

DE/EN

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

DÖRKEN

COATINGS

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 4)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the formation of ignitable and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged electrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Solvent fumes are heavier than air and spread over the ground. Fumes can form an explosive mixture with air.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

AGW (Germany)	Long-term value: 300 mg/m ³ 2(II); AGS; vgl. Nr. 2.9 (TRGS 900)
---------------	---

108-65-6 2-Methoxy-1-methylethyl acetate

AGW (Germany)	Long-term value: 270 mg/m ³ , 50 ppm 1(I); DFG, EU, Y
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

DÖRKEN

COATINGS

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 5)

108-31-6 maleic anhydride

AGW (Germany)	Long-term value: 0.081 mg/m ³ , 0.02 ppm 1;=2.5=(I);DFG, Sah, Y, 11
---------------	---

Regulatory information

AGW (Germany): TRGS 900

IOELV (EU): (EU) 2019/1831

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Personal protective equipment:
General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection: Not necessary if room is well-ventilated.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Goggles recommended during refilling

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties
General Information
Appearance:
Form: Fluid

(Contd. on page 7)

DE/EN

Safety data sheet

according to 1907/2006/EC, Article 31

DÖRKEN

COATINGS

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 6)

Colour:	White
Odour:	Weak after aliphatic hydrocarbons
Odour threshold:	For mixtures not applicable.
pH-value:	Not applicable to preparations which contain solvents.
Change in condition	
Melting point/Freezing point:	Not security-related.
Initial boiling point and boiling range:	145-205 °C
Flash point:	39 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C
Decomposition temperature:	For mixtures not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
Oxidising properties	The product is flammable, although not oxidising.
Vapour pressure at 20 °C:	3 hPa
Density at 20 °C:	2.07-2.24 g/cm ³
Vapour density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
polar solvents:	Not miscible or difficult to mix.
non-polar solvents:	Fully miscible.
Partition coefficient: n-octanol/water:	For mixtures not applicable.
Viscosity:	> 90 s (20°C / DIN 53211 / 4 mm) 40-60 s (20°C / ISO 2431 / 6 mm) > 60 s (20°C / ISO 2431 / 6 mm) > 20,5 mm ² /s (40°C)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity Vapours can form explosive mixtures with air.

(Contd. on page 8)

DE/EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: **DELTA-TINT® Decorative HP-S WEISS / WHITE 311**

(Contd. of page 7)

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

10.4 Conditions to avoid Keep away from heat sources, sparks and open flames.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

The product is not tested as one of the above but rather is classified according to the conventional method (calculation procedure set out in the EU Regulation (EC) No 1272/2008) and according to the toxicological risks. See chapters 2 and 3 for detail.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

623-40-5 2-Pentanone oxime

Oral	LD ₅₀	1,133 mg/kg (rat) (OECD 425)
------	------------------	------------------------------

Specific symptoms in biological assay:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Splashes of solvent may cause irritation to the eye and reversible damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness,

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: **DELTA-TINT® Decorative HP-S WEISS / WHITE 311**

(Contd. of page 8)

narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

623-40-5 2-Pentanone oxime

EC ₅₀ / 48 h	≥100 mg/l (Daphnia magna (big water flea)) (OECD 202)
EC ₅₀ / 72 h	88 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC ₅₀ / 96 h	≥100 mg/l (Oncorhynchus mykiss (rainbow trout)) (OECD 203)

12.2 Persistence and degradability

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation	80 % (28d) readily biodegradable
----------------	-------------------------------------

623-40-5 2-Pentanone oxime

OECD 301B CO ₂ Evolution Test	9 % (28d) under test conditions no biodegradation observed
--	---

12.3 Bioaccumulative potential

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Partition Coefficient log Pow	5-6.7 (n-octanol/water)
-------------------------------	-------------------------

623-40-5 2-Pentanone oxime

OECD 117 Log Kow (HPLC method)	1.43 (n-octanol/water) (22 °C; pH 7)
--------------------------------	--------------------------------------

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Behaviour in sewage processing plants:

Polyolefin amide alkeneamine sulfide

EC ₅₀ / 0,5 h	0.1-1 mg/l (algae) 100-1,000 mg/l (bacteria)
--------------------------	---

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP7	Carcinogenic

SECTION 14: Transport information

14.2 UN proper shipping name

UN-Number

ADR, IMDG, IATA

UN1263

ADR

1263 PAINT RELATED MATERIAL

IMDG, IATA

PAINT RELATED MATERIAL

14.3 Transport hazard class(es)

ADR



Class

3 (F1) Flammable liquids.

Label

3

IMDG, IATA



Class

3 Flammable liquids.

Label

3

Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:

Not applicable.

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

30

EMS Number:

F-E,S-E

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 10)

Stowage Category	A
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
Remarks:	When using receptacles with a capacity of at most 450 litre, the transport is not subject to the regulations/specifications of the ADR. However, it is recommended to note then in the shipping documents: > TRANSPORT AFTER SUBSECTION 2.2.3.1.5 ADR <
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Remarks:	Not subject to the IMDG provisions when packed in receptacles not exceeding 30 L capacity.
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E)

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Directive 2012/18/EU
Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

National regulations:
Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

(Contd. on page 12)

DE/EN

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

(Contd. of page 11)

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
Labelling according to Regulation (EC) No 2004/42 Not applicable.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".
 Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012
Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	On basis of test data
Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.05.2021

Version number 02-01

Revision: 11.05.2021

Trade name: DELTA-TINT® Decorative HP-S WEISS / WHITE 311

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

(Contd. of page 12)

Sources

- Regulation 1907/2006/EC (REACH-Regulation)
- Regulation 1272/2008/EC (CLP-Regulation)

* **Data compared to the previous version altered.** Replaces version 02-00

DE/EN