

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** CWS WERTLACK® Markierungsfarbe**Safety data sheet number:** 07-071903531001**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture** Coating agent**Uses advised against**

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**Dörken Coatings GmbH & Co. KG  
formely: CD-Color GmbH & Co. KG  
Wetterstr. 58  
58313 Herdecke  
Germany  
www.doerkencoatings.de

Phone: +49 2330 63 243

Fax: +49 2330 63 100 243

**Further information obtainable from:** msds.coatings@doerken.de**1.4 Emergency telephone number:**

Australia: 61-290372994

United Kingdom: 44-870-8200418 and 44-2038073798

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

DE/EN

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

Trade name: CWS WERTLACK® Markierungsfarbe

(Contd. of page 1)

#### Hazard pictograms



GHS02 GHS07

#### Signal word Danger

#### Hazard-determining components of labelling:

acetone

maleic anhydride

ethyl acetate

Fatty acids, C14-18 and C16-18-unsatd., maleated

#### Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

#### Precautionary statements

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P312 Call a doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

In case of inhalation: Higher doses may lead to a narcotic effect.

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 67-64-1	acetone	10-<20%
EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119471330-49-xxxx		

(Contd. on page 3)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥1-<10%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	1-<2.5%
CAS: 147900-93-4 EC number: 604-612-4 Reg.nr.: 01-2119971821-33-xxxx	Fatty acids, C-18, unsatd. trimers, compd. with 9-octadecen- 1-amine, (Z)- STOT RE 1, H372; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.25-<1%
CAS: 85711-55-3 EINECS: 288-315-1 Reg.nr.: 01-2119974148-28-xxxx	Fatty acids, tall-oil, compds. with oleylamine Skin Sens. 1, H317	≥0.1-<1%

**Additional information:**

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.  
For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**General information:**

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

**After eye contact:**

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an ophthalmologist.

**After swallowing:**

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

After eye contact: May cause irritations.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

(Contd. on page 4)

DE/EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 3)

**4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture**

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO) and nitrogen oxides (NO<sub>x</sub>). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

**5.3 Advice for firefighters****Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

DE/EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

See Section 13 for disposal information.

(Contd. of page 4)

**SECTION 7: Handling and storage**
**7.1 Precautions for safe handling**

Avoid the formation of ignitable and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged electrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Solvent fumes are heavier than air and spread over the ground. Fumes can form an explosive mixture with air.

**7.2 Conditions for safe storage, including any incompatibilities**
**Storage:**
**Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

**Information about storage in one common storage facility:**

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

**Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

**Storage class:** 3

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**
**Additional information about design of technical facilities:**

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

**8.1 Control parameters**
**Ingredients with limit values that require monitoring at the workplace:**
**67-64-1 acetone**

AGW (Germany)	Long-term value: 1200 mg/m <sup>3</sup> , 500 ppm 2(I);AGS, DFG, EU, Y
IOELV (EU)	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm

(Contd. on page 6)

DE/EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 5)

**1330-20-7 xylene (mix)**

AGW (Germany)	Long-term value: 440 mg/m <sup>3</sup> , 100 ppm 2(II);DFG, EU, H
IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin

**141-78-6 ethyl acetate**

AGW (Germany)	Long-term value: 730 mg/m <sup>3</sup> , 200 ppm 2(I);DFG, EU, Y
IOELV (EU)	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm

**100-41-4 ethylbenzene**

AGW (Germany)	Long-term value: 88 mg/m <sup>3</sup> , 20 ppm 2(II);DFG, H, Y, EU
IOELV (EU)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin

**Regulatory information**

AGW (Germany): TRGS 900

IOELV (EU): (EU) 2017/164

**Ingredients with biological limit values:**
**67-64-1 acetone**

BGW (Germany)	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton
---------------	---

**1330-20-7 xylene (mix)**

BGW (Germany)	1.5 mg/l Untersuchungsmaterial: Vollblut Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Xylol
	2000 mg/L Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Methylhippur-(Tolur-)Säure (alle Isomere)

**100-41-4 ethylbenzene**

BGW (Germany)	250 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Mandelsäure plus Phenoxyglyxylsäure
---------------	---

**Regulatory information** BGW (Germany): TRGS 903

**Additional information:** The lists valid during the making were used as basis.

(Contd. on page 7)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 6)

**8.2 Exposure controls** Provide good ventilation and/or an exhaust system in the work area.

**Personal protective equipment:**
**General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

**Respiratory protection:**

Use always breathing protection with splashing medium.

Use combination filter type A(-P2) according to EN 141.

**Protection of hands:**

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

It is recommended to use long gloves to minimize contact by splashing.

**Material of gloves**

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**

Tightly sealed safety goggles are to be worn during all work, in accordance with EN 166.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

**Body protection:** Solvent resistant protective clothing

**SECTION 9: Physical and chemical properties**
**9.1 Information on basic physical and chemical properties**
**General Information**
**Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Different according to colouring

<b>Odour:</b>	Very Esther-like
---------------	------------------

<b>Odour threshold:</b>	For mixtures not applicable.
-------------------------	------------------------------

(Contd. on page 8)

DE/EN

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 7)

<b>pH-value:</b>	Not applicable to preparations which contain solvents.
<b>Change in condition</b>	
<b>Melting point/Freezing point:</b>	Not security-related.
<b>Initial boiling point and boiling range:</b>	>35 °C The specified boiling point corresponds to the manufacturer's specifications for the lowest boiling fraction.
<b>Flash point:</b>	<21 °C
<b>Flammability (solid, gas):</b>	Not applicable.
<b>Ignition temperature:</b>	460 °C The specified ignition temperature refers to the solvent manufacturer specifications.
<b>Decomposition temperature:</b>	For mixtures not applicable.
<b>Auto-ignition temperature:</b>	Product is not selfigniting.
<b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Explosion limits:</b>	
<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	15 Vol %
	The specified explosion limits refer to the solvent manufacturer specifications.
<b>Oxidising properties</b>	The product is flammable, although not oxidising.
<b>Vapour pressure at 20 °C:</b>	233 hPa The specified vapour pressure refers to the solvent manufacturer specifications.
<b>Relative density at 20 °C</b>	~1.4
<b>Vapour density</b>	Not applicable.
<b>Evaporation rate</b>	For mixtures not applicable.
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>polar solvents:</b>	Not miscible or difficult to mix.
<b>non-polar solvents:</b>	Fully miscible.
<b>Partition coefficient: n-octanol/water:</b>	For mixtures not applicable.
<b>Viscosity:</b>	> 90 s (20°C / DIN 53211 / 4 mm) > 20,5 mm <sup>2</sup> /s (40°C)
<b>Solvent content:</b>	
<b>VOC (EC)</b>	VOC limit 2010 for Category i (SB): 500g/l.

(Contd. on page 9)

DE/EN



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 8)

**9.2 Other information**

No further relevant information available.

### SECTION 10: Stability and reactivity

**10.1 Reactivity** Vapours can form explosive mixtures with air.

**10.2 Chemical stability** Product is stable under normal storage conditions.

**10.3 Possibility of hazardous reactions**

No dangerous reactions known.

No dangerous reactions are known.

**10.4 Conditions to avoid** Keep away from heat sources, sparks and open flames.

**10.5 Incompatible materials:** strong oxidizing agents

**10.6 Hazardous decomposition products:**

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects**
**Acute toxicity**

The product is not tested as one of the above but rather is classified according to the conventional method (calculation procedure set out in the EU Regulation (EC) No 1272/2008) and according to the toxicological risks. See chapters 2 and 3 for detail.

**LD/LC50 values relevant for classification:**

The quoted data are literature values and/or manufacturer/supplier data.

**67-64-1 acetone**

Oral	LD <sub>50</sub>	5,800 mg/kg (rat)
Dermal	LD <sub>50</sub>	20,000 mg/kg (rbt)

**1330-20-7 xylene (mix)**

Oral	LD <sub>50</sub>	3,523 mg/kg (rat)
Dermal	LD <sub>50</sub>	1,100 mg/kg (ATE)
Inhalative	LC <sub>50</sub> / 4 h	11 mg/l (ATE)

**100-41-4 ethylbenzene**

Oral	LD <sub>50</sub>	3,500 mg/kg (rat)
Dermal	LD <sub>50</sub>	>5,000 mg/kg (rabbit)
Inhalative	LC <sub>50</sub> / 4 h	17.2 mg/l (rat)

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

(Contd. on page 10)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 9)

**CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

**General notes:**

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

**SECTION 12: Ecological information**
**12.1 Toxicity**
**Aquatic toxicity:**
**1330-20-7 xylene (mix)**

LC <sub>50</sub> / 96 h	13.5 mg/l (fish)
-------------------------	------------------

**100-41-4 ethylbenzene**

EC <sub>50</sub> / 48 h	2.1 mg/l (Daphnia magna (big water flea))
-------------------------	---

EC <sub>50</sub> / 96 h	3.6 mg/l (algae)
-------------------------	------------------

LC <sub>50</sub> / 96 h	12.1 mg/l (Pimephales promelas (fathead minnow))
-------------------------	--

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential**
**1330-20-7 xylene (mix)**

Partition Coefficient log Pow	3.16 (n-octanol/water) (20 °C; pH 7)
-------------------------------	--------------------------------------

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

**PBT:** Not applicable.

**vPvB:** Not applicable.

(Contd. on page 11)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 10)

**12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**
**13.1 Waste treatment methods**
**Recommendation**

Special waste. Do not empty residuals into drain or WC; send to collection for problem waste. Do not dispose of with household waste.

Hardened remnants of material may be disposed of as construction site, hardened paints or as household waste.

**European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP 3	Flammable
HP 4	Irritant - skin irritation and eye damage

**Uncleaned packaging:**
**Recommendation:**

Disposal must be made according to official regulations.

Not contaminated packages may be recycled.

Do not dispose of with household waste. Do not empty into drains.

Hand over receptacles/packages with remainders/leftovers to hazardous waste disposers or collection site for hazardous waste.

**SECTION 14: Transport information**
**UN-Number**
**ADR, IMDG, IATA**

UN1263

**14.2 UN proper shipping name**
**ADR**

1263 PAINT

**IMDG, IATA**

PAINT

**14.3 Transport hazard class(es)**
**ADR**

**Class**

3 (F1) Flammable liquids.

**Label**

3

(Contd. on page 12)

DE/EN

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

Trade name: CWS WERTLACK® Markierungsfarbe

(Contd. of page 11)

## IMDG, IATA



**Class** 3 Flammable liquids.  
**Label** 3

**Packing group**  
**ADR, IMDG, IATA** II

**14.5 Environmental hazards:** Not applicable.

**14.6 Special precautions for user** Warning: Flammable liquids.  
**Hazard identification number (Kemler code):** 33  
**EMS Number:** F-E,S-E  
**Stowage Category** B

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

## Transport/Additional information:

## ADR

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

**Transport category** 2  
**Tunnel restriction code** D/E

**Remarks:** When using receptacles with a capacity of at most 450 litre, the transport is not subject to the regulations/specifications of the ADR. However, it is recommended to note then in the shipping documents:

&gt; TRANSPORT AFTER SUBSECTION 2.2.3.1.5 ADR &lt;

## IMDG

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml  
**Remarks:** IMDG 2.3.2.3 (Verpackungsgruppe III ≤ 30L)  
 Not subject to the IMDG provisions when packed in receptacles not exceeding 30 L capacity.

## IATA

**Remarks:** IATA 3.3.3.1 (Verpackungsgruppe III ≤ 30L)

**UN "Model Regulation":** UN 1263 PAINT, 3, II, (D/E)

DE/EN

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 12)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

##### National regulations:

##### Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

**Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

##### Labelling according to Regulation (EC) No 2004/42

VOC limit 2010 for category i (SB): 500 g/l. This product contains max 500 g/l VOCs.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".  
 Misuse may cause damage to health and environment.

##### Labelling according to regulation (EC) No 528/2012

##### Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

##### Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 14)

### Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.08.2020

Version number 02-00

Revision: 09.07.2020

**Trade name: CWS WERTLACK® Markierungsfarbe**

(Contd. of page 13)

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

**Classification according to Regulation (EC) No 1272/2008**

Flammable liquids	On basis of test data
Serious eye damage/eye irritation Skin sensitisation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Abbreviations and acronyms:**

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - dermal – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**Sources**

- Regulation 1907/2006/EC (REACH-Regulation)

- Regulation 1272/2008/EC (CLP-Regulation)

\* **Data compared to the previous version altered.** Replaces version 01-01