

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **MEGA 004 Epoxi-Grund 2K**

Safety data sheet number: 07-071244443701

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MEGA eG
Fangdieckstrasse 45
22547 Hamburg
Germany
Phone: +4940/54004-0
Fax : +4940/54004-9

Further information obtainable from:

Department "Product range Paint and varnish"
Phone: +49 (0)40 54004-0
E-mail: technik@mega.de

1.4 Emergency telephone number:

+4940 / 54 00 4 - 528 (Mon - Thu 7.15am - 4.30pm, Fri 7.15am - 12.00am)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Warning

(Contd. on page 2)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 1)

Hazard-determining components of labelling:

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100)

Hydrocarbons, C9, aromatics

2-Methoxy-1-methylethyl acetate

maleic anhydride

n-Butyl acetate

Fatty acids, C14-18 and C16-18-unsaturated, maleated

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

In case of inhalation: Higher doses may lead to a narcotic effect.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 23.02.2021

Version number 03-00

Revision: 19.02.2021

Trade name: **MEGA 004 Epoxi-Grund 2K**

(Contd. of page 2)

Dangerous components:

CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	10-25%
CAS: 25036-25-3 NLP: 500-033-5	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥1-≤10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics Alternative CAS number: 64742-95-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	≥2.5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-xxxx	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	1-10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx	2-Butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	<5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<1%
CAS: 24468-28-8 EINECS: 246-279-4 Reg.nr.: 01-2119976378-19-xxxx	1,3,5-Triazin-2,4,6-(1H,3H,5H)-trion, Zinksalz Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<1%
	Fatty acids, C14-18 and C16-18-unsaturated, maleated Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.025%

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.
For the wording of the listed hazard phrases refer to section 16.

DE/EN

(Contd. on page 4)

Trade name: **MEGA 004 Epoxi-Grund 2K**

(Contd. of page 3)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

After eye contact: May cause irritations.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NO_x). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 5)

Trade name: **MEGA 004 Epoxi-Grund 2K**

(Contd. of page 4)

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the formation of ignitable and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged electrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Solvent fumes are heavier than air and spread over the ground. Fumes can form an explosive mixture with air.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

(Contd. on page 6)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 5)

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-Methoxy-1-methylethyl acetate

AGW (Germany)	Long-term value: 270 mg/m ³ , 50 ppm 1(I);DFG, EU, Y
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

Hydrocarbons, C9, aromatics

AGW (Germany)	Long-term value: 50 mg/m ³ 2(II); AGS; vgl. Nr. 2.9 (TRGS 900)
IOELV (EU)	Long-term value: 100 mg/m ³ , 20 ppm (trimethylbenzole)

123-86-4 n-Butyl acetate

AGW (Germany)	Long-term value: 300 mg/m ³ , 62 ppm 2(I);AGS, Y
IOELV (EU)	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm

111-76-2 2-Butoxyethanol

AGW (Germany)	Long-term value: 49 mg/m ³ , 10 ppm 2(I);EU, DFG; H, Y
IOELV (EU)	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 98 mg/m ³ , 20 ppm Skin

108-31-6 maleic anhydride

AGW (Germany)	Long-term value: 0.081 mg/m ³ , 0.02 ppm 1;=2.5=(I);DFG, Sah, Y, 11
---------------	---

Regulatory information

AGW (Germany): TRGS 900

IOELV (EU): (EU) 2019/1831

Ingredients with biological limit values:

111-76-2 2-Butoxyethanol

BGW (Germany)	150 mg/g Kreatinin Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende, bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten Parameter: Butoxyessigsäure (nach Hydrolyse)
---------------	--

Regulatory information BGW (Germany): TRGS 903

(Contd. on page 7)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 6)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

In case of suffering from allergy, asthma and chronic illness of the respiratory system avoid use of this product.

Respiratory protection:

Use always breathing protection with splashing medium.

Use combination filter type A(-P2) according to EN 141.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Multi-layer glove - PE / EVAL / PE

(PE = polyethylene, EVAL = ethylene-vinyl alcohol copolymer)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed safety goggles are to be worn during all work, in accordance with EN 166.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: Different according to colouring

Odour: Very Esther-like

(Contd. on page 8)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 7)

Odour threshold:	For mixtures not applicable.
pH-value:	Not applicable to preparations which contain solvents.
Change in condition	
Melting point/Freezing point:	Not security-related.
Initial boiling point and boiling range:	127 °C
Flash point:	>23 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	333 °C
Decomposition temperature:	For mixtures not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	8.5 Vol %
Oxidising properties	The product is flammable, although not oxidising.
Vapour pressure at 20 °C:	10.7 hPa
Relative density at 20 °C	1.41 - 1.49
Vapour density	Not applicable.
Evaporation rate	For mixtures not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
polar solvents:	Not miscible or difficult to mix.
non-polar solvents:	Fully miscible.
Partition coefficient: n-octanol/water:	For mixtures not applicable.
Viscosity:	40-60 s (20°C / ISO 2431 / 6 mm) > 20,5 mm ² /s (40°C)
Solvent content:	
VOC (EC)	VOC limit 2010 for Category j (SB): 500g/l.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity Vapours can form explosive mixtures with air.

10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

(Contd. on page 9)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 8)

10.4 Conditions to avoid Keep away from heat sources, sparks and open flames.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

The product is not tested as one of the above but rather is classified according to the conventional method (calculation procedure set out in the EU Regulation (EC) No 1272/2008) and according to the toxicological risks. See chapters 2 and 3 for detail.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

25036-25-3 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100)

Oral	LD ₅₀	>30,000 mg/kg (rat)
Dermal	LD ₅₀	>20,000 mg/kg (rat)

111-76-2 2-Butoxyethanol

Oral	LD ₅₀	470 mg/kg (rat) (OECD 401)
Dermal	LD ₅₀	1,100 mg/kg (ATE)
Inhalative	LC ₅₀ / 4 h	2.17 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD ₅₀	3,500 mg/kg (rat)
Dermal	LD ₅₀	>5,000 mg/kg (rabbit)
Inhalative	LC ₅₀ / 4 h	11 mg/l (ATE)

Specific symptoms in biological assay:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

(Contd. on page 10)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 9)

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

25036-25-3 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100)

EC₅₀ / 48 h >100 mg/l (algae)

LC₅₀ / 96 h >100 mg/l (fish)

Hydrocarbons, C9, aromatics

EC₅₀ / 48 h 3.2 mg/l (Daphnia magna (big water flea))

LC₅₀ / 96 h 9.2 mg/l (Oncorhynchus mykiss (rainbow trout))

7779-90-0 Trizinc bis(orthophosphate)

EC₅₀ / 48 h 0.33-0.66 mg/l (Daphnia magna (big water flea)) (OECD 202)

EC₅₀ / 72 h 0.14 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

LC₅₀ / 96 h 0.17 mg/l (Oncorhynchus mykiss (rainbow trout))

111-76-2 2-Butoxyethanol

EC₅₀ / 24 h 1,800 mg/l (Daphnia magna (big water flea))

EC₅₀ / 72 h 911 mg/l (Selenastrum capricornutum)

LC₅₀ / 96 h 1,700 mg/l (Oncorhynchus mykiss (rainbow trout))

>100 mg/l (Lepomis macrochirus (bluegill))

1314-13-2 zinc oxide

EC₅₀ / 48 h 0.17 mg/l (daphnia)

LC₅₀ / 96 h 0.14 mg/l (Oncorhynchus mykiss (rainbow trout))

IC₅₀ / 72 h 0.17 mg/l (algae)
literature

100-41-4 ethylbenzene

EC₅₀ / 48 h 2.1 mg/l (Daphnia magna (big water flea))

EC₅₀ / 96 h 3.6 mg/l (algae)

LC₅₀ / 96 h 12.1 mg/l (Pimephales promelas (fathead minnow))

(Contd. on page 11)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 10)

12.2 Persistence and degradability

Hydrocarbons, C9, aromatics

OECD 301F Manometric Respiratory Test	78 % (28d) (O ₂ consumption) readily biodegradable
---------------------------------------	--

111-76-2 2-Butoxyethanol

OECD 301B CO ₂ Evolution Test	90.4 % (28d) readily biodegradable
--	---------------------------------------

12.3 Bioaccumulative potential

111-76-2 2-Butoxyethanol

Partition Coefficient log Pow	0.81 (n-octanol/water) (25 °C; pH 7)
-------------------------------	--------------------------------------

12.4 Mobility in soil No further relevant information available.

General notes:

Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.

European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP7	Carcinogenic
HP13	Sensitising
HP14	Ecotoxic

SECTION 14: Transport information

14.2 UN proper shipping name

UN-Number

ADR, IMDG, IATA

ADR

UN1263

1263 PAINT, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 12)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 11)

IMDG

PAINT (Hydrocarbons, C9, aromatics, Trizinc bis(orthophosphate)), MARINE POLLUTANT
PAINT

IATA**14.3 Transport hazard class(es)****ADR****Class**

3 (F1) Flammable liquids.

Label

3

IMDG**Class**

3 Flammable liquids.

Label

3

IATA**Class**

3 Flammable liquids.

Label

3

Packing group**ADR, IMDG, IATA**

III

14.5 Environmental hazards:

Product contains environmentally hazardous substances: Trizinc bis(orthophosphate)

Marine pollutant:

Symbol (fish and tree)

Special marking (ADR):

Symbol (fish and tree)

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

30

EMS Number:F-E,S-E**Stowage Category**

A

14.7 Transport in bulk according to Annex II of**Marpol and the IBC Code**

Not applicable.

Transport/Additional information:**ADR****Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

3

Tunnel restriction code

D/E

(Contd. on page 13)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 12)

IMDG**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":UN 1263 PAINT, 3, III, (D/E), ENVIRONMENTALLY
HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

National regulations:**Information about limitation of use:**

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.**Labelling according to Regulation (EC) No 2004/42**

VOC limit according to 2004/42/EC for category j (SB) and maximum VOC content: see lid.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

Misuse may cause damage to health and environment.

(Contd. on page 14)

Trade name: MEGA 004 Epoxi-Grund 2K

(Contd. of page 13)

Labelling according to regulation (EC) No 528/2012

Additional information:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Relevant phrases

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids	On basis of test data
Skin corrosion/irritation Serious eye damage/eye irritation Skin sensitisation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity - oral – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Sources

- Regulation 1907/2006/EC (REACH-Regulation)
 - Regulation 1272/2008/EC (CLP-Regulation)

* **Data compared to the previous version altered.** Replaces version 02-00