according to 1907/2006/EC, Article 31



Printing date 23.02.2021

Version number 04-00

Revision: 22.02.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Trade name: MEGA 142 Aqualack Buntlack matt

Safety data sheet number: 07-071249123702

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: MEGA eG Fangdieckstrasse 45 22547 Hamburg Germany Phone: +4940/54004-0 Fax : +4940/54004-9

Further information obtainable from:

Department "Product range Paint and varnish" Phone: +49 (0)40 54004-0 E-mail: technik@mega.de

1.4 Emergency telephone number:

+4940 / 54 00 4 - 528 (Mon - Thu 7.15am - 4.30pm, Fri 7.15am - 12.00am)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms



Signal word Warning Hazard-determining components of labelling: 2-methyl-2H-isothiazol-3-one 1,2-benzisothiazol-3(2H)-one Hazard statements H317 May cause an allergic skin reaction.

(Contd. on page 2)

- DE/EN -

according to 1907/2006/EC, Article 31



Printing date 23.02.2021

Version number 04-00

Revision: 22.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 1)

Precautionary statements P280 Wear protective gloves. P302+P352 IF ON SKIN: Wash with plenty of soap and water. P362+P364 Take off contaminated clothing and wash it before reuse. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. **Additional information:** EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. 2.3 Other hazards Results of PBT and vPvB assessment **PBT:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

vPvB: Not applicable.

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Titanium dioxide Carc. 2, H351	10-25%	
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<2.5%	
CAS: 13463-41-7 EINECS: 236-671-3 Reg.nr.: 01-2119511196-46-xxxx	Pyrithione zinc Acute Tox. 3, H301; Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Irrit. 2, H315	<0.025%	
CAS: 2682-20-4 EINECS: 220-239-6 Reg.nr.: 01-2120764690-50-xxxx	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.0015$ %	≥0.0015-<0.025%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off. Never give anything by mouth to an unconscious person.

(Contd. on page 3) - DE/EN -

according to 1907/2006/EC, Article 31

медл 🔶

Printing date 23.02.2021

Version number 04-00

Revision: 22.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 2)

After inhalation: Supply fresh air; consult doctor in case of complaints. In case of unconsciousness place patient stably in side position for transportation. After skin contact: Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention. After eye contact: Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist. In case of troubles or persistent symptoms, consult an opthalmologist. After swallowing:

Rinse mouth thoroughly with water. Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide. Use fire extinguishing methods suitable to surrounding conditions. For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO_2) , carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage. Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Keep contaminated washing water and dispose of appropriately.

(Contd. on page 4)

- DE/EN

according to 1907/2006/EC, Article 31

Version number 04-00



Revision: 22.02.2021

Printing date 23.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 3)

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 12

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Ingredients with limit values that require monitoring at the workplace:			
34590-94-8 Dipro	34590-94-8 Dipropylene glycol monomethyl ether		
AGW (Germany)	Long-term value: 310 mg/m ³ , 50 ppm 1(I);DFG, EU, 11		
IOELV (EU)	Long-term value: 308 mg/m³, 50 ppm Skin		
13463-41-7 Pyrithione zinc			
MAK (Germany)	vgl. Abschn.llb		
Regulatory information AGW (Germany): TRGS 900 IOELV (EU): (EU) 2019/1831 Additional information: The lists valid during the making were used as basis.			
8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.			
•	(Contd. on page 5)		

according to 1907/2006/EC, Article 31



Printing date 23.02.2021

Version number 04-00

Revision: 22.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 4)

Personal protective equipment:

General protective and hygienic measures: Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Immediately remove all soiled and contaminated clothing Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Respiratory protection:

Use always breathing protection with splashing medium. Use combination filter type A(-P2) according to EN 141.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed safety goggles are to be worn during all work, in accordance with EN 166. Have eye wash bottle or eye rinse ready at work place. Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Impervious protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties General Information			
Appearance: Form: Colour:	Fluid Different according to colouring		
Odour:	Weak after glycol ethers		
Odour threshold:	For mixtures not applicable.		
pH-value at 20 °C:	8-9		
Change in condition Melting point/Freezing point: Initial boiling point and boiling range:	Not security-related. 100 °C (H₂O)		

(Contd. on page 6)

Printing date 23.02.2021

Safety data sheet

according to 1907/2006/EC, Article 31

медл 🔶

Version number 04-00

Revision: 22.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

	(Contd. of page 5)
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Not applicable.
Decomposition temperature:	For mixtures not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Oxidising properties	In its condition as supplied, the product is neither flammable nor oxidising.
Vapour pressure at 20 °C:	23 hPa (H₂O)
Relative density at 20 °C	1.03 - 1.30
Vapour density	Not applicable.
Evaporation rate	For mixtures not applicable.
Solubility in / Miscibility with water: polar solvents: non-polar solvents:	Miscible / waterdilutable. Partly miscible. Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	For mixtures not applicable.
Viscosity:	Not security-related.
Solvent content: VOC (EC)	VOC limit 2010 for Category d (WB): 130g/l.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions are known.
No further relevant information available.
10.2 Chemical stability Product is stable under normal storage conditions.
10.3 Possibility of hazardous reactions
No dangerous reactions known.
No dangerous reactions are known.
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials: strong oxidizing agents

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Version number 04-00



Revision: 22.02.2021

Printing date 23.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 6)

10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

The product is not tested as one of the above but rather is classified according to the conventional method (calculation procedure set out in the EU Regulation (EC) No 1272/2008) and according to the toxicological risks. See chapters 2 and 3 for detail.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

169117-72-0 2,5,8,11-Tetramethyl-6-dodecyn-5,8-diol ethoxylate

LD₅₀ >2,000 mg/kg (rat) Oral

Dermal LD₅₀ >2,000 mg/kg (rabbit)

Specific symptoms in biological assay:

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties). Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

The mixture contains no or only small amounts of materials which are classified as an aspiration hazard. It can therefore be assumed that the mixture is not an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: There are no statements/information available of the preparation.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential

169117-72-0 2,5,8,11-Tetramethyl-6-dodecyn-5,8-diol ethoxylate

Partition Coefficient log Pow 3.78 (n-octanol/water)

(Contd. on page 8)

according to 1907/2006/EC, Article 31

медл 🔶

Version number 04-00

Revision: 22.02.2021

Printing date 23.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 7)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB). **PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European	European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
HP7	Carcinogenic		

SECTION 14: Transport information

14.2 UN proper shipping name UN-Number ADR, ADN, IMDG, IATA ADR, ADN, IMDG, IATA 14.3 Transport hazard class(es)	Void Void	
ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of		
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)

- DE/EN

according to 1907/2006/EC, Article 31



Printing date 23.02.2021

Version number 04-00

Revision: 22.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 8)

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category d (WB) and maximum VOC content: see lid.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet". Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012

Additional information:

Contains biocidal products: Preservatives for products during storage.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. **Relevant phrases**

Relevant pillases

H301 Toxic if swallowed. H311 Toxic in contact with skin.

- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Skin sensitisation The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

Acute Tox. 3: Acute toxicity - oral – Category 3 Acute Tox. 2: Acute toxicity - inhalation – Category 2 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

according to 1907/2006/EC, Article 31



Printing date 23.02.2021

Version number 04-00

Revision: 22.02.2021

Trade name: MEGA 142 Aqualack Buntlack matt

(Contd. of page 9)

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Carc. 2: Carcinogenicity – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 **Sources** - Regulation 1907/2006/EC (REACH-Regulation)

- Regulation 1272/2008/EC (CLP-Regulation)

* Data compared to the previous version altered. Replaces version 03-00

DE/EN -