

Replace: new

3M™ 2044 Masking tape



Description

This thin washi paper tape with medium adhesion is suited for interior masking of smooth and lightly textured surfaces (e.g. glass, plastic, varnishes, glazes, wood, metal), as well as for use with masking film. It removes cleanly for up to 60 days and is UV resistant.

Product Characteristics	
Backing	Flat back paper
Adhesive	Acrylic adhesive
Standard Roll length	50 m
Color	Blue

Typical Physical Properties	value	Method
Total thickness	81 µm	AFERA 5006
Adhesion to steel	0,76 N/cm	AFERA 5001 / A
Tensile strength	30,7 N/cm	AFERA 5004
Elongation at break	4 %	AFERA 5004

The values displayed are the result of illustrative lab test measures made according to the indicated external norm and shall not be considered as a commitment from 3M

Storage

To obtain best performances, store this product under normal condition of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

Warning

Do not use with or on nitrocellulose lacquer coating

Do not use on paper, unprimed wallboard or rough surfaces.

In case of doubt make a trial in an inconspicuous area.

3M Construction & Home Improvement Markets

Product Information Sheet

Features/Advantages/Benefits

Features	Advantages	Benefits
Acrylic Adhesive	Good Instant adhesion Minimum adhesion build-up over time	Stick easily to the surface Will remove cleanly
	UV resistance	
Flat back paper	Straight line	Easy handling

Important notice:

The use of the 3M product described within this document assumes that the user has read and understood the user notice. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected purpose.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation