

Universal Adhesive

Product description:

Sustainable universal adhesive to lay elastic and textile flooring from the MEGAgrün Healthy Green Living collection, for example design flooring (PVC free), linoleum in strips up to a max. of 3.2 mm, design cork floor Wise Wood pro SRT (climate positive and PVC free) and carpet floors made of plant and animal fibres as well as Econyl fibres. Suitable for even, absorbent and smoothed surfaces. Indoor use only.

Properties:

- short flash-off time
- long working time
- highest level of adhesion

Packaging size:

14 kg

Base surface preparation:

Please observe DIN 18 365. The surface must be stable, viable, dry, free of cracks, clean and free of substances that compromise adhesion. Vacuum off the surface thoroughly and adjust MEGA 235 Dispersion Concentrate according to the absorptivity of the surface, precoat and fill with MEGA 636 Cement-Based Filling Compound. Allow primer and filling compound to fully dry.

Application:

1. Apply universal adhesive evenly using a suitable toothed scraper and allow to flash off in line with the amount applied, the room climate and the absorptivity of the surface. Only apply as much adhesive that can be covered within the working time.

2. Lay down flooring, rub/roll over the entire surface and rework after approx. 20 minutes.

3. Remove residual adhesive in a fresh state using water.

Technical specifications

Complete curing:

After 72 hours

Flash-off time: 10–45 min.*
 Working time: 15–120 min.*
 Load-bearing: after approx. 24 h*
 Weld seams: after approx. 24 h*
 *at 20 °C and 65 % rel. humidity

Processing temperature:

Not below +15 °C

Relative humidity:

No above 75 %

Consumption:

Flooring backing	Toothing	Consumption
smooth	A 5	180–200 g/m ²
smooth	A 1	200–280 g/m ²
slightly textured	A 2	250–350 g/m ²
textured	B 1	320–380 g/m ²

General information

Storage:

Can be stored for at least 12 months. Store in a cool and dry place. Protect against frost.

Composition:

Polymer dispersion, modified resins, preservatives, mineral filling agents, additives and water

GISCODE:

D1–solvent-free

EMICODE:

EC1 PLUS

Hazard warnings and safety instructions:

Solvent-free according to TRGS 610 (Technical Rules for Hazardous Substances). The use of barrier cream is fundamentally recommended. Keep out of the reach of children. Provide for sufficient ventilation during and after application/drying!

Avoid eating, drinking and smoking during application of the product. In the case of contact with eyes or skin, immediately rinse thoroughly with water. Do not allow to penetrate the sewage system, waterbodies or ground soil. Clean tools immediately after use using soap and water. Only give fully empty containers to recycling. Allow remaining product to air-dry and dispose of as construction waste or household waste.

You can obtain information for allergic persons using the telephone number: 040 54004-0.

Observe the safety data sheet!

