

Object Line Wall + Ceiling

Product description:

Solvent-free, low emission, one-coat interior wall paint in wet abrasion resistance class 3 according to DIN EN 13 300, complies with washable according to DIN 53 778.

Application:

For ceilings and walls if a matte surface is required on ingrain wallpaper, plaster, concrete, expanded polystyrene, drywall, etc. is required.

Properties:

Synthetic dispersion paint for indoor use.

- very easy to use
- water-dilutable
- environmentally friendly
- diffusible
- can be applied with airless sprayer
- dull matte
- odourless

Wet abrasion resistance class 3 according to DIN EN 13 300, complies with washable according to DIN 53 778. Contrast ratio (coverage) complies with class 1 with a yield of approx. 5 m²/l according to DIN EN 13 300.

Binding agent basis:

Synthetic dispersion according to DIN 55 945

Spec. weight:

Approx. 1.6 kg/l

Gloss level:

Dull matte according to DIN EN 13 300

Shade of colour:

White

Packaging size:

12.5 l and 25 l

Application:

With paint roller, brush and airless device. To avoid seams, coat wet-on-wet in one go.

Surface:

The surface must be clean, dry and viable. Please observe the guidelines of the VOB, Part C, DIN 18 363, sec. 2 and 3. Non-adherent old layers of paint must be completely removed. Sandy or highly absorbent surfaces, including drywall, must be pretreated with MEGA 202 Hydro Primer. Non-absorbent, stable surfaces require a primer coat with MEGA 253 Primer WP plus.

Technical specifications

Dilution:

With water up to a max. of 5 %.

Tinting:

With full tone and tinting paints up to a max. of 5 %. This can lead to the indicated properties changing.

Cleaning the tools:

Clean tools immediately after use using water.

Drying process:

Paintable after approx. 4 - 6 h at 20 °C and 50 % rel. humidity. Please observe respectively longer drying times in the case of cooler or humid air. At least +5 °C for air and surface.

Consumption:

Approx. 200 ml/m² for one coat depending on the surface. Exact consumption data for the calculation must be determined on the object.

Airless spraying:

Nozzle: 0.021 - 0.026 inch
Spraying angle: 50°
Spray pressure: 150 - 180 bars

General information

Processing temperature:

At least +5 °C object and ambient temperature.

Storage:

Cool however, frost-free. Seal the opened container tightly.

Declaration of the substances of content:

Vinyl acetate dispersion, titanium dioxide, calcium carbonate, silicates, water, additives, preservatives

Information on disposal:

Only give fully empty containers to recycling. Liquid material residues can be disposed of as wastes resulting from water-based paints, dried up material residue in the form of hardened paints or as household waste.

EU threshold value for this product:

Product category: A/a
30 g/l VOC (2010)
This product contains < 1 g/l VOC.

GISCODE:

BSW20

WHC 1:

Self-classification

Observe the safety data sheet!

