

Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCor[®] EG Phosphat Plus Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Corrosion protection, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Deutschland GmbH
		Kornwestheimer Str. 103-107
		D-70439 Stuttgart
Telephone	:	+49 711 8009 0
E-mail address of person	:	EHS@de.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK GmbH Global Regulatory Compliance +49(0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)


Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0



Hazardous components which must be listed on the label:

xylene

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene

Additional Labelling


EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Version 9.0



Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
xylene Contains: ethylbenzene <= 25 %	1330-20-7 215-535-7 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 10 - < 20
reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (number average molecular weight 700 - 1100)	25068-38-6 Not Assigned	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 10 - < 20
trizinc bis(orthophosphate) Contains: zinc oxide <= 2 %	7779-90-0 231-944-3 01-2119485044-40- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 10 - < 20
titanium dioxide; [in powder form containing 1 % or more of parti- cles with aerodynamic diameter ≤ 10 μm]	13463-67-7 236-675-5 01-2119489379-17- XXXX	Carc. 2; H351	>= 5 - < 10
zinc oxide	1314-13-2 215-222-5 01-2119463881-32- XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 5 - < 10
1-methoxy-2-propanol Contains: 2-methoxypropanol <= 0,3 %	107-98-2 203-539-1 01-2119457435-35- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 2,5



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

2-methylpropan-1-ol	78-83-1 201-148-0 01-2119484609-23- XXXX	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	>= 1 - < 2,5
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 1 - < 2,5
1,3-bis[12-hydroxy-octadecamide- N-methylene]-benzene	Not Assigned 423-300-7 01-0000016979-49- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 4; H413	>= 0,25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.	
If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. 	
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 	
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 	
4.2 Most important sympt	ns and effects, both acute and delayed	
Symptoms	 Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health efferences 	ects

Revision Date: 18.05.2021 Date of last issue: 04.08.2020		Version 9.0	Print Date 18.05.2021
Risks	:	irritant effects sensitising effects	
		Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonge exposure if inhaled.	d or repeated
4.3 Indication of any immediate r	me	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
Unsuitable extinguishing media	:	Water High volume water jet	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter fire.	er and spread
ngnung		Do not allow run-off from fire fighting to enter dr courses.	ains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathin	ng apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water se must not be discharged into drains. Fire residues and contaminated fire extinguishir be disposed of in accordance with local regulation	ng water must

SECTION 6: Accidental release measures

6.1 Personal precautions, prote	ctive	equipment and emergency procedures
Personal precautions	:	Use personal protective equipment.

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.
		· · ·



Revision Date: 18.05.2021 Date of last issue: 04.08.2020	Version 9.0	Print Date 18.05.2
	Beware of vapours accumulating to forr tions. Vapours can accumulate in low a	
6.2 Environmental precautions Environmental precautions	: Prevent product from entering drains. If the product contaminates rivers and l respective authorities.	akes or drains inform
6.3 Methods and material for cont	ainment and cleaning up	
Methods for cleaning up	: Contain spillage, and then collect with r sorbent material, (e.g. sand, earth, diate miculite) and place in container for disp / national regulations (see section 13).	omaceous earth, ver-

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage,	incl	luding any incompatibilities

-				1
	Requirements for storage	:	Keep container tightly closed in a dry and well-ventilated	



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

areas and containers		place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Storage class (TRGS 510)	:	3, Flammable liquids
Further information on stor- age stability	:	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *				
		of exposure)	ters *					
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC				
	Further information: Identifies the possibility of significant uptake							
	through the skin, Indicative							
		STEL	100 ppm 442 mg/m3	2000/39/EC				
		AGW	100 ppm 440 mg/m3	DE TRGS 900				
	Peak-limit: exc	ursion factor (categ	ory): 2;(II)					
	Further informa	ation: Skin absorption	on					
titanium dioxide; [in powder form contain- ing 1 % or more of particles with aerody- namic diameter \leq 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium diox- ide)	DE TRGS 900				
	Peak-limit: excursion factor (category): 2;(II)							
		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium diox- ide)	DE TRGS 900				
	Peak-limit: excursion factor (category): 2;(II)							
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC				
	Further information: Identifies the possibility of significant uptake							
	through the skin, Indicative							
		STEL	150 ppm 568 mg/m3	2000/39/EC				
		AGW	100 ppm 370 mg/m3	DE TRGS 900				
	Peak-limit: excursion factor (category): 2;(I)							
	Further information: Senate commission for the review of com-							
	pounds at the work place dangerous for the health (MAK-							
	commission)., European Union (The EU has established a limit							
	value: deviations in value and peak limit are possible), When there							
	is compliance with the OEL and biological tolerance values, there							
	is no risk of harming the unborn child							
2-methylpropan-1-ol	78-83-1	AGW	100 ppm 310 mg/m3	DE TRGS 900				



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

Peak-limit: excursion factor (category): 1;(I)
Further information: Senate commission for the review of com-
pounds at the work place dangerous for the health (MAK-
commission)., When there is compliance with the OEL and biolog-
ical tolerance values, there is no risk of harming the unborn child

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.


Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
xylene	1330-20-7	xylene: 1,5 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903
1-methoxy-2-propanol	107-98-2	1-Methoxypropan- 2-ol: 15 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

8.2 Exposure controls

Personal protective equipment

Eye protection :	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation. This can be achieved by local



Version 9.0




exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental expos	ure controls
General advice	 Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	various
Odour	:	hydrocarbon-like
Odour Threshold		No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	23 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	7,9993 hPa
Relative vapour density	:	No data available
Density	:	ca. 1,80 g/cm3 (20 °C)
Solubility(ies)		



Version 9.0



Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	ca. 270 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	600 - 1.200 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.
10.4 Conditions to avoid		
Conditions to avoid	:	Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Revision Date: 18.05.2021 Date of last issue: 04.08.2020

Acute toxicity

Version 9.0

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Not classified based on available information. **Components:**

<u>components.</u>		
xylene:		
Acute oral toxicity	:	LD50 Oral (Rat): 3.523 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.700 mg/kg
trizinc bis(orthophosphate):		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.001 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,7 mg/l Exposure time: 4 h Test atmosphere: dust/mist
zinc oxide:		
Acute oral toxicity	:	LD50 Oral (Rat): > 15.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,7 mg/l Exposure time: 4 h Test atmosphere: dust/mist
1-methoxy-2-propanol:		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50: 7,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
oxirane, mono[(C12-14-alky	lov	w)methyl] derivs :
Acute oral toxicity	:	
1,3-bis[12-hydroxy-octadeca	ami	de-N-methylene]-benzene:
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg
Skin corrosion/irritation Causes skin irritation.		

Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0



Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:		
xylene:		
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic tox-	:	NOEC: > 1,3 mg/l



Revision Date: 18.05.2021 Date of last issue: 04.08.2020

Version 9.0

Date of last issue: 04.08.2020		
icity)		Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)
zinc oxide:		
Toxicity to algae/aquatic plants	:	EC50 (Selenastrum capricornutum (green algae)): 0,17 mg/l Exposure time: 72 h
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1
1-methoxy-2-propanol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
1,3-bis[12-hydroxy-octadeca	ami	de-N-methylenel-benzene:
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
12.2 Persistence and degradabil No data available	ity	
12.3 Bioaccumulative potential No data available		
12.4 Mobility in soil No data available		
12.5 Results of PBT and vPvB as	se	ssment
Product:		
Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher
12.6 Endocrine disrupting prope	rtie	s
Product:		
Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 In accordance with the EWC Waste Regulation the classifica- tion of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number. Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany.
	For further details see www.sika.de

SECTION 14: Transport information

14.1 UN number		
ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADR	:	PAINT
IMDG	:	PAINT (zinc oxide)
ΙΑΤΑ	:	Paint
14.3 Transport hazard class(es)		
ADR	:	3
IMDG	:	3
ΙΑΤΑ	:	3
14.4 Packing group		

Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0



ADR

Cla Ha: Lat	cking group ssification Code zard Identification Number pels nnel restriction code	:	III F1 30 3 (D/E)
Lat	DG cking group bels S Code	:	III 3 F-E, S-E
Pao airc Pao Pao	A (Cargo) cking instruction (cargo craft) cking instruction (LQ) cking group pels	:	366 Y344 III Flammable Liquids
Pao ger Pao Pao	CA (Passenger) cking instruction (passen- aircraft) cking instruction (LQ) cking group bels	:	355 Y344 III Flammable Liquids
14.5 En	vironmental hazards		
AD ריחE	R <i>v</i> ironmentally hazardous	:	yes

IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

÷

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 3



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

	International Chemical Weapons Schedules of Toxic Chemicals and	:	Not applicable	
	REACH - Candidate List of Substa Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
	REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
	Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that de-	:	Not applicable
	Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu-	:	Not applicable
	Regulation (EC) No 649/2012 of t ment and the Council concerning of dangerous chemicals		:	Not applicable
	REACH Information:	All substances containe - registered by our upst - registered by us, and/ - excluded from the reg - exempted from the reg	trea or jula	im suppliers, and/or tion, and/or
I	Seveso III: Directive 2012/18/EU o jor-accident hazards involving dar P5c			and of the Council on the control of ma-
I	E2	ENVIRONMENTAL HA	ZA	RDS
	Water contaminating class : (Germany)	WGK 2 obviously haza		
	Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 20,88 %
		Directive 2010/75/ELLo	f 24	1 November 2010 on industrial

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 20,88 %


GISCODE

: RE70

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Product is no subject to the Chemicals Prohibition Ordinance. Country DE 00000024986



Version 9.0



15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

I un text of II-otatements		
H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335		May cause respiratory irritation.
H336	÷	May cause drowsiness or dizziness.
H351		Suspected of causing cancer if inhaled.
H373	:	May cause damage to organs through prolonged or repeated
	•	exposure if inhaled.
H400		Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
11415	•	May cause long lasting harmun enects to aquatic life.
Full text of other abbreviatio	ns	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.		Carcinogenicity
Eye Dam.		Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first
2000/39/20	•	list of indicative occupational exposure limit values
DE TRGS 900		Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	
	:	TRGS 903 - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	÷	Short term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average
ADR	:	European Agreement concerning the International Carriage of
0.1.0		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
		47 / 4



Revision Date: 18.05.2021 Date of last issue: 04.08.2020 Version 9.0

ΙΑΤΑ		International Air Transport Association
IMDG	÷	International Maritime Code for Dangerous Goods
LD50	÷	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the	mixture:	Classification procedure:		
Flam. Liq. 3	H226	Based on product data or assessment		
Skin Irrit. 2	H315	Calculation method		
Eye Irrit. 2	H319	Calculation method		
Skin Sens. 1	H317	Calculation method		
STOT RE 2	H373	Calculation method		
Aquatic Chronic 2	H411	Calculation method		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

DE / EN



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCor[®] EG Phosphat Plus Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Corrosion protection, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Deutschland GmbH
		Kornwestheimer Str. 103-107
		D-70439 Stuttgart
Telephone	:	+49 711 8009 0
E-mail address of person	:	EHS@de.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK GmbH Global Regulatory Compliance +49(0)6132-84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

226: Flammable liquid and vapour.
1302: Harmful if swallowed.
315: Causes skin irritation.
318: Causes serious eye damage.
1317: May cause an allergic skin reaction.
335: May cause respiratory irritation.
373: May cause damage to organs through pro- onged or repeated exposure if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

5 01 1d31 1350E. 0 4 .00.2020			
Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H226 H302 H315 H317 H318 H335 H373	Flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause damage to organs through pro- longed or repeated exposure if inhaled.
Precautionary statements	:	Prevention:	
	·	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P260	Do not breathe mist or vapours.
		P264 P280	Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P305 + P351 +	P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:


Cashew, nutshell liq. xylene Amines, polyethylenepoly-, triethylenetetramine fraction

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Version 5.0



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Fatty acids, tall-oil, dimers, poly- mers with tall-oil fatty acids and triethylenetetramine	68915-18-4 Not Assigned	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 40 - < 60
Cashew, nutshell liq.	8007-24-7 700-991-6 01-2119502450-57- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 25 - < 40
xylene Contains: ethylbenzene <= 25 %	1330-20-7 215-535-7 01-2119488216-32- XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 20 - < 25
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 1 - < 2,5
Amines, polyethylenepoly-, tri- ethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	>= 0,25 - < 1

For explanation of abbreviations see section 16.

1

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.



Revision Date: 16.09.2021 Date of last issue: 04.08.2020		Version 5.0	Print Date 16.09.202
If inhaled	:	Move to fresh air. Consult a physician after significant exp	oosure.
In case of skin contact	:	Take off contaminated clothing and sho Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	:	Small amounts splashed into eyes can sue damage and blindness. In the case of contact with eyes, rinse ir of water and seek medical advice. Continue rinsing eyes during transport t Remove contact lenses. Keep eye wide open while rinsing.	mmediately with plenty
If swallowed	:	Do not induce vomiting without medical Rinse mouth with water. Do not give milk or alcoholic beverages Never give anything by mouth to an unc	i.
4.2 Most important symptoms a	nd	effects, both acute and delayed	
Symptoms	:	Gastrointestinal discomfort Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed inform and symptoms.	nation on health effects
Risks	:	irritant effects sensitising effects	
		Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation. May cause damage to organs through p exposure if inhaled.	prolonged or repeated
4.3 Indication of any immediate	me	dical attention and special treatment n	reeded
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting mea	su	res	
5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2)	



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

			Dry chemical
	Unsuitable extinguishing media	:	Water High volume water jet
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Use personal protective equipment. Remove all sources of ignition.
	Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.	
		If the product contaminates rivers and lakes or drains infor	
		respective authorities.	

6.3 Methods and material for containment and cleaning up

2

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling
- Avoid exceeding the given occupational exposure limits (see section 8).



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

Duit	, of lust issue. 04.00.2020		
			Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage,	inc	luding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Storage class (TRGS 510)	:	3, Flammable liquids
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s) Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
xylene	1330-20-7	TWA	50 ppm	2000/39/EC
			221 mg/m3	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

STEL	100 ppm 442 mg/m3	2000/39/EC	
AGW	50 ppm 220 mg/m3	DE TRGS 900	
Peak-limit: excursion factor (category): 2;(II)			
Further information: Skin absorption			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
xylene	1330-20-7	xylene: 1,5 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		methylhippuric acid (all isomers): 2 g/l (Urine)	Immediately after exposure or after working hours	TRGS 903


8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances



Version 5.0



Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1	Information on basic physical Physical state	liquid	
	Colour	:	transparent
	Odour	:	slight
	Boiling point/boiling range	:	No data available
	Upper/lower flammability or	exp	losive limits
	Upper explosion limit / Up- per flammability limit	:	7 %(V)
	Lower explosion limit / Lower flammability limit	:	1 %(V)
	Flash point	:	ca. 48 °C Method: closed cup
	Auto-ignition temperature	:	465 °C
	рН	:	Not applicable substance/mixture is non-soluble (in water)
	Viscosity		
	Viscosity, dynamic	:	ca. 1.500 mPa.s (20 °C)
	Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

Solubility(ies) Water solubility	:	insoluble
Vapour pressure	:	7,9993 hPa
Density	:	ca. 0,95 g/cm3 (20 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid	: Heat, flames and sparks.
---------------------	----------------------------

10.5 Incompatible materials

Materials to avoid : No data available


10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed.	
Components:	
Cashew, nutshell liq.: Acute oral toxicity	: LD50 Oral (Rat): 500 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rat): 2.000 mg/kg



Version 5.0



xylene:					
Acute oral toxicity	:	LD50 Oral (Rat): 3.523 mg/kg			
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.700 mg/kg			
2,4,6-tris(dimethylaminomet	hy)phenol:			
Acute oral toxicity	:	LD50 (Rat): > 1.999 mg/kg			
		Remarks: Harmful if swallowed. Annex VI - Harmonised			
		REGULATION (EC) No 1272/2008			
		· · · ·			
Amines, polyethylenepoly-,	trie	thylenetetramine fraction:			
Acute oral toxicity	:	LD50 Oral (Rat): 1.716 mg/kg			
Acute inhalation toxicity		Assessment: Corrosive to the respiratory tract.			
Acute initialation toxicity	•	Assessment. Convine to the respiratory tract.			
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.465 mg/kg			
Skin corrosion/irritation					
Causes skin irritation.					
<u>Components:</u>					
2,4,6-tris(dimethylaminomet	hy)phenol:			
Species	:	Rabbit			
Assessment	:	Corrosive			
Method	:	OECD Test Guideline 404			
Assessment	:	irritating			
Remarks	:	Annex VI - Harmonised			
		REGULATION (EC) No 1272/2008			
Serious eye damage/eye irritation					
	au				

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	:	Rabbit Causes serious eye damage.
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

xylene: Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic tox- icity)	:	NOEC: > 1,3 mg/l Exposure time: 56 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 1,17 mg/l Exposure time: 7 d Species: Daphnia (water flea)

Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0



2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic:EC50 (Scenedesmus capricornutum (fresh water algae)): > 10plants- 100 mg/lExposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number. Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany. For further details see www.sika.de

Version 5.0



SECTION 14: Transport information

14.1 UN number		
ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263
14.2 UN proper shipping name		
ADR	:	PAINT
IMDG	:	PAINT
ΙΑΤΑ	:	Paint
14.3 Transport hazard class(es)		
ADR	:	3
IMDG	:	3
ΙΑΤΑ	:	3
14.4 Packing group		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		III F1 30 3 (D/E)
IMDG Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	•	366 Y344 III Flammable Liquids
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids

14.5 Environmental hazards

ADR

Print Date 16.09.2021

Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

Environmentally hazardous:noIMDG
Marine pollutant:noIATA (Passenger)
Environmentally hazardous:noIATA (Cargo)
Environmentally hazardous:no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

	Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			Not applicable
	Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)			Not applicable
	Regulation (EC) No 1005/2009 on substances that deplete the ozone layer			Not applicable
REACH - List of substances subject to authorisation (Annex XIV)			:	Not applicable
	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).			None of the components are listed (=> 0.1 %).
	International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			Not applicable
	REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

		rective 2012/18/EU of the European Parliament and of the Council on the contr azards involving dangerous substances. FLAMMABLE LIQUIDS			
1	Water hazard class (Germa- ny)	:	WGK 2 obviously hazardous to water Classification according to AwSV, Annex 1 (5.2)		
	Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 24,74% w/w		
			Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 24,74% w/w		

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Product is no subject to the Chemicals Prohibition Ordinance.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

E	40.44	~ f	LI Statamanta
ruii	τεχτ	ΟΤ	H-Statements

H226	•	Flammable liquid and vapour.		
H302		Harmful if swallowed.		
H304	:	May be fatal if swallowed and enters airways.		
H312		Harmful in contact with skin.		
-	:			
H314	•	Causes severe skin burns and eye damage.		
H315	:	Causes skin irritation.		
H317	:	May cause an allergic skin reaction.		
H318	:	Causes serious eye damage.		
H319	:	Causes serious eye irritation.		
H332	:	Harmful if inhaled.		
H335	:	May cause respiratory irritation.		
H373	:	May cause damage to organs through prolonged or repeated		
		exposure if inhaled.		
H412	:	Harmful to aquatic life with long lasting effects.		
Full text of other abbreviations				
Acute Tox.	:	Acute toxicity		
Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
Asp. Tox.		Aspiration hazard		
•	:	•		
Eye Dam.	:	, ,		
Eye Irrit.	:	Eye irritation		

Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0



e of last issue. 04.06.2020				
Flam. Liq. Skin Corr. Skin Irrit. Skin Sens. STOT RE STOT SE 2000/39/EC	 Specific target organ to Europe. Commission D 	xicity - repeated exposure xicity - single exposure irective 2000/39/EC establishing a first tional exposure limit values		
DE TRGS 900 TRGS 903 2000/39/EC / TWA 2000/39/EC / STEL DE TRGS 900 / AGW ADR	 Germany. TRGS 900 - TRGS 903 - Biological Limit Value - eight hour Short term exposure lir Time Weighted Averag 	Occupational exposure limit values. limit values rs nit e concerning the International Carriage of		
CAS DNEL EC50 GHS IATA IMDG LD50	 Chemical Abstracts Se Derived no-effect level Half maximal effective Globally Harmonized S International Air Transp International Maritime (Median lethal dosis (the once, which causes the 	Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of		
LC50		ation (concentrations of the chemical in test animals during the observation		
MARPOL	: International Convention	n for the Prevention of Pollution from d by the Protocol of 1978		
OEL PBT PNEC REACH SVHC vPvB	 Occupational Exposure Persistent, bioaccumula Predicted no effect con Regulation (EC) No 199 and of the Council of 18 istration, Evaluation, Au cals (REACH), establis Substances of Very Hig 	Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative		
Further information				
Classification of the mixtur	۲ ۵ .	Classification procedure:		
Flam. Liq. 3	H226	Based on product data or assessment		
Acute Tox. 4	H302	Calculation method		
Skin Irrit. 2	H315	Calculation method		
Eye Dam. 1	H318	Calculation method		
Skin Sens. 1	H317	Calculation method		
STOT SE 3	H317 H335	Calculation method		
STOT SE 3 STOT RE 2		Calculation method		
STULKE 2	H373			



Revision Date: 16.09.2021 Date of last issue: 04.08.2020 Version 5.0

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

DE / EN