

Classic Radiator Paint

Product description:

Glossy radiator paint based on a special synthetic resin free of aromatic compounds.

Application:

Indoors. For high-quality painting of hot-water heaters. Apply a test coat for industrial powder-coated radiators.

Properties:

- dries very quickly
- rust inhibiting
- resistant to yellowing up to 80 °C
- heat-resistant up to 180 °C
- odourless
- excellent coverage and filling capacity
- excellent edge coverage
- excellent spreading rate and application properties
- good stability on vertical surfaces

Binding agent basis:

Special resin free of aromatic compounds

Spec. weight:

1.13 kg/l

Shade of colour:

White

Packaging size:

2.5 l

Application:

With brush, paint roller and sprayer.

Base surface preparation:

The surfaces must be viable, free of dirt and separating substances. Remove loose coats of paint. Clean and sand old adhesive coats of paint well. Preliminary work must have been conducted on the radiators according to DIN 55 900.

Pretreatment:

Repaint coatings:

Sandpaper the old layers of paint using steel wool and repair blank spots.

Recoating:

After drying overnight, new coat

Technical specifications

Dilution:

This product is ready for use

Cleaning the tools:

Clean immediately after use using MEGA 904 Synthetic Resin Thinner or MEGA 901 White Spirit.

Consumption:

Approx. 80 - 100 ml/m² depending on the coating thickness and surface roughness of the base surface. Exact consumption data must be determined on the object.

Drying process:

At 20 °C and 50 % rel. humidity:

Dust dry: after approx. 3 h

Dry to handle: after approx. 5 h

Completely dry

and paintable: after approx. 20 h

(heat exposure accelerates the drying process.)

Airless spraying:

If required, dilute up to a max. of 5 %

High pressure spraying:

3 - 4 bars, nozzle 1.5 - 1.8 mm

General information

Storage:

At least 24 months

Declaration of the substances of content:

Alkyd resin, titanium dioxide, silicates, mineral pigments/filling agents, aliphatic compounds, water, additives

Information on disposal:

Only give fully empty containers to recycling. Give liquid material residues to the collection centre for old paints/varnishes, dispose of dried up material residues as construction or demolition waste or as residential waste or household waste.

EU threshold value for this product:

Product category: A/i

This product contains a max. of 410 g/l VOC.

GISCODE:

BSL40

Hazard warnings and safety instructions:

Liquid and vapour flammable. If a physician needs to be consulted, have packaging or identification label at hand. Keep out of the reach of children. Keep away from heat, hot surfaces, sparks, open flames as well as other sources of ignition. Do not smoke. Only use outdoors or in well ventilated rooms. IN CASE OF SKIN CONTACT (or hair): Immediately take off all contaminated pieces of clothing. Wash/shower skin using water. Repeated contact can lead to chapped skin or skin fissures. Attention! Dangerous respirable droplets can form when spraying; do not inhale aerosols or droplets.

Observe the safety data sheet!

