

according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LUCITE® Xtra Protect 2in1

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG Wetterstr. 58

58313 Herdecke

Germany www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Australia: 61-290372994

United Kingdom: 44-870-8200418 and 44-2038073798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word Danger

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 1)

Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 3-Iodo-2-propynylbutylcarbamate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

| Dangerous components: | | |
|---|--|---------|
| EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 50-<75% |
| | Asp. Tox. 1, H304 | |
| CAS: 13463-67-7 EINECS: 236-675-5 | Titanium dioxide Carc. 2, H351 | 1-<5% |
| Reg.nr.: 01-2119489379-17-xxxx | | |
| CAS: 55406-53-6 EINECS: 259-627-5 | 3-lodo-2-propynylbutylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317 | 0.95% |
| CAS: 68920-66-1 NLP: 500-236-9 Reg.nr.: 01-2119489407-26-xxxx | Alcohols, C16-18 and C18-unsaturated, ethoxylated Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Skin Irrit. 2, H315 | <0.25% |
| EC number: 931-745-8 Reg.nr.: 01-2119582803-32-xxxx | Imidazolium compounds, 2-(C17 and C17-unsatd. alkyl)-1-[2-(C18 and C18-unsatd. amido)ethyl]-4,5-dihydro-1-methyl, Me sulfates Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319 | <0.25% |

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

CAS: 61791-53-5 Amines, N-tallow alkyltrimethylenedi-, oleates <0.0015% EINECS: 263-186-4 Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Skin Irrit. 2, H315

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Wash with plenty of soap and water.

In case of skin reactions consult a physician. Do not scratch.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Risk of aspiration!

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

Hazards

When swallowed and vomited immediately, aspiration into the lungs may occur resulting in chemical pneumonia or suffocation.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 3)

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the formation of ignitible and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged elektrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 4)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Solvent fumes are heavier than air and spread over the ground. Fumes can form an explosive mixture with air

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 10

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

AGW (Germany) Long-term value: 300 mg/m³

2(II); AGS; vgl. Nr. 2.9 (TRGS 900)

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics

AGW (Germany) Long-term value: 300 mg/m³

2(II); AGS; vgl. Nr. 2.9 (TRGS 900)

Regulatory information AGW (Germany): TRGS 900

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Respiratory protection:

Use always breathing protection with splashing medium.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 5)

Use combination filter type A(-P2) according to EN 141.

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374.

Material of gloves

Nitrile rubber

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Wear protective goggles to protect against splashing.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Solvent resistant protective clothing

| 9.1 Information on basic physical a General Information | and chemical properties | |
|---|------------------------------------|--|
| Appearance: | | |
| Form: | Fluid | |
| Colour: | Different according to colouring | |
| Odour: | Weak after aliphatic hydrocarbons | |
| Odour threshold: | For mixtures not applicable. | |
| pH-value: | Mixture is non-soluble (in water). | |
| Change in condition | | |
| Melting point/Freezing point: | Not security-related. | |
| Initial boiling point and boiling ra | ange: 186-214 °C | |
| Flash point: | >61 °C | |
| Flammability (solid, gas): | Not applicable. | |
| Ignition temperature: | >200 °C | |
| Decomposition temperature: | For mixtures not applicable. | |
| Auto-ignition temperature: | Product is not selfigniting. | |

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

| | (Contd. of page |
|---|---|
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 0.6 Vol % |
| Upper: | 7 Vol % |
| Oxidising properties | The product is flammable, although not oxidising. |
| Vapour pressure at 20 °C: | 0.5 hPa |
| Density at 20 °C: | ~0.86 g/cm³ |
| Vapour density | Not applicable. |
| Evaporation rate | For mixtures not applicable. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| polar solvents: | Not miscible or difficult to mix. |
| non-polar solvents: | Fully miscible. |
| Partition coefficient: n-octanol/water: | For mixtures not applicable. |
| Viscosity: | < 20,5 mm²/s (40°C) |
| 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- 10.1 Reactivity Vapours can form explosive mixtures with air.
- **10.2 Chemical stability** Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

- **10.4 Conditions to avoid** Keep away from heat sources, sparks and open flames.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 7)

| 55406-53- | 55406-53-6 3-lodo-2-propynylbutylcarbamate | |
|------------|--|---------------------|
| Oral | LD ₅₀ | 300-500 mg/kg (rat) |
| Dermal | LD_{50} | >2,000 mg/kg (rat) |
| Inhalative | LC ₅₀ / 4 h | 0.5 mg/l (ATE) |

Specific symptoms in biological assay:

Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation Splashes of solvent may cause irritation to the eye and reversible damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

| | 55406-53-6 3-lodo-2- | propynylbutylcarbamate | |
|---|-----------------------------------|--|--------------------|
| | EC ₅₀ / 48 h | 0.47 mg/l (daphnia) (OECD 202) | |
| | EC ₅₀ / 72 h | 0.049 mg/l (Pseudokirchneriella subcapitata) (OECD 201) | |
| | LC ₅₀ / 96 h (dynamic) | 0.145 mg/l (Oncorhynchus mykiss (rainbow trout)) | |
| | NOEC / 21 d | 10 mg/l (daphnia) (OECD 211) | |
| | NOEC / 28 d | 0.014 mg/l (Pimephales promelas (fathead minnow)) (OECD 210) | |
| - | | | (Contd. on page 9) |

DE/EN



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 8)

| 12.2 Persistence and degradability | |
|--|---------------------------------------|
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, c | yclics, < 2% aromatics |
| OECD 301F Manometric Respirometry Test | 80 % (28d) |
| | readily biodegradable |
| 55406-53-6 3-lodo-2-propynylbutylcarbamate | · |
| OECD 307 Aerobic And Anaerobic Transformation S | oil 0.03-0.04 d (soil microorganisms) |
| OECD 308 Simulation Biodegradation Aqu Sed Syste | em 1-1.2 d (degradation half-life) |
| 12.3 Bioaccumulative potential | |
| 55406-53-6 3-lodo-2-propynylbutylcarbamate | |
| Partition Coefficient log Pow 2.8 (n-octanol/water) (C | DECD 117) |

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

| Behaviour in sewage processing plants: | | |
|--|--|--|
| 55406-53-6 3-lodo-2-propynylbuty | lcarbamate | |
| OECD 302B Zahn-Wellens Test | >70 % (activated sludge organisms) | |
| OECD 303A Activated Sludge Units | 100 % (activated sludge organisms) | |
| EC ₂₀ / 3 h | 8.2 mg/l (activated sludge organisms) (OECD 209) | |
| EC ₅₀ / 3 h | 8.2 mg/l (activated sludge organisms) (OECD 209) | |

General notes: Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

| European waste catalogue | |
|--------------------------|---|
| 03 02 05* | other wood preservatives containing hazardous substances |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP7 | Carcinogenic |

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

HP14 Ecotoxic (Contd. of page 9)

| 14.1 UN-Number | |
|---|-----------------|
| ADR, ADN, IMDG, IATA | Void |
| 14.2 UN proper shipping name | |
| ADR, ADN, IMDG, IATA | Void |
| 14.3 Transport hazard class(es) | |
| ADR, ADN, IMDG, IATA | |
| Class | Void |
| 14.4 Packing group | |
| ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Not applicable. |
| 14.7 Transport in bulk according to Ann | nex II of |
| Marpol and the IBC Code | Not applicable. |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 11)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 10)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit 2010 for category f (SB): 700 g/l. This product contains max 700 g/l VOCs.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012

Active substance content in 100 g of product: 0.95 g 3-iodo-2-propynyl butylcarbamate (IPBC)

Authorisation number: see lid.

Authorisation holder:

Kurt Obermeier GmbH & Co. KG • Berghäuser Str. 70 • 57319 Bad Berleburg • Germany

Additional information: Do not use on wood which may come in direct contact with food and feeding stuff.

Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 12)



according to 1907/2006/EC, Article 31

Printing date 05.03.2022 Version number 02-01 Revision: 04.03.2022

Trade name: LUCITE® Xtra Protect 2in1

(Contd. of page 11)

Classification according to Regulation (EC) No 1272/2008

Aspiration hazard

Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.

DE/EN -