

according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: CWS WERTLACK® Epoxi-Grund

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating agent

Uses advised against

This product is not suitable for uses other than those specified in the "Use of the substance/mixture". If your particular manner of use is not listed, please contact the creator of this safety data sheet.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Dörken Coatings GmbH & Co. KG

Wetterstr. 58 58313 Herdecke

Germany

www.doerkencoatings.de

Phone: +49 2330 63 243 Fax: +49 2330 63 100 243

Further information obtainable from: msds.coatings@doerken.de

1.4 Emergency telephone number:

Australia: 61-290372994

United Kingdom: 44-870-8200418 and 44-2038073798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS0

Signal word Warning

Hazard-determining components of labelling:

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100)

Hydrocarbons, C9, aromatics

2-Methoxy-1-methylethyl acetate

maleic anhydride

n-Butyl acetate

Fatty acids, C14-18 and C16-18-unsaturated, maleated

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Vapours of the product are heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Vapours can form explosive mixtures with air.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 2)

In case of inhalation: Higher doses may lead to a narcotic effect.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

CAS: 13463-67-7	Titanium dioxide	10-25%
EINECS: 236-675-5 Reg.nr.: 01-2119489379-17-xxxx	Carc. 2, H351	
CAS: 25036-25-3 NLP: 500-033-5	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥1-≤10%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-xxxx	Hydrocarbons, C9, aromatics Alternative CAS number: 64742-95-6 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335; STOT SE 3, H336	≥2.5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40-xxxx	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥2.5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	1-10%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36-xxxx	-	<5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<1%
CAS: 24468-28-8 EINECS: 246-279-4	1,3,5-Triazin-2,4,6-(1H,3H,5H)-trion, Zinksalz Aguatic Acute 1, H400; Aguatic Chronic 1, H410	≥0.25-<1%

DE/EN



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

		(Contd. of page 3)
EC number: 701-043-4	Fatty acids, C14-18 and C16-18-unsaturated, maleated	≥0.1-<1%
Reg.nr.: 01-2119976378-19-xxxx	Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 108-31-6	maleic anhydride	≥0.001-<0.025%
EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin	
-	Sens. 1A, H317	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C ≥ 0.001 %	

Additional information:

All hydrocarbons used comply with note P (less than 0.1% benzene) of the CLP regulation.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In all cases of doubt, or when symptoms persist, seek medical advice.

Soiled, soaked clothes immediately take off.

Never give anything by mouth to an unconscious person.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

Take off immediately all contaminated clothing and wash it before reuse.

After eye contact:

Remove contact lenses. Keep eye lids open and rinse plentifully for at least 10 minutes with clean running water. Subsequently consult an ophthalmologist.

In case of troubles or persistent symptoms, consult an opthalmologist.

After swallowing:

Rinse mouth thoroughly with water.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

After eye contact: May cause irritations.

Headache, dizziness, numbness, sickness/nausea, tiredness, stunning effect, dry skin, allergic reactions.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

DE/EN

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 4)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Extinguishing powder, foam, carbon dioxide.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Can form explosive gas-air mixtures.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Fire will produce dangerous decomposition products like dense, black smoke, carbon dioxide (CO₂), carbon monoxide (CO) and nitrogen oxides (NOx). Inhalation may cause serious health damage.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources and ensure a well-ventilated room. Do not inhale fumes.

Avoid contact with skin and eyes.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

DE/EN



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 5)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid the formation of ignitible and explosion- hazardous solution vapours.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Material can become charged elektrostatically. Anti-static clothing including shoes are recommended.

Avoid contact with skin and eyes as well as inhalation of vapours.

Avoid the handling of incompatible substances and mixtures. Incompatible substances: see section 10.5

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Solvent fumes are heavier than air and spread over the ground. Fumes can form an explosive mixture with air

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Make sure spills can be contained, e.g. in sump pallets.

Protect from frost, heat and direct sunlight. Keep tightly closed, cool and dry.

Information about storage in one common storage facility:

Note the rules for common storage in accordance with TRGS 510 - "Storage of hazardous substances in transportable containers".

Store away from foodstuffs.

Further information about storage conditions: None.

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Additional information about design of technical facilities:

Ensure a good ventilation. This can be achieved by local exhaustion or general exhaust air.

Ingredients with	Ingredients with limit values that require monitoring at the workplace: 108-65-6 2-Methoxy-1-methylethyl acetate		
108-65-6 2-Metho			
AGW (Germany)	Long-term value: 270 mg/m³, 50 ppm 1(I);DFG, EU, Y		
	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin		
Hydrocarbons, C	29, aromatics		
	Long-term value: 50 mg/m³ 2(II); AGS; vgl. Nr. 2.9 (TRGS 900)		

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

		(Contd. of page 6)
IOELV (EU)	Long-term value: 100 mg/m³, 20 ppm (trimethylbenzole)	
123-86-4 n-Butyl	acetate	
AGW (Germany)	Long-term value: 300 mg/m³, 62 ppm 2(I);AGS, Y	
IOELV (EU)	Short-term value: 723 mg/m³, 150 ppm Long-term value: 241 mg/m³, 50 ppm	
111-76-2 2-Buto	xyethanol	
AGW (Germany)	Long-term value: 49 mg/m³, 10 ppm 2(I);EU, DFG; H, Y	
IOELV (EU)	Short-term value: 246 mg/m³, 50 ppm Long-term value: 98 mg/m³, 20 ppm Skin	
108-31-6 maleic anhydride		
AGW (Germany)	Long-term value: 0.081 mg/m³, 0.02 ppm 1;=2.5=(I);DFG, Sah, Y, 11	

Regulatory information

AGW (Germany): TRGS 900 IOELV (EU): (EU) 2019/1831

Ingredients with biological limit values:

111-76-2 2-Butoxyethanol

BGW (Germany) 150 mg/g Kreatinin

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende, bei Langzeitexposition: am

Schichtende nach mehreren vorangegangenen Schichten

Parameter: Butoxyessigsäure (nach Hydrolyse)

Regulatory information BGW (Germany): TRGS 903

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls Provide good ventilation and/or an exhaust system in the work area.

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

In case of suffering from allergy, asthma and chronic illness of the respiratory system avoid use of this product.

Respiratory protection:

Use always breathing protection with splashing medium.

Use combination filter type A(-P2) according to EN 141.

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 7)

Protection of hands:

Work with gloves. Gloves must be inspected for damage before use. Defective or damaged gloves must not be used. Gloves must satisfy the specifications of EC directive 89/686/EWG and standard EN 374. It is recommended to use long gloves to minimize contact by splashing.

Material of gloves

Multi-layer glove - PE / EVAL / PE

(PE = polyethylene, EVAL = ethylene-vinyl alcohol copolymer)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed safety goggles are to be worn during all work, in accordance with EN 166.

Have eye wash bottle or eye rinse ready at work place.

Professional Cooperative Rules - BGR 192 Use of eye and face protection

Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and General Information Appearance:	chemical properties
Form:	Fluid
Colour:	Different according to colouring
Odour:	Very Esther-like
Odour threshold:	For mixtures not applicable.
pH-value:	Mixture is non-soluble (in water).
Change in condition Melting point/Freezing point: Initial boiling point and boiling range	Not security-related. e: 127 °C
Flash point:	27 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	333 °C
Decomposition temperature:	For mixtures not applicable.
	(Contd on page 0)

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

	(Contd. of page 8
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	8.5 Vol %
Oxidising properties	The product is flammable, although not oxidising.
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.42-1.48 g/cm³
Vapour density	Not applicable.
Evaporation rate	For mixtures not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
polar solvents:	Not miscible or difficult to mix.
non-polar solvents:	Fully miscible.
Partition coefficient: n-octanol/water:	For mixtures not applicable.
Viscosity:	> 90 s (20°C / DIN 53211 / 4 mm)
	> 60 s (20°C / ISO 2431 / 6 mm)
	> 20,5 mm ² /s (40°C)
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity Vapours can form explosive mixtures with air.
- 10.2 Chemical stability Product is stable under normal storage conditions.

10.3 Possibility of hazardous reactions

No dangerous reactions known.

No dangerous reactions are known.

- **10.4 Conditions to avoid** Keep away from heat sources, sparks and open flames.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products:

In case of fire arise: smoke and carbon oxides. Under certain fire conditions tracks of other toxic products can not be excluded.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 9)

LD/LC50 values relevant for classification:

The quoted data are literature values and/or manufacturer/supplier data.

25036-25-	25036-25-3 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100)		
Oral	LD ₅₀	>30,000 mg/kg (rat)	
Dermal	LD ₅₀	>20,000 mg/kg (rat)	
111-76-2	111-76-2 2-Butoxyethanol		
Oral	LD ₅₀	470 mg/kg (rat) (OECD 401)	
		1,200 mg/kg (ATE)	
Inhalative	LC ₅₀ / 4 h	2.17 mg/l (rat)	

Specific symptoms in biological assay:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product is not classified as carcinogenic, mutagenic or toxic to reproduction (CMR properties).

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Due to the viscosity (see section 9), classification as an aspiration hazard is omitted.

General notes:

Inhalation of solvent concentrations in excess of the OEL or MAK limit values can lead to health damage such as irritation of the mucous membranes and respiratory tract, damage to the kidneys and liver, and impairment of the central nervous system. Symptoms: headaches, dizziness, fatigue, muscle weakness, narcotic effect and, in exceptional cases, loss of consciousness. Prolonged or repeated contact with the product impairs the skin's natural lipid replenishment and causes the skin to dry out. The product can enter the body through the skin. Splashes of solvent may cause irritation to the eye and reversible damage.

DE/EN

(Contd. on page 11)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 10)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Toxic to aq	Toxic to aquatic life with long lasting effects.		
25036-25-3 Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number averagemolecular weight 700 - 1100)			
EC ₅₀ / 48 h	>100 mg/l (algae)		
LC₅₀ / 96 h	LC₅₀ / 96 h >100 mg/l (fish)		
Hydrocarb	ons, C9, aromatics		
EC ₅₀ / 48 h	3.2 mg/l (Daphnia magna (big wat	er flea))	
LC₅₀ / 96 h	9.2 mg/l (Oncorhynchus mykiss (ra	ainbow trout))	
7779-90-0	Trizinc bis(orthophosphate)		
EC ₅₀ / 48 h	0.33-0.66 mg/l (Daphnia magna (b	pig water flea)) (OECD 202)	
EC₅₀ / 72 h	0.14 mg/l (Pseudokirchneriella sub	ocapitata) (OECD 201)	
LC₅₀ / 96 h	0.17 mg/l (Oncorhynchus mykiss ((rainbow trout))	
	-Butoxyethanol		
EC₅₀ / 24 h	1,800 mg/l (Daphnia magna (big water flea))		
EC ₅₀ / 72 h	911 mg/l (Selenastrum capricornutum)		
LC ₅₀ / 96 h	1,700 mg/l (Oncorhynchus mykiss (rainbow trout))		
	>100 mg/l (Lepomis macrochirus (bluegill))		
1314-13-2	zinc oxide		
EC ₅₀ / 48 h	EC₅₀ / 48 h 0.17 mg/l (daphnia)		
LC₅₀ / 96 h	6 h 0.14 mg/l (Oncorhynchus mykiss (rainbow trout))		
IC₅₀ / 72 h	IC ₅₀ / 72 h 0.17 mg/l (algae) literature		
12.2 Persis	stence and degradability		
Hydrocarb	ons, C9, aromatics		
OECD 3011	F Manometric Respirometry Test	78 % /O₂ consump (28d) readily biodegradable	
	-Butoxyethanol		
OECD 301I	B CO ₂ -Evolution Test (Sturm Test)		
		readily biodegradable	

12.3 Bioaccumulative potential

111-76-2 2-Butoxyethanol

Partition Coefficient log Pow 0.81 (n-octanol/water) (25 °C; pH 7)

12.4 Mobility in soil No further relevant information available.

General notes:

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 12)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 11)

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

This product does not contain relevant substances that have been assessed as persistent, bioaccumulative and toxic (PBT) or as very persistent and very bioaccumulative (vPvB).

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

European waste catalogue			
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
HP3	Flammable		
HP4	Irritant - skin irritation and eye damage		
HP7	Carcinogenic		
HP13	Sensitising		
HP14	Ecotoxic		

SECTION 14: Transport information

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
IMDG	PAINT (Hydrocarbons, C9, aromatics, Trizinc
	bis(orthophosphate)), MARINE POLLUTANT
IATA	PAINT

14.3 Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.

(Contd. on page 13)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

3

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 12)

Label **IMDG**



Class

3 Flammable liquids.

Label **IATA**



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA Ш

14.5 Environmental hazards: Product contains environmentally hazardous substances:

Hydrocarbons, C9, aromatics

Marine pollutant: Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): **EMS Number:** F-E,S-E **Stowage Category**

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3 **Tunnel restriction code** D/E

IMDG

Limited quantities (LQ) 5L **Excepted quantities (EQ)** Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

> > (Contd. on page 14)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 13)

UN 1263 PAINT, 3, III, (D/E), ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Observe employment restrictions concerning young persons.

Observe employment restrictions for expectant or nursing mothers.

Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Labelling according to Regulation (EC) No 2004/42

VOC limit according to 2004/42/EC for category j (SB) and maximum VOC content: see lid.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 15)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 14)

The given conditions of work of the user extract themselves from our knowledge and control. The product/the preparation may be used without written permission for no other use, than the mentioned intended purpose. The user is responsible for the observance of all necessary legal instructions.

This Safety Data Sheet replaces all previous versions. With the newest version in each case, the preceding Safety Data Sheets are set out of strength.

For further information please consult the "Technical Data Sheet".

Misuse may cause damage to health and environment.

Labelling according to regulation (EC) No 528/2012

Additional information:

Contains epoxy constituents. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	On basis of test data	
Skin corrosion/irritation Serious eye damage/eye irritation Skin sensitisation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Abbreviations and acronyms:

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 16)



according to 1907/2006/EC, Article 31

Printing date 04.03.2022 Version number 03-01 Revision: 04.03.2022

Trade name: CWS WERTLACK® Epoxi-Grund

(Contd. of page 15)

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

DE/EN -