

tesa® 51960, 07239



Product Information

Carpet laying tape for professional users- removable -

tesa® 51960 is a double-sided carpet laying tape. The open side is largely residual-free removable from many surfaces and consists of PP-film with an acrylic adhesive. The different adhesion value is tailor-made for carpet laying applications and guarantees a very high tack on many commonly used surfaces.

tesa® 51960 is most extensively resistant to ageing and plasticisers (no discoloration of PVC or CV-floorings). The side with the higher adhesion is covered with a white liner.

Main Application

Border and butt joints of floor coverings based on foam or textile woven backings as well as PVC and CV-floorings on most surfaces.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PP film reinforced by fabric	• Type of adhesive	tackified acrylic
• Colour	translucent	• Elongation at break	80 %
• Total thickness	248 µm	• Tensile strength	30 N/cm

Adhesion to

• Steel (initial)	4.7 N/cm	• PP (covered side, initial)	4.2 N/cm
• Steel (covered side, initial)	9.0 N/cm	• Steel (after 14 days)	6.6 N/cm
• PE (initial)	3.0 N/cm	• Steel (covered side, after 14 days)	13.7 N/cm
• PE (covered side, initial)	4.5 N/cm	• PE (after 14 days)	3.5 N/cm
• PP (initial)	3.5 N/cm	• PE (covered side, after 14 days)	5.1 N/cm

Properties

• Temperature resistance short term	120 °C	• Resistance to chemicals	●●●●
• Temperature resistance long term	60 °C	• Softener resistance	●●
• Tack	●●●	• Static shear resistance at 23°C	●●
• Humidity resistance	●●●●	• Static shear resistance at 40°C	●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

According to DIN 18365 the surface has to be even, clean, permanently jointed and dry as well as free of oil or wax.

(Not suitable for natural stone)

tesa® 51960, 07239

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>