

tesa® Professional 4688 Cloth Tape 55 Mesh



Product Information

Standard polyethylene coated cloth tape

tesa® 4688 is a standard cloth tape with a PE-extruded substrate and a natural-rubber adhesive mass. This combination forms the basis for easy handling: the tape is easy to unroll and simple to tear by hand. The repair tape is strong but also sufficiently flexible to be a reliable aid to craftsmen. It can be used for a variety of applications and offers very good adhesion even on rough surfaces. The waterproof and ageing-resistant duct tape is available in seven colours: black, white, blue, yellow, red, silver/matt and green.

Features

- Indoor and outdoor applications
- Bonding of construction films
- Bundling of cables
- Repairing, packaging, protection, marking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PE extruded cloth	• Tensile strength	52 N/cm
• Total thickness	260 µm	• Temperature resistance short term	110 °C
• Type of adhesive	natural rubber	• Temperature resistance (30 min)	110 °C
• Elongation at break	9 %	• Mesh	55 count per square inch

Adhesion to

- steel 3.4 N/cm

Properties

• Hand tearability	●●●	• Ageing resistance (UV)	●●●
• Straight tear edges	●●●	• Humidity resistance	●●●
• Certified according to TLV 9027/01/06 for use in nuclear power plant	●●●	• UV-resistance	●●●
		• Water resistant	●●●
		• Fluorescent	no
		• Conformability	●●●
• Suitable for sensitive surfaces	●		
• Suitable for rough surfaces	●●●		
• Tack	●●●		
• Abrasion resistance	●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit
<http://l.tesa.com/?ip=04688>

tesa® Professional 4688 Cloth Tape 55 Mesh



Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04688>