

tesa® PRO 66958

Mounting Universal



Product Information

tesa PRO Mounting Universal - Strong and double-sided tape - Ideal for indoor use - Simple solution for fixing lighter objects - Hand tearable

tesa PRO Mounting Universal

tesa PRO Mounting Universal is a must-have, multi purpose tape for every professional craftsman or -woman working in indoor spaces. Fix light objects such as cable channels, stucco mounting and skirting, secure and permanently on most surfaces without leaving holes or damages in the wall structure. tesa PRO Mounting Universal is a true all-rounder! The smart solution for a quick and easy assignment.

Apply in vertical strips and along the full length of the object or surface. Press firmly for five seconds on dirt- and dust-free surface.

Features

- *Durable and resistant: Long-term temperature resistance at 40 degrees and short-term resistance at 60 degrees
- *Reliable hold without damaging the wall structure: tesa PRO Mounting Universal doesn't require the use of screws, plugs or nails - for fast and easy mounting with no tools necessary
- *Ideal for interior use: Strong double-sided adhesive tape for secure fixing of lighter objects such as cable channels, stucco mounting and skirting - compensates slightly rough surfaces
- *Easy to use: The mounting tape can be cut into individual small or large pieces for an adhesive strip in the optimized size
- *Scope of delivery: 1 x tesa PRO Mounting Universal tape - Dimensions: 1,5 m x 19 mm - Strong and double-sided - Material: Adhesive: Synthetic rubber, Backing: PE-foam

Application

Easy to apply:

- In order for the mounting tape to develop its full holding power, the object and surface must be free of dust, dirt and grease.
- Don't touch the open adhesive surface as it could impair the adhesive strength.
- Apply in vertical strips and along the full length of the object or surface.
- Press firmly for five seconds.
- For removal, carefully pull the mounting tape parallel from the wall. As the mounting tapes are intended for permanent use, material residues may remain on the object. Try to remove with tesa adhesive remover.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PE foam	• Tensile strength	7 N/cm
• Colour	white	• Type of liner	glassine
• Total thickness	1050 µm	• Colour of liner	yellow
• Type of adhesive	synthetic rubber	• Thickness of liner	70 µm
• Elongation at break	200 %	• Weight of liner	80 g/m ²

For latest information on this product please visit
<http://l.tesa.com/?ip=66958>

tesa® PRO 66958

Mounting Universal



Product Information

Adhesion to

• Steel (initial)	4.0 N/cm	• Steel (after 14 days)	4.0 N/cm
• PC (initial)	4.0 N/cm	• PC (after 14 days)	4.0 N/cm
• PE (initial)	4.0 N/cm	• PE (after 14 days)	4.0 N/cm
• PET (initial)	4.0 N/cm	• PET (after 14 days)	4.0 N/cm
• PP (initial)	4.0 N/cm	• PP (after 14 days)	4.0 N/cm
• PVC (initial)	4.0 N/cm	• PVC (after 14 days)	4.0 N/cm

Properties

• Temperature resistance short term	60 °C	• Resistance to chemicals	●●
• Temperature resistance long term	40 °C	• Softener resistance	●●
• Tack	●●●	• Static shear resistance at 23°C	●●●●
• Ageing resistance (UV)	●●	• Static shear resistance at 40°C	●●
• Humidity resistance	●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=66958>