

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)
Article number : 0062__000 **Version (Revision) :** 9.0.0 (8.0.0)
Revision date : 22.07.2020 **Print date :** 22.07.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH) (0062__000)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Products Category [PC]

PC9a - Coatings and paints, thinners, paint removers

Sectors of use [SU]

SU21 - Consumer uses: Private households (= general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

PUFAS Werk KG

Street : Im Schedetal 1

Postal code/city : 34346 Hann. Münden

Telephone : +49 (0)5541 7003-01

Telefax : +49 (0)5541 7003-50

Information contact :

E-mail (competent person) : sds@pufas.de

Website : www.pufas.de

1.4 Emergency telephone number

+49 (0)5541 7003-41/-64

Only available during office hours (Mo-Th 8 - 16 h, Fr 8 - 12.30 h).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 3 ; H412 - Hazardous to the aquatic environment : Chronic 3 ; Harmful to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

STOT RE 2 ; H373 - STOT-repeated exposure : Category 2 ; May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Exclamation mark (GHS07)

Signal word

Danger

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)

Article number : 0062_000 **Version (Revision) :** 9.0.0 (8.0.0)

Revision date : 22.07.2020 **Print date :** 22.07.2020

Hazard components for labelling

HYDROCARBONS, C9-C11, N_ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; CAS No. : 64742-48-9
HYDROCARBONS, C9, AROMATICS ; CAS No. : 64742-95-6
HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1

Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/eye protection.
P260 Do not breathe vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P101 If medical advice is needed, have product container or label at hand.
P273 Avoid release to the environment.
P501 Dispose of contents/container in accordance with local/regional/national regulations of waste disposal.

Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This mixture does not contain any substances classified as PBT/vPvB or included in the SVHC-Candidate List.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description

Consist of: Styrene-acrylic-resin, solvent

Hazardous ingredients

HYDROCARBONS, C9-C11, N_ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; REACH No. : 01-2119463258-33 ;
EC No. : 919-857-5; CAS No. : 64742-48-9

Weight fraction : ≥ 60 - < 70 %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336

HYDROCARBONS, C9, AROMATICS ; REACH No. : 01-2119455851-35 ; EC No. : 918-668-5; CAS No. : 64742-95-6

Weight fraction : ≥ 10 - < 15 %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H335 STOT SE 3 ; H336
Aquatic Chronic 2 ; H411

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; REACH No. : 01-2119458049-33 ;
EC No. : 919-446-0; CAS No. : 64742-82-1

Weight fraction : ≥ 10 - < 10,5 %
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT RE 1 ; H372 STOT SE 3 ; H336
Aquatic Chronic 2 ; H411

Additional information

Full text of H- and EUH-phrases: see section 16.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name :	Deeply-Penetrating Primer LH - Universal (solvent-based) (Universal Tiefengrund LH)		
Article number :	0062__000	Version (Revision) :	9.0.0 (8.0.0)
Revision date :	22.07.2020	Print date :	22.07.2020

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Notice the directions for use on the label. When in doubt or if symptoms are observed, get medical advice. Change contaminated, saturated clothing.

Following inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Do NOT induce vomiting. Call a physician in any case!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist alcohol resistant foam Carbon dioxide (CO₂) Extinguishing powder

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

The usual precautionary measures for the handling of chemicals have to be observed. Provide adequate ventilation. Remove all sources of ignition. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name :	Deeply-Penetrating Primer LH - Universal (solvent-based) (Universal Tiefengrund LH)		
Article number :	0062__000	Version (Revision) :	9.0.0 (8.0.0)
Revision date :	22.07.2020	Print date :	22.07.2020

6.4 Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Normal precautions taken when handling chemicals should be observed. Avoid contact with skin and eyes. Keep away from food, drink and animal feeding stuffs.

Measures to prevent fire

Only use the material in places where open light, fire and other flammable sources can be kept away. Provide adequate ventilation as well as local exhaustion at critical locations. Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed.

Further information on storage conditions

Do not store outside. Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Please note safety instructions and directions for use on the drum.

Recommended storage temperature : Store it separately from foods.

7.3 Specific end use(s)

Recommendation

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

None

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

goggles

Skin protection

Hand protection

Gloves(tested for example according to EN374) made of the following materials used by hand contact with the product:

Nitrile rubber (NBR)

Thickness of the gloves: > 0.4 mm

Breakthrough time: >= 8h

After washing hands replace lost skin fat by fat containing skin creams.

Body protection

Wearing of closed working clothes. Remove contaminated, saturated clothing.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)

Article number : 0062_000 **Version (Revision) :** 9.0.0 (8.0.0)

Revision date : 22.07.2020 **Print date :** 22.07.2020

Respiratory protection

Suitable respiratory protection apparatus

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

General information

The usual precautionary measures for the handling of chemicals have to be observed. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Environmental exposure controls

See also section 6 and 12.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid

Colour : colourless

Odour

Turpentine

Safety characteristics

Melting point/freezing point :	(1013 hPa)	No data available
Initial boiling point and boiling range :	(1013 hPa)	145 - 200 °C
Flash point :		40 °C Brookfield
Auto-ignition temperature :		265 °C
Lower explosion limit :		0,7 Vol-%
Upper explosion limit :		6,4 Vol-%
Vapour pressure :	(20 °C)	3 hPa
Density :	(20 °C)	0,82 g/cm ³
Water solubility :	(20 °C)	practically insoluble
Cinematic viscosity :	(40 °C)	< 20,5 mm ² /s
Solid content :		12,5 Wt %
Solvent content :		87,3 Wt %
VOC-value :		745 g/l

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

None, if handled according to order.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)

Article number : 0062_000 **Version (Revision) :** 9.0.0 (8.0.0)

Revision date : 22.07.2020 **Print date :** 22.07.2020

10.6 Hazardous decomposition products

Gases/vapours, flammable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

No data available

Acute oral toxicity

Parameter : ATEmix calculated

Exposure route : Oral

Effective dose : > 2000 mg/kg

Parameter : LD50 (HYDROCARBONS, C9-C11, N_ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; CAS No. : 64742-48-9)

Exposure route : Oral

Species : Rat

Effective dose : > 5000 mg/kg

Parameter : LD50 (HYDROCARBONS, C9, AROMATICS ; CAS No. : 64742-95-6)

Exposure route : Oral

Species : Rat

Effective dose : > 2000 mg/kg

Parameter : LD50 (HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Oral

Species : Rabbit

Effective dose : > 2000 mg/kg

Acute dermal toxicity

Parameter : ATEmix calculated

Exposure route : Dermal

Effective dose : > 2000 mg/kg

Parameter : LD50 (HYDROCARBONS, C9-C11, N_ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; CAS No. : 64742-48-9)

Exposure route : Dermal

Species : Rabbit

Effective dose : > 5000 mg/kg

Method : OECD 402

Parameter : LD50 (HYDROCARBONS, C9, AROMATICS ; CAS No. : 64742-95-6)

Exposure route : Dermal

Species : Rabbit

Effective dose : > 2000 mg/kg

Parameter : LD50 (HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Dermal

Species : Rabbit

Effective dose : > 2000 mg/kg

Acute inhalation toxicity

Parameter : ATEmix calculated

Exposure route : Inhalation

Effective dose : > 20 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)

Article number : 0062__000 **Version (Revision) :** 9.0.0 (8.0.0)

Revision date : 22.07.2020 **Print date :** 22.07.2020

Parameter : LC50 (HYDROCARBONS, C9-C11, N_ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; CAS No. : 64742-48-9)

Exposure route : Inhalation

Species : Rat

Effective dose : > 21 mg/l

Exposure time : 4 h

Method : OECD 403

Parameter : LC50 (HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1)

Exposure route : Inhalation

Species : Rat

Effective dose : > 13100 mg/l

Exposure time : 4 h

Additional information

This product is unlikely to harm health, given normal and proper handling and hygienic precautions.

Corrosion

No data available

Skin corrosion/irritation

Parameter : Skin corrosion/irritation (HYDROCARBONS, C9, AROMATICS ; CAS No. : 64742-95-6)

Parameter : Human

Result : no skin irritation

Serious eye damage/eye irritation

Parameter : Serious eye damage/eye irritation (HYDROCARBONS, C9, AROMATICS ; CAS No. : 64742-95-6)

Parameter : Human

Result : irritates

Additional information

The liquid slightly irritates the skin, vapours in higher concentration irritate eyes and respiration.

Respiratory or skin sensitisation

No data available

Repeated dose toxicity (subacute, subchronic, chronic)

No data available

Additional information

No known symptoms to date.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No data available

Germ cell mutagenicity

No data available

Reproductive toxicity

No data available

Overall Assessment on CMR properties

No known symptoms to date.

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

Harmful: may cause lung damage if swallowed.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)
Article number : 0062__000 **Version (Revision) :** 9.0.0 (8.0.0)
Revision date : 22.07.2020 **Print date :** 22.07.2020

Phototoxicity

Additional information

No known symptoms to date.

SECTION 12: Ecological information

12.1 Toxicity

No information available.

Aquatic toxicity

Acute (short-term) toxicity to aquatic algae and cyanobacteria

Parameter : EC50 (HYDROCARBONS, C9, AROMATICS ; CAS No. : 64742-95-6)
Species : Fish
Effective dose : 1 - 10 mg/l
Parameter : EC50 (HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS
(2-25%) ; CAS No. : 64742-82-1)
Species : Daphnia magna (Big water flea)
Exposure time : 48 h

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances classified as PBT/vPvB or included in the SVHC-Candidate List.

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

Additional information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation. Handle contaminated packages in the same way as the substance itself.

Waste codes/waste designations according to EWC/AVV

Waste code product

Not used:

08 01 11

Drying up:

08 01 12

or

17 09 04

Waste name

Not used:

waste paint and varnish containing organic solvents or other dangerous substances

Drying up:

waste paint and varnish other than those mentioned in 08 01 11

or

mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)
Article number : 0062__000 **Version (Revision) :** 9.0.0 (8.0.0)
Revision date : 22.07.2020 **Print date :** 22.07.2020

Waste code packaging

15 01 02
or
15 01 04

Waste name

plastic packaging
or
metallic packaging

SECTION 14: Transport information

14.1 UN number

UN 1866

14.2 UN proper shipping name

Land transport (ADR/RID)

RESIN SOLUTION

Sea transport (IMDG)

RESIN SOLUTION

Air transport (ICAO-TI / IATA-DGR)

RESIN SOLUTION

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / ~~S-E~~
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

14.8 Additional information

The ADR-classification is not applying to our assembled packing (see ADR 3.4. LQ 5 I) => limited Quantity

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Deeply-Penetrating Primer LH - Universal (solvent-based)
(Universal Tiefengrund LH)
Article number : 0062__000 **Version (Revision) :** 9.0.0 (8.0.0)
Revision date : 22.07.2020 **Print date :** 22.07.2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

- this product is not subject to EC Detergent regulation no. 648/2004.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

Directive (2004/42/CE) - Classification:

- EU-VOC-Grenzwert für dieses Produkt(Kat.: A/h, Lb) = 750 g/l (2010)

- VOC-Gehalt dieses Produktes max.: 745 g/l

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3 Additional information

None

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.