

Glutolin CF – Crystal Finish Decorative coatings for interior use

Instructions for use:	<i>Glutolin CF Crystal Finish</i> is an acrylate based effect coating with nacre-effect. Suitable for interior ceiling and wall coatings on wallpapers, colours, brick, masonry, finery, Styrofoam and similar surfaces.	
Technical specifications:	Components:	Styrol-Acrylic- Dispersion, additive
	Density:	approx. 1.4 g/cm ³
	Consumption:	1 litre for 3 m ²
	Colour	White nacre
Surface preparation:	The surface must be dry, firm and free of release agents (dust, formwork release oil, etc.) Remove all traces of loose plaster, flaking paint residues and old coats of distemper paint using <i>Glutosolv TA Wallpaper Remover</i> .	
	Prime highly absorbent, sanding and chalking surfaces using <i>Glutogrund LF Deeply Penetrating Primer</i> . We recommend to use <i>Glutogrund TP White</i> or emulsion paint before applying <i>Glutolin CF Crystal Finish</i> .	
Application:	Glutolin CF Crystal Finish is ready to use and can be applied using a brush or spatula.	
	Do not use if the surface and/or room temperature are below + 5° Celsius! Clean tools in water immediately after use.	
Storage:	Store in a cool, but frost-free place! Keep containers tightly sealed!	
Important information:	Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)	
Available size:	Tub 2.5 Art. no. 017601074	