

Oil Stain Remover Oelflecken Entferner

Description

Eliminates engine oil, diesel and heating oil stains. Also for deep-seated and old stains. For all absorbent and non-absorbent surfaces.

Action

For dissolution and deep-acting removal of mineral and synthetic oil stains as well as contaminations containing oil and grease. Suitable for old and stubborn residues. Long contact time (of the oil stain remover) through gel-like consistency.

Scope of application

For application on all absorbent and non-absorbent surfaces. For garages, driveways, roads, paths and other surfaces of natural stone, cast stone, cement screed, concrete and asphalt as well as glass, tiles, metal, glazed and unglazed ceramic, clinker, paving.

Also for workshops, motor vehicles, tools and machinery.

Application

Apply on dry surfaces only. Apply a thick layer of oil stain remover onto the contamination and distribute it on the stain using a brush or broom. Leave to soak several hours (preferably overnight) depending on degree of contamination.

The result is a light-coloured powder layer which can be brushed away afterwards. In case of particularly stubborn or deep-seated contamination in the substrate repeat the work step if necessary.

Please note

Do not apply on plastic surfaces. Minor residues may remain after sweeping off the light-coloured powder layer, especially on dark surfaces, but they will disappear by themselves after a while. If desired, these residues can be instantly removed using the Glutoclean Grease, Wax and Dirt Remover.

Technical data

- Density: 0.81 g/ml
- pH value: n.a.
- Appearance: clear liquid
- Odour: characteristic

Safety notes

- Flammable.
- Harmful: May cause lung damage if swallowed.
- Repeated exposure may cause skin dryness or cracking.
- Vapours may cause drowsiness and dizziness.
- Keep out of the reach of children.
- Do not inhale vapour.
- Avoid contact with skin and eyes.
- Use only in well-ventilated areas.

Info Telephone: +49 (0) 55 41 / 70 03 - 491

Packaging unit

500 ml tray (6 pcs. in carton)

Order no. 390 381

There is a huge diversity of application conditions and areas of applications of our products. Therefore, we can only give general instructions for use in the product information concerned. They can and shall only give general advice. Check and adapt the use of the products to local conditions and the surfaces to be treated. Always pre-test the products on an inconspicuous area in all cases of doubt or in absence of experience. We would be happy to offer you advice if you have special requirements.

We shall only be liable for incomplete or incorrect technical data in case of gross default on our part (wilful misconduct or gross negligence).