

Stone Sealing Stein Versiegelung

Description

For inside and out. Dirt and water-repellent. Semi-gloss appearance.

Action

Sealing with long-time protection for the stone. Thanks to the waterproof, UV-resistant protective semi-gloss coat, the treated surface will become dirt-repellent and carefree. The stone's appearance, colour and structure are improved and remain intact in the long-term. The protective coat is non-yellowing and durable.

Scope of application

For all absorbent natural and artificial stone surfaces in indoor and outdoor areas, cast stones, washed concrete, slate, marble, sandstone, terrazzo, porphyry, Solnhofen tiles, concrete surfaces and the like.

For treatment of floors, stairs and window sills as well as terrace and balcony.

Application

Apply on dry surface only. Clean the surface beforehand. Apply the sealing thinly and evenly using a paint roller or brush. In the process, do not apply more liquid than can be absorbed by the surface.

Do not apply excessively so as to avoid ponding. No streaks should develop. The following drying time is about 2 hours. Do not step on the area during this drying phase. Afterwards, protect the sealed surface from effect of moisture for 2 days.

Please note

Surfaces to be sealed must be dry without fail. White spots after drying indicate moisture in the stone. The flooring areas must be protected against reverse moisture penetration from the underground. Always work in sections on large areas. Cover glass and surfaces sensitive to solvents during the application. Do not process at temperatures below 12 °C.

Non-absorbent, polished or finely polished surfaces cannot be sealed.

Technical data

- Density: 0.78 g/ml
- pH value: n.a.
- Appearance: clear liquid
- Odour: characteristic

Consumption/range

Sufficient for 15-20 m².

Safety notes

- Harmful, dangerous for the environment
- Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Harmful: May cause lung damage if swallowed.
- Repeated exposure may cause skin dryness or cracking.
- Vapours may cause drowsiness and dizziness.
- Keep out of the reach of children.
- Do not inhale vapour.
- Do not empty into drains; dispose of this product and its container at hazardous or special waste collection point.
- If swallowed, do not induce vomiting. Seek medical advice immediately and show this container or label.

Info Telephone: +49 (0) 55 41 / 70 03 - 491

Packaging unit

1000 ml metal canister (4 pcs. in carton)

Order no. 390 354

There is a huge diversity of application conditions and areas of applications of our products. Therefore, we can only give general instructions for use in the product information concerned. They can and shall only give general advice. Check and adapt the use of the products to local conditions and the surfaces to be treated. Always pre-test the products on an inconspicuous area in all cases of doubt or in absence of experience. We would be happy to offer you advice if you have special requirements.

We shall only be liable for incomplete or incorrect technical data in case of gross default on our part (wilful misconduct or gross negligence).