

PUFAS MC Wallpaper Adhesive G20 for pasting machines - instant

PUFAS MC Gerätekleister G 20 instant

High quality, quick-dissolving, pasting machine adhesive made from methyl cellulose and synthetic resin.

Instructions for use: *PUFAS MC Wallpaper Adhesive G20 for pasting machines - instant* is ideally suited for reliable, secure pasting of vinyl wallpapers, structured vinyl wallpapers, woodchip wallpapers, heavyweight paper wallpapers, embossed wallpapers, textile wallpapers and similar wall coverings. Ideally suited for use with standard commercial wallpapering machines.

Technical specifications:

Components:	methyl cellulose, synthetic resin powder
Density:	0.55 g/cm ³
pH-value:	approx. 8
Solubility:	ready to use in approx. 5 minutes
Usage:	approx. 200 ml/m ²

Surface preparation: The surface must be dry, firm and free of dust and grease. Remove old, peeling wallpapers and distemper paints using *PUFAS Wallpaper Remover*. Make good cracks and holes using *PUFAS Interior* or *PUFAMUR Super Bonding Filler*. Prime highly absorbent, sanding and chalking surfaces with *PUFAS Deeply-Penetrating Primer – solvent free*.

Water-soluble contaminations in the surface, which could show through when wallpapered over, should be isolated using *PUFAS Insulating Spray White*. To make a subsequent change of wallpaper easier, we recommend priming the surface with *PUFAS Wallpaper Base Primer 'Tapeten-Wechselgrund'*, especially when hanging washable wallpapers.

Instructions for use: Stirring vigorously, sprinkle *PUFAS MC Wallpaper Adhesive G20 for pasting machines – instant* into clean, cold water (see table) and continue to stir for a few minutes. Leave for 5 minutes and then stir vigorously again.

Apply the adhesive to the wallpaper using a wallpapering machine or brush, fold the pasted ends inwards and hang after an adequate soaking time. Always observe the wallpapering machine and wallpaper manufacturer's instructions for use.

We recommend to add approx. 20 % *PUFAS Wallpaper and Border Adhesive* for use on hardly absorbent surfaces and to increase the moisture resistance.

Do not use if the object and/or room temperature are below + 5° Celsius!
Clean tools with water immediately after use.
Remove adhesive residues using a damp cloth

Mixing ratio:

for	Mixing ratio	Quantity of water per 750 g packet	Coverage of a 750 g packet
Pre-pasting	1:40	30 l	approx. 250-300 m ²
Wallpapering machine	1:20	15 l	approx. 75 m ²
Woodchip wallpaper	1:20	15 l	approx. 75 m ²
Heavy wallpapers, textile, embossed + vinyl wallpapers	1:20	15 l	approx. 75 m ²

Storage: Store in a cool and dry place!

Available sizes:

300 g collapsible box	022601000
750 g collapsible box	022602000