

## PufaMIX Universal concentrated colorants

Universal pigment concentrate in 32 shades for water and solvent-based paint systems

### Instructions for use

*PufaMIX Universal concentrated colorants* are ideally suited for tinting standard commercial, diluted emulsion, binder, and latex paints, synthetic resin plasters, acrylic varnishes, alkyd resin varnishes, nitrocellulose lacquers and similar paint systems. Furthermore, they are suitable for tinting scumble coats, wood stainers, wood waxes and cement paints.

The shades denoted with "L" in the colour card (No. 6, 7, 10, 18) are only for indoor use, those denoted with "LW" are for both indoor and outdoor use. Only the oxide colours (No. 3, 4, 5, 14, 19, 20, 21, 22, 23, 24, 29, 30, 31, 32) can be used for tinting silicate paints for outdoor use and low-aromatic compound and aromatic-free paints.

### Technical specifications:

Components: Inorganic and organic pigments, dispersed in water and propylene glycol  
 Density: 1.15-1.90 g/cm<sup>3</sup> (depending on the shade)  
 pH-value: approx. 6.5-7.50

### Application:

Shake the bottle well before use.

Add *PufaMIX Universal concentrated colorants* to the paint to be tinted and mix thoroughly until fully homogeneous. We recommend using a stirring machine when tinting varnishes.

The basic rule is: Always try out first and carry out a rub off test! First tint – then thin!

The following maximum added quantities are to be observed for the various paint systems.

<b>Emulsion paints</b>	<b>max. 10 %</b>
<b>Acrylic varnishes</b>	<b>max. 6 %</b>
<b>Alkyd resin varnishes</b>	<b>max. 8 %</b>
<b>Synthetic resin plasters</b>	<b>max. 10 %</b>
<b>Scumble coats</b>	<b>max. 5 %</b>

All *PufaMIX Universal concentrated colorants* can be mixed with each other.

Clean tools with water immediately after use.

### Storage:

Store in a cool and frost-free place! Keep the containers tightly sealed!

### Available sizes:

20 ml PE bottle	07xx01000
200 ml PE bottle	07xx02000
500 ml PE bottle	07xx03000

There is a huge diversity of application conditions and areas of applications of our products. Therefore, we can only give general instructions for use in the product information concerned. They can and shall only give general advice. Check and adapt the use of the products to local conditions and the surfaces to be treated. Always pre-test the products on an inconspicuous area in all cases of doubt or in absence of experience. We would be happy to offer you advice if you have special requirements. We shall only be liable for incomplete or incorrect technical data in case of gross default on our part (wilful misconduct or gross negligence).