

PUFAS Siloxane Façade Paint



- scrub-resistant facade coating
- with long-term film protection against algae and green growth
- highly water-repellent
- high water vapour permeability
- low-stress
- alkali- and ageing-resistant

Instructions for use:

PUFAS Siloxane Façade Paint is suitable for all outdoor high-grade coverings on mineral surfaces, such as concrete, clay tiles, lime and cement plaster as well as for coats of immersion paint. *PUFAS Siloxane Façade Paint* is also suitable for interior areas subjected to high wear. Against algae and fungus fouling, *PUFAS Siloxane Façade Paint* protects itself through an internal protecting film.

Technical specifications:

Components:	Plastic-dispersion, titanium dioxide, extenders, water and additives
Density:	1.56 g/cm ³
pH-value:	9,5-10
Contrast ratio according to EN 13300:	Class 2 at a coverage of 7 m ² /l
Gloss level according to EN 13300 :	dull matt
Wet Scrub resistance according to EN 13300:	Class 2
Usage:	150-200 ml/m ² per coat

Surface preparation:

The surface must be dry, firm and free of release agents (dust, oil, mould, algae, etc.). Clean areas affected by mould or algae using *PUFAS Algae and Mould STOP* and final cleaning using clear water. Prime highly absorbent, sanding and chalking surfaces with *PUFAS Deeply Penetrating Primer – Solvent Free* or *LH*. Fill and smooth cracks, holes and unevenness using *PUFAS Exterior* or *Pufamur Exterior Façade Filler*. Water-soluble contamination of the surface, which could show through when painted over with emulsion paint should be isolated using *PUFAS Insulating Spray White*.

Application:

Apply *PUFAS Siloxane Façade Paint* using a paint roller, brush or an airless method.

Depending on the absorbency of the surface, the paint can be thinned with max. 10 % water for the first coat. After the first coat has dried the second coat should be applied unthinned.

Clean tools with water immediately after use.

Do not use on surfaces or in rooms below + 5° Celsius!

Important information:

Please consult safety data sheet for safety-relevant data.

Storage:

Store in a cool, but frost-free place! Keep container tightly closed!

Available sizes:

2.5 l PE oval tub	014302000 / EAN 4007954143025
5 l PE oval tub	014303000 / EAN 4007954143032
10 l PE oval tub	014304000 / EAN 4007954143049