

PUFAS Roof and Plinth Paint

Dach- und Sockelfarbe

Weather resistant, solvent-free synthetic resin emulsion paint in 11 shades for use indoors and outdoors.

Instructions for use: PUFAS Roof and Plinth Paint is suitable for painting pantiles made from clay

and concrete, fibre cement roofs, roof underviews as well as for house bases made from cement, synthetic resin plaster, concrete and similar mineral surfac-

es.

Technical specifications: Components: Synthetic resin emulsion, coloured pigments

Density: approx. 1.4 g/cm³

pH-value: 8-9 Gloss unit

according to EN 53778:

Scrubbing cycles

according to EN 133300: > 5,000 DH, scrub resistant to EN 53778

Consumption: 150-200 ml/m² per coat

Surface preparation: The surface must be dry, firm, dust and grease free. Remove flaking coats of

paint and plaster. If the surface is affected by algae and moose, clean the area with PUFAS STOP Algae and Mould. Make good cracks and holes using PUFAS Exterior or PUFAMUR Exterior Façade Filler. Prime highly absorbent, sanding and chalking surfaces with PUFAS Deeply-Penetrating Primer LF or

LH. Apply an undercoat of PUFAS Isolation Paint to new eternit roofs.

Neutralize alkaline, chalky and cement-containing surfaces with OLAFIRN

Protect the base from moisture out of the ground or from the inside to guarantee

good adhesion of the coat.

Application: PUFAS Roof and Plinth Paint is ready to use and can be applied using a brush,

paint roller or standard airless devices. The paint can be thinned with approx. 5 % water for the primer coat. After the first coat has completely dried, apply one

or two un-thinned coats of paint as needed.

PUFAS Roof and Plinth Paints can be mixed with each other and with white

façade paints. Only use full colour for painting roofs.

Do not use if the surface and /or room temperature are below + 5° Celsius!

Clean tools in water immediately after use.

Important information: Please see the EU Safety Data Sheet for all safety-related data (EU-CLP).

Storage: Store in a cool but frost-free place! Keep the containers tightly sealed!

Available sizes: 2,5 I oval PE tub 09xx07000

5.0 I oval PE tub 09xx05000 12.5 I oval PE tub 09xx06000