



Professional dust extractor range completes the dust-free experience

When you're sanding with professional tools and high-class abrasives you need dust extraction that is up to par. Mirka's 1230/1242 dust extractor range is that and more: equipped with a high-performance 1200 W motor and a 1-stage turbine that creates 250 mbar suction with an airflow of 4500 l/min. The 1230 models have a 30-litre dust container and the 1242 a larger, 42-litre container. A wide range of accessories is available that fit all models.

- Mirka® Dust Extractor 1230 L PC
- Mirka® Dust Extractor 1230 L AFC
- Mirka® Dust Extractor 1230 M AFC
- Mirka® Dust Extractor 1242 M AFC

Advantages with automatic filter cleaning

- Less maintenance
- Constant performance
- Possibility to work without dust bags

All dust extractors have an auto-start function, which means not just less noise but an overall longer lifetime for the dust extractor. For the push-to-clean model, a simple push of a button is needed to clean the filter. If it needs to be removed, the filter is easy to reach through a separate opening in the back. Dust extractors equipped with an automatic filter cleaning system (AFC) are available in M (medium) and L (light) dust class. The efficient filter cleans itself every 15 seconds which clearly improves the performance of the dust extractor. The HEPA filter, available as an accessory, is easy to install.

The flat top provides extra storage possibilities. Use the case fastening accessory to attach cases or the work station, which has shelves and hooks.





Technical features Mirka® Dust Extractor 1242 M AFC

Easily accessible flat filter

Filter can easily be reached through an opening in the back.

Automatic Filter Cleaning

Keeps the filter automatically clean for better performance and longer lifetime.

High volume container

42 litres for applications where a lot of material is extracted.

Large wheels

Easy manoeuvrability on uneven surfaces.

High performance motor and turbine

1200 W motor and 1-stage turbine creates 250 mbar pressure and 4500 l/min airflow.

Cable storage

Durable strap keeping the cable in place during transportation.

M-class

Proven performance for higher user protection.

Hose storage

The hose is always ready for use.

Air intake filter

Longer lifetime of motor.

AutoStart function

Dust extractor runs only when the power tool is running.

Airflow sensor

Indicates when airspeed is below 20 m/s.

Hose inlet plug

Eliminates the risk of dust leaking out during transportation.



Technical specifications	Dust Extractor 1230 L/M	Dust Extractor 1242 M AFC
Voltage mains supply	220 – 240 V ~	220 – 240 V ~
Mains frequency	50/60 Hz	50/60 Hz
Power input	1200 W	1200 W
Volume flow air	4500 l/min	4500 l/min
Vacuum	250 mbar	250 mbar
Noise level, LpA	60 dBA	60 dBA
Container volume	30 l	42 l
Dimension W x D x H	385 x 565 x 565 mm	385 x 565 x 607 mm
Weight	14.5 kg	16.0 kg

For more information please visit www.mirka.com and check our videos on the Mirka YouTube channel

Mirka Ltd Finland

