

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021
Print Date: 13-Jan-2023

Revision Number: 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name: **Mega 406 Siloxan-Elast Fassadenfarbe**
Article number: 026070540514
UFI: MP5W-QGCA-C70A-JASP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product categories [PC]: PC9 - Coatings and paints, fillers, putties, thinners
Sector of uses [SU]: SU19 - Building and construction work

1.3. Details of the supplier of the safety data sheet

Supplier: MEGA eG
Fangdieckstrasse 45
D - 22547 Hamburg
Telefon: +49 40/ 54004-0
Telefax: +49 40/ 54004-9
www.mega.de

Responsibility Statement: Department productsector paints and coatings
Telephone: 040 54004-528

E-mail address: technik@mega.de

1.4. Emergency telephone number

Emergency Telephone: +49 40 / 54004 - 528 (Mo. - Tue. 7.15 - 16.30 Uhr, Fr. bis 12.00 Uhr)

Emergency Telephone - §45 - (EC)1272/2008	
Europe	112
Austria	+43 1 406 43 43 (Giftinformationszentrale)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin sensitization	Category 1A - (H317)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Signal word: **Warning**

Hazard components for labeling:

Contains 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone, 1,2-Benzisothiazol-3(2H)-one, 3(2H)-Isothiazolone, 2-methyl-

Hazard statements:

H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements:

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary Statements - EU (§28, 1272/2008):

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Harmful to aquatic life.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	CAS No	EC No (EU Index No)	REACH registration number	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Weight-%
Kieselguhr, soda ash flux-calcined	68855-54-9	272-489-0	01-2119488518-22	STOT RE 2 (H373)	1 - < 3
Silica, cristobalite	14464-46-1	238-455-4	-	STOT RE 1 (H372)	0.25 - < 0.5
1,2-Benzisothiazol-3(2H)-one	2634-33-5	() 220-120-9	01-2120761540-60	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Eye Dam. 1 (H318) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	0.01 - < 0.05
2-Bromo-2-nitro-1,3-propanediol	52-51-7	200-143-0	01-2119980938-15	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	0.01 - < 0.05
3(2H)-Isothiazolone, 2-methyl-	2682-20-4	220-239-6	01-2120764690-50	Acute Tox. 3 (H301) Acute Tox. 3 (H311)	0.01 - < 0.05

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

				Skin Corr. 1B (H314) Skin Sens. 1A (H317) Eye Dam. 1 (H318) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	
Zinc pyrithione	13463-41-7	236-671-3	01-2119511196-46	Acute Tox. 3 (H301) Eye Dam. 1 (H318) Acute Tox. 2 (H330) Repr. 1B (H360D) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	0.005 - < 0.01
Terbutryn	886-50-0	212-950-5	-	Acute Tox. 4 (H302) Skin Sens. 1B (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	0.005 - < 0.01
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	55965-84-9	611-341-5 911-418-6	01-2120764691-48	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Skin Corr. 1B (H314) Skin Sens. 1A (H317) Eye Dam. 1 (H318) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	0.001 - < 0.005

Chemical name	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
2-Bromo-2-nitro-1,3-propanediol 52-51-7		10	1	
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	Skin Sens. 1A :: C>=0.0015%	10	1	
Zinc pyrithione 13463-41-7		1000	10	
Terbutryn 886-50-0	Skin Sens. 1B :: C>=3%	100	100	
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1A :: C>=0.0015%	100	100	

Acute Toxicity Estimate:

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE_{mix}) for classifying a mixture based on its components

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapor - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Kieselguhr, soda ash flux-calcined	2002	No data available	3	No data available	No data available

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

68855-54-9					
1,2-Benzisothiazol-3(2H)-one 2634-33-5	490	2000	0.0501	0.501	No data available
2-Bromo-2-nitro-1,3-propanedi ol 52-51-7	180	1600	No data available	No data available	No data available
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	120	242	0.34	0.501	No data available
Zinc pyrithione 13463-41-7	177	100	0.0501	3	No data available
Terbutryn 886-50-0	500	10210.2	9	No data available	No data available
5-Chloro-2-methyl-3(2H)-isothi azolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	457	660	0.0501	No data available	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Full text of H- and EUH-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice:	Show this safety data sheet to the doctor in attendance.
Inhalation:	Remove to fresh air.
Eye contact:	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin contact:	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion:	Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians: May cause sensitization in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

surrounding environment.

Large Fire:

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media:

Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical:

Product is or contains a sensitizer. May cause sensitization by skin contact.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters:

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

For emergency responders:

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions:

See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment:

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up:

Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards:

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections:

See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling



Advice on safe handling:

Handle in accordance with good industrial hygiene and safety practice. Avoid contact

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

General hygiene considerations: Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Other information: No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits:

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Kieselguhr, soda ash flux-calcined 68855-54-9		TWA: 0.3 mg/m ³			TWA: 2.4 mg/m ³ TWA: 6 mg/m ³
Silica, cristobalite 14464-46-1	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³
3(2H)-Isothiazolone, 2-methyl- 2682-20-4		TWA: 0.05 mg/m ³ Sh+			
5-Chloro-2-methyl-3(2H)-isot hiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9		TWA: 0.05 mg/m ³ Sh+			
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland
Silica, cristobalite 14464-46-1	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.15 mg/m ³ TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
Kieselguhr, soda ash flux-calcined 68855-54-9		TWA: 0.3 mg/m ³	TWA: 0.3 mg/m ³		
Silica, cristobalite 14464-46-1	TWA: 0.05 mg/m ³			TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
1,2-Benzisothiazol-3(2H)-one 2634-33-5			skin sensitizer		
2-Bromo-2-nitro-1,3-propane diol 52-51-7			* skin sensitizer		
3(2H)-Isothiazolone, 2-methyl- 2682-20-4			TWA: 0.2 mg/m ³ Peak: 0.4 mg/m ³ skin sensitizer		
Zinc pyrithione 13463-41-7			*		
5-Chloro-2-methyl-3(2H)-isot hiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9			MAK: 0.2 mg/m ³		
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania
Kieselguhr, soda ash	TWA: 1.2 mg/m ³				

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Revision Number: 1

Print Date: 13-Jan-2023

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

flux-calcined 68855-54-9	STEL: 3.6 mg/m ³				
Silica, cristobalite 14464-46-1	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
Kieselguhr, soda ash flux-calcined 68855-54-9					TWA: 2 mg/m ³ TWA: 1 mg/m ³
Silica, cristobalite 14464-46-1			TWA: 0.075 mg/m ³	TWA: 0.05 mg/m ³ TWA: 0.1 mg/m ³ TWA: 0.15 mg/m ³ STEL: 0.15 mg/m ³ STEL: 0.45 mg/m ³ STEL: 0.3 mg/m ³	TWA: 0.1 mg/m ³
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Kieselguhr, soda ash flux-calcined 68855-54-9				TWA: 0.3 mg/m ³	
Silica, cristobalite 14464-46-1	TWA: 0.025 mg/m ³	TWA: 0.05 mg/m ³		TWA: 0.1 mg/m ³	TWA: 0.05 mg/m ³
Chemical name	Sweden	Switzerland	United Kingdom	Russia	Turkey
Kieselguhr, soda ash flux-calcined 68855-54-9		TWA: 0.3 mg/m ³			
Silica, cristobalite 14464-46-1	NGV: 0.05 mg/m ³	TWA: 0.15 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.3 mg/m ³	TWA: 1 mg/m ³ MAC: 3 mg/m ³	
3(2H)-Isothiazolone, 2-methyl- 2682-20-4		S+ TWA: 0.2 mg/m ³ STEL: 0.4 mg/m ³			
5-Chloro-2-methyl-3(2H)-isot hiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9		S+ TWA: 0.2 mg/m ³			

Biological occupational exposure limits: This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL):

component information:

Worker - inhalative:

Chemical name	long term, systemic	short term, systemic	long term, local	short term, local
Kieselguhr, soda ash flux-calcined	0.05 mg/m ³			
1,2-Benzisothiazol-3(2H)-one	6.81 mg/m ³			
2-Bromo-2-nitro-1,3-propaned iol	3.5 mg/m ³	10.5 mg/m ³	2.5 mg/m ³	2.5 mg/m ³
3(2H)-Isothiazolone, 2-methyl-			0.021 mg/m ³	0.043 mg/m ³
5-Chloro-2-methyl-3(2H)-isoth iazolone, mixture with 2-methyl-3(2H)-isothiazolone			0.02 mg/m ³	0.04 mg/m ³

Worker - dermal:

Chemical name	long term, systemic	short term, systemic	long term, local	short term, local
1,2-Benzisothiazol-3(2H)-one	0.966 mg/kg bw/day			

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Revision Number: 1

Print Date: 13-Jan-2023

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Chemical name	long term, systemic	short term, systemic	long term, local	short term, local
2-Bromo-2-nitro-1,3-propaned iol	2 mg/kg bw/day	6 mg/kg bw/day	8 µg/cm ²	8 µg/cm ²
Zinc pyrithione	0.01 mg/kg bw/day			

Consumer - inhalative:

Chemical name	long term, systemic	short term, systemic	long term, local	short term, local
Kieselguhr, soda ash flux-calcined	0.05 mg/m ³			
1,2-Benzisothiazol-3(2H)-one	1.2 mg/m ³			
2-Bromo-2-nitro-1,3-propaned iol	0.6 mg/m ³	1.8 mg/m ³		0.6 mg/m ³
3(2H)-Isothiazolone, 2-methyl-			0.021 mg/m ³	0.043 mg/m ³
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone			0.02 mg/m ³	0.04 mg/m ³

Consumer - dermal:

Chemical name	long term, systemic	short term, systemic	long term, local	short term, local
1,2-Benzisothiazol-3(2H)-one	0.345 mg/kg bw/day			
2-Bromo-2-nitro-1,3-propaned iol	0.7 mg/kg bw/day	2.1 mg/kg bw/day	4 µg/cm ²	4 µg/cm ²

consumer - oral:

Chemical name	long term, systemic	short term, systemic	long term, local	short term, local
Kieselguhr, soda ash flux-calcined	18.7 mg/kg bw/day			
2-Bromo-2-nitro-1,3-propaned iol	0.18 mg/kg bw/day	0.5 mg/kg bw/day		
3(2H)-Isothiazolone, 2-methyl-	0.027 mg/kg bw/day	0.053 mg/kg bw/day		
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	0.09 mg/kg bw/day	0.11 mg/kg bw/day		

Predicted No Effect Concentration (PNEC):

component information:

Chemical name	Kieselguhr, soda ash flux-calcined CAS: 68855-54-9
Sewage treatment	100 mg/L
Chemical name	1,2-Benzisothiazol-3(2H)-one CAS: 2634-33-5
Freshwater	4.03 µg/L
Marine water	0.403 µg/L
Freshwater (intermittent release)	1.1 µg/L
Marine water (intermittent release)	110 ng/L
Sewage treatment	1.03 mg/L

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Freshwater sediment	49.9 µg/kg sediment dw
Marine sediment	4.99 µg/kg sediment dw
Soil	3 mg/kg soil dw
Chemical name	2-Bromo-2-nitro-1,3-propanediol CAS: 52-51-7
Freshwater	0.01 mg/L
Marine water	0.0008 mg/L
Freshwater (intermittent release)	0.0025 mg/L
Sewage treatment	0.43 mg/L
Freshwater sediment	0.041 mg/kg sediment dw
Marine sediment	0.00328 mg/kg sediment dw
Soil	0.5 mg/kg soil dw
Chemical name	3(2H)-Isothiazolone, 2-methyl- CAS: 2682-20-4
Freshwater	3.39 µg/L
Marine water	3.39 µg/L
Freshwater (intermittent release)	3.39 µg/L
Marine water (intermittent release)	3.39 µg/L
Sewage treatment	0.23 mg/L
Soil	0.0471 mg/kg soil dw
Chemical name	Zinc pyrithione CAS: 13463-41-7
Freshwater	90 ng/L
Marine water	90 ng/L
Sewage treatment	0.01 mg/L
Freshwater sediment	0.0095 mg/kg sediment dw
Marine sediment	0.0095 mg/kg sediment dw
Soil	1.02 mg/kg soil dw
Chemical name	5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone CAS: 55965-84-9
Freshwater	3.39 µg/L
Marine water	3.39 µg/L
Freshwater (intermittent release)	3.39 µg/L
Marine water (intermittent release)	3.39 µg/L
Sewage treatment	0.23 mg/L
Freshwater sediment	0.027 mg/kg sediment dw
Marine sediment	0.027 mg/kg sediment dw
Soil	0.01 mg/kg soil dw

8.2. Exposure controls

Engineering controls: None under normal use conditions.

Personal protective equipment: The usual precautionary measures for the handling of chemicals have to be observed.



Eye/face protection: Wear safety glasses with side shields (or goggles).

Hand protection: Wear suitable gloves.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

PPE - Glove material	Glove thickness	Break through time
NBR (Nitrile rubber)	0.4 mm	>=480 min.

Skin and body protection: Wear suitable protective clothing.

Respiratory protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Recommended Filter Type: Filtering device (full mask or mouthpiec) with filter: AP-2

Environmental exposure controls: No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	dispersion				
Color	white				
Odor	characteristic				
Melting point / melting range				<i>Conditions</i>	<i>Method</i>
Boiling point / boiling range	>	107	°C		<i>Remarks</i>
Flammability					Not established
Decomposition temperature					Not established
Flash point					not relevant
Autoignition temperature					Not established
Lower explosive limit					None known
Upper explosion limit					not relevant
Vapor pressure					not relevant
Density	~	1.230	g/cm ³	20 °C	Not established
Water solubility					Miscible
pH		8 - 9		20 °C	
pH (as aqueous solution)					Not applicable
Partition coefficient					Not established
Kinematic viscosity					Not applicable
Odor threshold					Not established
Relative density					Not established
Evaporation rate					Not established
Relative vapor density		no data available			
Particle Size		no data available			
Particle Size Distribution		no data available			

9.2. Other information

Bulk density: no data available
Softening point No information available
Molecular weight No information available

9.2.1. Information with regard to physical hazard classes:

Explosive properties Not an explosive
Oxidizing properties Not oxidising.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

9.2.2. Other safety characteristics: No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity: No information available.

10.2. Chemical stability

Stability: Stable under normal conditions.

Explosion data:

Sensitivity to mechanical impact: None.

Sensitivity to static discharge: None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions: None under normal processing.

10.4. Conditions to avoid

Conditions to avoid: None known based on information supplied.

10.5. Incompatible materials

Incompatible materials: None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products: None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure:

Product Information:

Inhalation: Specific test data for the substance or mixture is not available.

Eye contact: Specific test data for the substance or mixture is not available.

Skin contact: May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).

Ingestion: Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics:

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Symptoms: Itching. Rashes. Hives.

Numerical measures of toxicity:

Acute toxicity: The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral): 27,054.10 mg/kg
ATEmix (inhalation-dust/mist): 109.90 mg/l

Component Information:

Chemical name	Parameter	Species	effektive Dosis	Method
Kieselguhr, soda ash flux-calcined 68855-54-9	Oral LD50	Rat	> 2000 mg/kg	OECD 401
1,2-Benzisothiazol-3(2H)-one 2634-33-5	Oral LD50	Rat	490 mg/kg	
2-Bromo-2-nitro-1,3-propanediol 52-51-7	Oral LD50	Rat	180 mg/kg	
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	Oral LD50	Rat	120 mg/kg	
Zinc pyrithione 13463-41-7	Oral LD50	Rat	177 mg/kg	
Terbutryn 886-50-0	Oral LD50	Rat	2045 mg/kg	
5-Chloro-2-methyl-3(2H)-isothiazolon e, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	Oral LD50	Rat	457 mg/kg	

Chemical name	Parameters	Species	Effective dose	Method
2-Bromo-2-nitro-1,3-propanediol 52-51-7	Dermal LD50	Rat	1600 mg/kg	
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	Dermal LD50	Rabbit	200 mg/kg	
Zinc pyrithione 13463-41-7	Dermal LD50	Rabbit	100 mg/kg	
Terbutryn 886-50-0	Dermal LD50	Rabbit	> 10200 mg/kg	
5-Chloro-2-methyl-3(2H)-isothiazolon e, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	Dermal LD50	Rabbit	660 mg/kg	

Chemical name	Parameters	Species	Effective dose	Exposure time	Method
Kieselguhr, soda ash flux-calcined 68855-54-9	Inhalation LC50	Rat	> 2.6 mg/L		OECD 403
2-Bromo-2-nitro-1,3-propanedi ol 52-51-7	Inhalation LC50	Rat	800 mg/m ³	4 h	
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	Inhalation LC50	Rat	0.34 mg/L	4 h	
Zinc pyrithione	Inhalation LC50	Rat	0.05 - 0.5 mg/L	4 h	

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Chemical name	Parameters	Species	Effective dose	Exposure time	Method
13463-41-7			140 mg/m ³		
Terbutryn 886-50-0	Inhalation LC50	Rat	> 8 g/m ³	4 h	
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	Inhalation LC50	Rat	171 - 2360 mg/m ³	4 h	

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Skin corrosion/irritation:	No information available.
Serious eye damage/eye irritation:	No information available.
Respiratory or skin sensitization:	May cause sensitization by skin contact.
Germ cell mutagenicity:	No information available.
Carcinogenicity:	No information available.
Reproductive toxicity:	No information available.

Chemical name	European Union
Zinc pyrithione	Repr. 1B

STOT - single exposure:	No information available.
STOT - repeated exposure:	No information available.

Chemical name	Exposure route	Target Organs
Kieselguhr, soda ash flux-calcined 68855-54-9	Inhalation	lung
Silica, cristobalite 14464-46-1	Inhalation	lung

Aspiration hazard:	No information available.
--------------------	---------------------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2. Other information

No information available.

SECTION 12: Ecological information

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

12.1. Toxicity

Ecotoxicity: Harmful to aquatic life with long lasting effects.

fish toxicity:

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	LC50		2.15 mg/L	96 h	
2-Bromo-2-nitro-1,3-propanedi ol 52-51-7	LC50	Lepomis macrochirus	11 mg/L	96 h	OECD 203
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	LC50		4.77 mg/L	96 h	
5-Chloro-2-methyl-3(2H)-isothi azolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	LC50	Oncorhynchus mykiss	0.22 mg/L	96 h	OECD 203

toxicity to crustacea:

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50		2.9 mg/L	48 h	
2-Bromo-2-nitro-1,3-propanedi ol 52-51-7	EC50	Daphnia magna	1.04 mg/L	48 h	OECD 202
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	LC50		0.934 mg/L	48 h	
5-Chloro-2-methyl-3(2H)-isothi azolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	EC50	Daphnia magna	0.1 mg/L	48 h	OECD 202

Algae Toxicity:

Chemical name	Parameter	Species	Effective dose	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50		0.11 mg/L	72 h	
2-Bromo-2-nitro-1,3-propanedi ol 52-51-7	EC50	Anabaena flos aqua	0.068 mg/L	72 h	OECD 201
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	EC50		0.103 mg/L	72 h	
Zinc pyrithione 13463-41-7	EC50		0.003 mg/L	96 h	
5-Chloro-2-methyl-3(2H)-isothi azolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	EC50	Pseudokirchneriella subcapitata	0.048 mg/L	72 h	OECD 201

Bacteria toxicity:

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Revision Number: 1

Print Date: 13-Jan-2023

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Chemical name	Parameters	Species	Effective dose	Exposure time	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	EC50		12.8 mg/L	3 h	
2-Bromo-2-nitro-1,3-propanediol 52-51-7	EC50	activated sludge	43 mg/L	3 h	
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	EC50		41 mg/L	3 h	
Zinc pyrithione 13463-41-7	EC50		2.4 mg/L	3 h	
Terbutryn 886-50-0	EC20	activated sludge	>100 mg/L	3 h	
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	EC50	activated sludge	7.92 mg/L	3 h	

12.2. Persistence and degradability

Persistence and degradability:

Chemical name	degradation rate	test duration	Rapidly biodegradable	Remarks	Method
1,2-Benzisothiazol-3(2H)-one 2634-33-5	100 %	0.04 d	Yes		OECD 307
2-Bromo-2-nitro-1,3-propanediol 52-51-7	100 %	28 d	Yes		
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	100 %	0.07 d	Yes		
Zinc pyrithione 13463-41-7	100 %		Yes		
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	> 60 %	28 d	Yes		OECD 301

12.3. Bioaccumulative potential

Bioaccumulation:

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
1,2-Benzisothiazol-3(2H)-one 2634-33-5	1.3	6.62
2-Bromo-2-nitro-1,3-propanediol 52-51-7	0.38	3.16
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	-0.26 -0.34 -0.28	3.16

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Zinc pyrithione 13463-41-7	1.12	1.4
Terbutryn 886-50-0	3.19	103
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	0.69	3.16

12.4. Mobility in soil

Mobility in soil: No information available.

Mobility: No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment:

Chemical name	PBT and vPvB assessment
Kieselguhr, soda ash flux-calcined 68855-54-9	PBT assessment does not apply
1,2-Benzisothiazol-3(2H)-one 2634-33-5	The substance is not PBT / vPvB
2-Bromo-2-nitro-1,3-propanediol 52-51-7	The substance is not PBT / vPvB
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	The substance is not PBT / vPvB
Zinc pyrithione 13463-41-7	The substance is not PBT / vPvB
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties.

No information available.

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Terbutryn 886-50-0	Group III Chemical	-

12.7. Other adverse effects.

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products: Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging: Do not reuse empty containers.

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Waste codes / waste designations according to EWC / AVV: 08 01 12 (waste paint and varnish other than those mentioned in 08 01 11)

SECTION 14: Transport information

14.1. UN number

ADR:	Not regulated
RID:	Not regulated
IMDG:	Not regulated
IATA:	Not regulated

14.2 UN proper shipping name

ADR:	Not regulated
RID:	Not regulated
IMDG:	Not regulated
IATA:	Not regulated

14.3. Transport hazard class(es)

ADR:	Not regulated
RID:	Not regulated
IMDG:	Not regulated
IATA:	Not regulated

14.4. Packing group

ADR:	Not regulated
RID:	Not regulated
IMDG:	Not regulated
IATA:	Not regulated

14.5. Environmental hazards

ADR:	
RID:	
IMDG:	Not regulated
IATA:	

14.6. Special precautions for user

ADR:	Not regulated
Special Provisions:	None
RID:	Not regulated
Special Provisions:	None
IMDG:	Not regulated
Special Provisions:	None
IATA:	Not regulated
Special Provisions:	None

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

No information available

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union:

Regulation (EC) No. 1907/2006 (Annex II - (EC) No. 2020/878) and Regulation (EC) No. 1272/2008

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Take note of Directive 94/33/EC on the protection of young people at work:

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken

Authorizations and/or restrictions on use:

- This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Substance subject to authorization per REACH Annex XIV	Restricted substance per REACH Annex XVII
1,2-Benzisothiazol-3(2H)-one 2634-33-5		75.
2-Bromo-2-nitro-1,3-propanediol 52-51-7		75.
3(2H)-Isothiazolone, 2-methyl- 2682-20-4		75.
Zinc pyrithione 13463-41-7		75.
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9		3

Persistent Organic Pollutants:
(EC) 2019/1021

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009: Not applicable

Chemical name	Biocidal Products Regulation (EU) No 528/2012 (BPR)
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	13 - Working or cutting fluid preservatives 12 - Slimicides 11 - Preservatives for liquid-cooling and processing systems
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	2 - Disinfectants and algicides not intended for direct application to humans or animals 4 - Food and feed area disinfectant 6 - Preservatives for products during storage 11 - Preservatives for liquid-cooling and processing systems 12 - Slimicides 13 - Working or cutting fluid preservatives

Chemical name	EU - Water Framework Directive (2000/60/EC)
Terbutryn	Priority substance

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Revision Number: 1

Print Date: 13-Jan-2023

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

886-50-0	
Chemical name	EU - Environmental Quality Standards (2008/105/EC)
Terbutryn 886-50-0	Priority Substance ([45])

volatile organic compounds (VOC) content:
 acc. reg. 2010/75/EG: 0 %
 acc. reg. 2004/42/EG (Decopaint): 0 g/L

National regulations:

Denmark:

Chemical name	Denmark - MAL
Silica, cristobalite 14464-46-1	0 m3/10 g substance MAL factor 0.1 mg/m ³ Limit Value respirable >=0.1 - 2 % by weight [3] >=1 - 10 % by weight [3] >=10 % by weight [6] >=2 % by weight [6]
1,2-Benzisothiazol-3(2H)-one 2634-33-5	0 m3/10 g substance MAL factor >=1.0 % by weight [3]
2-Bromo-2-nitro-1,3-propanediol 52-51-7	50000 m3/10 g substance MAL factor 2500 m3/10 g substance MAL factor []
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	0 m3/10 g substance MAL factor >=0.03 - 1.0 % by weight [3] >=0.003 - 1.0 % by weight [3] >=1.0 % by weight [6]
Zinc pyrithione 13463-41-7	0 m3/10 g substance MAL factor >=1 % by weight [3]

Germany:

Water hazard class (WGK): slightly hazardous to water (WGK 1) - Classification according to AwSV

Chemical name	WGK Classification (AwSV)	ID number
Kieselguhr, soda ash flux-calcined 68855-54-9	nwg	854
Silica, cristobalite 14464-46-1	nwg	849
1,2-Benzisothiazol-3(2H)-one 2634-33-5	2	5141
2-Bromo-2-nitro-1,3-propanediol 52-51-7	2	5204
3(2H)-Isothiazolone, 2-methyl- 2682-20-4	3	2960
Zinc pyrithione 13463-41-7	3	7636
Terbutryn 886-50-0	2	612
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone 55965-84-9	3	2959

TA Luft (German Air Pollution Control Regulation):

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

total dust incl. fine dust (digit 5.2.1): 25 - 30%
org. substances (Ziffer 5.2.5): < 5%
org. subst. dust (digit 5.2.5): < 5%

Storage class (TRGS 510): LGK12 - Non-combustible liquids

France:

Occupational Illnesses (R-463-3, France):

Chemical name	French RG number
Silica, cristobalite 14464-46-1	RG 25
1,2-Benzisothiazol-3(2H)-one 2634-33-5	RG 65

RG 25 - Conditions resulting from inhalation of mineral dusts containing crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc), graphite, or coal.
RG 65 - Allergic eczema

Netherlands:

Chemical name	Silica, cristobalite
Netherlands - List of Carcinogens	Present X

Chemical name	Zinc pyrithione
Netherlands - List of Reproductive Toxins	Development Category 1B
ZZS list: SVHC	x ()

Water contaminating class (Netherlands): B (4)

Austria:

Flammable Liquids Regulations, VbF: Not regulated

Poland:

Ordinance of the Minister of Family, Labor and Social Policy dated June 12, 2018 on the highest permissible concentrations and intensities of harmful factors for health in the work environment (Dz. U. 2018 item 1286, as amended)
Act of December 14, 2012 on waste (Journal of Laws of 2013, item 21; as amended)
Act on chemical substances and their mixtures of February 25, 2011. (Journal of Laws No. 63, item 322; as amended)
Regulation of the Minister of Labor and Social Policy of September 26, 1997 on general regulations of safety and hygiene at work (Dz. U. of 2003, No. 169, item 1650; as amended).

Switzerland:

VOC content:: acc. VOCV CH 814.018, att. 1: 0 %

Hungary:

Decree No 44/2000 (XII.27.) of the Ministry of Economic Affairs and Labour of the Republic of Hungary on certain procedures and activities Joint Decree No. 5/2020 ITM on Chemical Safety at Work 178/2017 (VII. 5.)
Government Decree on the European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) „A“ and „B“ of the European Agreement on Road Transport

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

International Inventories:

TSCA	Does not comply
DSL/NDSL	Does not comply
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Does not comply
KECL	Does not comply
PICCS	Does not comply
AICS	Does not comply
NZIoC	Does not comply

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- NZIoC** - New Zealand Inventory of Chemicals
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

Chemical Safety Report: No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet:

Full text of H-Statements referred to under section 3:

- EUH071 - Corrosive to the respiratory tract
- H301 - Toxic if swallowed
- H302 - Harmful if swallowed
- H310 - Fatal in contact with skin
- H311 - Toxic in contact with skin
- H312 - Harmful in contact with skin
- H314 - Causes severe skin burns and eye damage
- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H318 - Causes serious eye damage
- H330 - Fatal if inhaled
- H331 - Toxic if inhaled
- H335 - May cause respiratory irritation
- H372 - Causes damage to organs through prolonged or repeated exposure
- H373 - May cause damage to organs through prolonged or repeated exposure
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects
- H411 - Toxic to aquatic life with long lasting effects

Legend:

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
ADR: European agreement concerning the international carriage of dangerous goods by road (Accord européen relatif transport des marchandises dangereuses par route)
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany)
BCF: Bio-Concentration Factor
BOD(5): Biochemical oxygen demand (within 5 days)
CAS: Chemical Abstract Service
CLP: Classification, Labelling and Packaging
CMR: Carcinogenic, Mutagenic, toxic for Reproduction
DIN: German Standards Institute / German industrial norm
DNEL: Derived No Effect Level
DOC: Dissolved organic carbon
EAK/ AVV: European waste catalogue/ waste directory-regulation
EC50: Effective Concentration 50%
ECHA: European Chemical Agency
EINECS: European Inventory of Existing Commercial Chemical Substances
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
IATA: International Air Transport Association
IC50: Inhibition Concentration 50%
IMDG: International Maritime Dangerous Goods Code
LC50: Lethal Concentration 50% - LD50: Lethal dose 50%
MAK: Treshold limit values Germany
NLP: No Longer Polymers
NOAEC: No Observed Adverse Effect Concentration
NOAEL: No Observed Adverse Effect Level
OECD: Organization for Economic Cooperation and Development
PBT: persistent, bioaccumulative, toxic
PC: Product category
PNEC: Predicted No Effect Concentration
REACH: Registration, Evaluation and Authorization of Chemicals
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer)
STEL: Short-term Exposure Limit
STP: Sewage treatment plant
SVHC: Substance of Very High Concern
TLV: Threshold Limit Value
TWA: Time Weighted Average
UN: United Nations
VOC: Volatile Organic Compounds
vPvB: very persistent, very bioaccumulative

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Ceiling: Maximum limit value

* Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapor	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitization	Calculation method

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008



Revision date: 30-Aug-2021

Print Date: 13-Jan-2023

Revision Number: 1

Mega 406 Siloxan-Elast Fassadenfarbe - 026070540514

Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS:

European Chemicals Agency (ECHA)

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGl(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

Revision date: 04-Oct-2021

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006:

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet