



tesa[®] Professional 4365 Easy Cover[®] Precision

Product Information

2-in-1: Masking film with mask tape for sharp paint edges

Product Description

We proudly present: the practical 2-in-1 solution for precise results. The combination of transparent, supple masking film and powerful adhesive tape Precision Mask[®] 4334 saves both time and effort, because the adhesive tape guarantees razor-sharp paint edges and the film ensures the entire surroundings remain clean – in only one working step. Professional masking film and high-quality adhesive tape combined with your skilled craftsmanship are the ideal basis for outstanding paint work that will leave your customers extremely pleased.

Product Features

- Indoor masking
- For long-term applications (up to 5 month)
- The 2-in-1 solution for masking off and protecting large areas
- Flat, sharp edges to paint and lacquer
- For smooth and slightly textured surfaces
- For high-quality painting and lacquering work
- For painting tasks and spray techniques

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing material | Washi paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----|--------------------|---------|
| • Elongation at break | 4 % | • Tensile strength | 30 N/cm |
|-----------------------|-----|--------------------|---------|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|



tesa[®] Professional 4365 Easy Cover[®] Precision

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04365>