

tesa® Professional 4401 Easy Cover® Precision Standard Paper

Product Information

Standard Precision masking tape with masking paper

Product Description

tesa Easy Cover® 4401 is a combination of high quality folded special paper and tesa® 4344 Precision Mask® Standard for the masking of large areas in one working step. It is resistant against dispersion paints and allows easy removability up to 3 months after indoor application.

Easy Cover® 4401 is successfully tested for all standard in-door applications such as skirting boards, window sills, window and door frames. It allows safe and precise fixation on smooth and slightly textured surfaces. The masking paper avoids paint bleeding or leaking to the protected area while the tape ensures a clean and precise painting result with flat paint edges. So with tesa® Easy Cover® 4401, you are well equipped to pave the way for outstanding painting work. In combination with your skilled craftsmanship, you will achieve results that will impress your customers.

Product Features

- Time-saving 2-in-1 covering solution for top professionals: covering large areas and accurate masking in one step
- Combination of masking paper and integrated tesa® precision crepe
- · For flat and precise paint edges
- Applicable on smooth and slightly structured surfaces
- Ideal foundation for superb paint jobs indoors
- · Easy to remove even after 3 months

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing material Washi paper
Total thickness
90 μm

• Type of adhesive acrylic

Properties/Performance Values

Elongation at break
Tensile strength
Material of masking coverage paper

Adhesion to Values

• Steel 1.7 N/cm



tesa® Professional 4401 Easy Cover® Precision Standard Paper

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

