



# **Technical Bulletin TM 684**

# Megamur Style Care Treatment

# **Product description:**

Additional transparent protective coating based on polymer wax in the MEGA 680 Megamur Style Walls and Floors Filler System. The treated surface is easier to care for and is given a classic surface appearance.

# Application:

As an extra protective coating against premature soiling of the newly constructed surfaces. Durability (e.g. against premature signs of wear) is prolonged significantly. MEGA 684 Megamur Style Care Treatment should be applied before occupying the rooms.

### **Properties:**

- crystal clear
- classic surface appearance
- easy to clean
- · prolongs the durability of the sealing

### Please observe:

MEGA 684 Megamur Style Care Treatment can be applied as early as 16 - 24 hours after the sealing is applied.

# Material basis:

Polymer wax

# Spec. weight:

approx. 1.02 g/m<sup>3</sup>

#### pH value: approx. 8.5

арргох. 6.5

# Shade of colour:

Wet = milky Dry = transparent

# Packaging size:

11

## Consumption: approx. 1 I/60m<sup>2</sup>

Drying process:

Can be walked on after approx. 2 - 3 hours Load-bearing after approx. 12 hours

# Storage:

Cool, dry, frost-free. Unopened container can be stored for at least 12 months.

# Information on disposal:

For disposal, please observe the legal regulations.

#### Product code: Ö20

# Hazard warnings and safety instructions:

In the case of contact with eyes, immediately rinse thoroughly with water and consult a physician. Keep out of the reach of children. If inhaled/swallowed, consult a physician immediately and have safety data sheet at hand.

# Observe the safety data sheet and care instructions!





All specifications can only be regarded as general information. The working conditions beyond our sphere of influence and the multitude of different materials preclude any claim to liability relating to this information. A guarantee can only be given for the high and stable quality of our products.