



Product Description

ERFURT-KlimaTec SR 2

Manufacturer

ERFURT & SOHN KG • Hugo-Erfurt-Straße 1
42399 Wuppertal • GERMANY • www.erfurt.com

Raw materials/Manufacture

ERFURT-System Adhesive SR 2 is a polyvinyl acetate polymer-based emulsion adhesive, specifically developed for use with ERFURT KlimaTec, which has excellent adhesion.

Product data

- Order no. 1001207
- Weight: 18 kg container

Product features

- For use indoors
- Excellent adhesion
- Simple and smooth to apply with a long-pile lambskin roller
- Can be sprayed with an airless unit
- Simple, quick and clean to use
- Optimum adhesion to the base surface
- Excellent wet strength
- Excellent wallpapering results
- 20 minute working time
- No heavy metal compounds added

Application/Handling

ERFURT-System Adhesive SR 2 has been specifically developed for use with the ERFURT KlimaTec system. It can be used with all solid, smooth or slightly textured base surfaces on interior walls and ceilings.

Preparation of the base surface

The base surface should be dry, clean and firm. Remove loose old paint and wallpaper. Use a filler to level serious differences in height.

Working conditions

Depending on the base surface and application volume, the consumption is 0.3 to 0.5 kg/m². Ensure that the working temperature does not fall below 10 °C. The working time is generally around 20 minutes, under normal temperature and humidity conditions.

Adhesion



Using a long-pile roller, generously apply ERFURT-System Adhesive SR 2 evenly to the base surface over an area measuring the width of 1 or 2 strips.



Place the wallcovering into the adhesive and press down with a wallpapering palette knife so that the adhesive is evenly distributed and a flat base surface is achieved.

Drying

At +20°C and 65% relative air humidity, paint after approx. 6 – 12 hours of drying. This time may be longer at lower temperatures and with higher air humidity.

Cleaning your tools

Wash with water immediately after use.

Storage

Keep ERFURT-System Adhesive SR 2 containers well sealed and store in a cool and frost-free place. Protect from direct sunlight. The system adhesive can be stored for at least two years in its sealed original container.

Disposal

Dispose of dried and/or hardened remains of ERFURT-System Adhesive SR 2 with normal household waste.

Made in Germany

ERFURT & SOHN KG
Hugo-Erfurt-Straße 1
42399 Wuppertal

Phone.: +49 202 6110 0
Fax: +49 202 6110 89 451

E-mail: info@erfurt.com
Website: www.erfurt.com

KlimaTec

PRO

www.erfurt.com