
## Product data sheet





Cordless Rotary Hammer with SDS plus

## **GBH 18V-26F**



Universal rotary hammer with quick-change chuck in the SDS plus cordless category

### The most important data

Battery voltage	18.0 V
Impact energy (according to EPTA 05/2016)	2.6 J
Drilling dia. in concrete with hammer drill bits	4 – 26 mm

**Part Number** 0 611 910 000

#### > More product information

## Technical data

#### Technical data

Impact energy (according to EPTA 05/2016)	2.6 J
Impact rate at rated speed	0 – 4,350 bpm
Rated speed	0 – 980 rpm
Battery voltage	18.0 V
Tool holder	SDS plus
Packaging dimensions (width x length x height)	251 x 398 x 104 mm

#### Drilling range

Drilling dia. in concrete with hammer drill bits	4 – 26 mm
Opt. app. range in concrete with hammer drill bits	8 – 16 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm

## Noise/vibration information

## Hammer drilling in concrete

Vibration emission value ah	15.2 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>
Chiselling in concrete	
Vibration emission value ah	9.6 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

# Invented for life

## Product data sheet

### Power tools for trade & industry

# Advantages:

- Optional GDE 18V-16 Professional dust extraction unit integrates with the hammer for a self-contained HEPA dust solution
- KickBack Control and Electronic Precision Control for better tool handling and increased user protection
- Delivers 2.6 J of impact energy for fast drilling and high chisel removal performance



































