
Product data sheet





Cordless Rotary Hammer with SDS plus

GBH 18V-28 CF



Cordless rotary hammer for full-throttle hammer drilling, with quick-change chuck

The most important data

The first state states	
Battery voltage	18.0 V
Impact energy (according to EPTA 05/2016)	3.3 J
Drilling dia. in concrete with hammer drill bits	4 – 28 mm

Part Number 0 611 921 001

> More product information

Technical data

Technical data

Impact energy (according to EPTA 05/2016)	3.3 J
Impact rate at rated speed	4,220 bpm
Battery voltage	18.0 V
Weight excl. battery	3.4 kg
Tool holder	SDS plus
Packaging dimensions (width x length x height)	357 x 442 x 253 mm
Drilling range	
Drilling dia. in concrete with hammer drill bits	4 – 28 mm
Opt. app. range in concrete with hammer drill bits	8 – 18 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	14 m/s²
Uncertainty K	1.5 m/s ²
Drilling in metal	
Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²
Screwdriving	
Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s ²
Chiselling in concrete	
Vibration emission value ah	9 m/s²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Brushless motor and striking mechanism with 3.3 J impact energy for impressive performance
- Vibration Control and KickBack Control for increased user protection
- Perfect control and the right setting for every job with three different work modes (Auto, Favorite, Soft)





















