

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Cordless Rotary Hammer BITURBO with SDS max

GBH 18V-36 C



Outstanding compactness and power – Bosch’s GBH 18V-36 C Professional cordless SDS max hammer

The most important data

Battery voltage	18.0 V
Impact energy (according to EPTA 05/2016)	7 J
Hammer drilling diameter range in concrete	14 – 35 mm

Part Number 0 611 915 001[> More product information](#)

Technical data

Technical data

Impact energy (according to EPTA 05/2016)	7 J
Impact rate at rated speed	0 – 2,900 bpm
Rated speed	0 – 500 rpm
Battery voltage	18.0 V
Weight excl. battery	5.1 kg
Tool holder	SDS max
Packaging dimensions (width x length x height)	408 x 617 x 150 mm

Drilling range

Opt. app. range in concrete with hammer drill bits	14 – 35 mm
Hammer drilling diameter range in concrete	14 – 35 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	11.4 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	10.8 m/s ²
Uncertainty K	1.5 m/s ²



Product data sheet

Power tools for trade & industry

Advantages:

- Extremely compact – significantly more compact than any other cordless SDS max hammer on the market
- Maximum power with lightweight design – BITURBO Brushless hammer with ProCORE18V battery with top performance of 7.0 J max at 6.1 kg
- Highly intelligent – User Interface and Bluetooth connectivity combined with soft start and lock-on button for permanent chiselling

