

**BOSCH**

Invented for life

# Product data sheet

## Power tools for trade & industry

Combi Laser

### GCL 2-15



Compact and versatile for short-distance levelling applications

#### The most important data

Working range	up to 15 m
Accuracy	$\pm 0.3 \text{ mm/m}^*$ (* plus use-dependent deviation)
Self-levelling range	$\pm 4^\circ$

**Part Number** 0 601 066 E00[> More product information](#)

## Technical data

### Technical data

Laser diode	630 – 650 nm, < 1mW
Operating temperature	-10 – 50 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range	up to 15 m
Accuracy	$\pm 0.3 \text{ mm/m}^*$ (*plus use-dependent deviation)
Working range of laser points, max.	10 m (top), 10 m (bottom)
Self-levelling range	$\pm 4^\circ$
Levelling time	4 s
Dust and splash protection	IP 54
Power supply	3 x 1.5 V LR6 (AA)
Operating time (max.)	6 h in cross line and point mode, 8 h in cross line mode, 12 h in line and point mode, 16 h in line mode, 22 h in point mode
Tripod thread	1/4", 5/8"
Weight, approx.	0.49 kg

Colour of laser line	red
Projection	2 lines / 2 points
Plumb point accuracy	$\pm 0.7 \text{ mm/m}^*$ (*plus use-dependent deviation)



**BOSCH**

Invented for life

# Product data sheet

Power tools for trade & industry

---

## Advantages:

- Both horizontal and vertical lines are perfect for short-distance levelling applications
- Enjoy precise transfer applications thanks to two centred plumb points
- Rotating mount RM 1 Professional allows laser lines to be easily positioned around the plumb points



15 m



5/8" + 1/4"



LASER



EASY  
POSITIONING



SLIDE

---