

### Combi Laser

# GCL 2-50 G



Durability and ease of use. Green laser lines and green plumb points

### The most important data

Working range with receiver	up to 50 m
Working range	up to 15 m
Accuracy	± 0.3 mm/m* (* plus use- dependent deviation)

Part Number 0 601 066 M02

### > More product information

# Technical data

### Technical data

reenneur autu	
Operating temperature	-10 – 45 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range	up to 15 m
Working range with receiver	up to 50 m
Accuracy	± 0.3 mm/m* (*plus use-dependent deviation)
Working range of laser points, max.	10 m
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 64
Power supply	4 x 1.5 V LR6 (AA)
Tripod thread	1/4"
Weight, approx.	0.58 kg
Colour of laser line	green
Color of plumb points	green
Projection	2 lines / 2 points
Plumb point accuracy	± 0.7 mm/m* (*plus use-dependent deviation)
Compatible laser receivers	LR 7

# Product data sheet



Power tools for trade & industry

# Advantages:

- Durable design, featuring a rubberised housing with recessed glasses and dust and splash water protection IP 64 to withstand tough environments
- ON/OFF switch and one-button keypad make for ease of use
- Green laser lines and green plumb points provide enhanced visibility

