

Cordless Drill/Driver GSR 12V-35 FC



The most versatile drill driver with brushless motor and FlexiClick attachment system in the 12V category

The most important data

Torque (soft/hard/max.)	20/35/- Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,750 rpm
Max. screw diameter	8 mm

Part Number 0 601 9H3 004

> More product information

Technical data

Technical data

Torque (soft/hard/max.)	20/35/- Nm
No-load speed (1st gear / 2nd gear)	0 - 460 / 0 - 1,750 rpm
Battery type	Lithium-Ion
Chuck capacity, min./max.	0.8 / 10 mm
Battery voltage	12.0 V
Weight excl. battery	0.59 kg
Torque settings	20+1
Packaging dimensions (width x length x height)	235 x 333 x 109 mm
Screw diameter	
Max. screw diameter	8 mm
Drilling diameter	
Max. drilling diameter in wood	32 mm
Max. drilling diameter in steel	10 mm

Noise/vibration information

Drilling in metal

Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s²
Screwdriving	
Vibration emission value ah	2.5 m/s ²
Uncertainty K	1.5 m/s²

Product data sheet Power tools for trade & industry



Advantages:

- FlexiClick System: easy-to-switch attachments offering up to 8 combinations
- Extremely compact yet highly powerful, with 35 Nm and 1,750 rpm, provides optimum handling in hard-to-reach places
- Brushless motor along with Electronic Motor Protection prevents overload and ensures a longer tool lifetime

