
Product data sheet





Cordless Orbital Sander

GSS 18V-10



The compact and ergonomic orbital sander in the 18 $\rm V$ category

The most important data

| Battery voltage | 18.0 V |
|-----------------------|--------|
| Sanding plate, width | 101 mm |
| Sanding plate, length | 113 mm |

Part Number 0 601 9D0 202

> More product information

Technical data

Technical data

| Battery voltage | 18.0 V |
|--|--------------------|
| No-load orbital stroke rate | 22,000 opm |
| Orbit diameter | 1.6 mm |
| Packaging dimensions (width x length x height) | 360 x 440 x 155 mm |
| Delta sanding plate w/ hook-and-loop, length | 150 mm |
| Delta sanding plate w/ hook-and-loop, width | 100 mm |
| Sanding plate w/ hook-and-loop, length | 130 mm |
| Sanding plate w/ hook-and-loop, width | 80 mm |
| Sanding plate w/ hook-and-loop & clamp, length | 101 mm |
| Sanding plate w/ hook-and-loop & clamp, width | 113 mm |
| | |

Sanding surface


| Sanding plate, width | 101 mm |
|--|---------------------|
| Sanding plate, length | 113 mm |
| Sanding surface | 114 cm ² |
| Sanding sheet for clamping, width | 115 mm |
| Sanding sheet for clamping, length | 140 mm |
| Sanding sheet with hook-and-loop fastening, width | 115 mm |
| Sanding sheet with hook-and-loop fastening, length | 107 mm |

Noise/vibration information

Sanding panel materials

| Vibration emission value ah | 7.5 m/s ² |
|-----------------------------|----------------------|
| Uncertainty K | 1.5 m/s ² |

Product data sheet





Advantages:

- Features an ergonomic palm rest and compact design for easy, comfortable handling
- Robust metal sheet provides tool durability
- Clamping system with hook-and-loop foam pad designed for the easy sanding paper changes











