

Technical data sheet

1919 siawood +



Status:	Ok
Approval:	25.01.2023

Classification	Public series
Product type:	Coated abrasives
Main industries:	Furniture Production Building Interior
Further industries:	Kitchens Panels Parquet

Product profile		
Grit type:	Aluminium oxide	P036 – P220
Grit range (total):	36-220	FEPA P / ISO 6344
Backing:	f-wt paper (FSC-certified)	
Coating:	Electrostatic open	
Bonding:	Resin over resin	
Special coating:		
Equipment:	TopTec	

Properties		Technology
Removal rate:	9 - very high	- Open coating - siafast - TopTec
Lifetime:	10 - very long	
Finishing:	8 - good	
Flexibility:	3 - rigid	
Contact pressure:		

Advantages	
Building Interior:	<ul style="list-style-type: none">- Premium product for the highest quality demands in stationary wood sanding- Minimal clogging thanks to modern coating technology- Outstanding performance and long life- Very high stock removal rates and excellent finish- Backing with very high stability and rigidity- Lower grinding costs due to longer lifetime
Furniture Production:	<ul style="list-style-type: none">- Premium product for the highest quality demands in stationary wood sanding- Minimal clogging thanks to modern coating technology- Outstanding performance and long life- Very high stock removal rates and excellent finish- Backing with very high stability and rigidity- Lower grinding costs due to longer lifetime







Applications	
Building Interior:	
Furniture Production:	<ul style="list-style-type: none">- Calibrating surfaces- Coarse sanding of solid wood and wood-based materials- Fine sanding of solid wood, veneer and wood-based materials




Technical data sheet

1919 siawood +



Material		
Building Interior:	Bodyfiller Mineral materials Primer filler Wood Wood Wood	Plastics Bodyfiller Solid surface material Primer filler ● Soft wood ○ Hard wood Resinous wood
Furniture Production:	Coatings Coatings Plastics Plastics Solid wood Solid wood Solid wood	○ Bodyfiller ○ Primer filler ○ Solid surface material ○ Plastics ● Soft wood ● Hard wood ● Resinous wood

Conversion forms	Upper conversion	Lower conversion
	Rolls	- Jumbolino - Jumbo rolls - Paper rolls - siafast rolls - Economy rolls
	Sheet	- Standard sheets
	Strips	- siafast strips - Self-adhesive strips - Various strips
	Delta and polygons	- Delta and polygons
	Discs	- siafast discs - Self-adhesive discs - Various discs
	Belts	- Wide belts (width: from 400 mm) - Hand sanding belts and sleeves (width: 30–390 mm/length: up to 950 mm) - Narrow, edge and long belts (width: 25–399 mm/length: up to 10,700 mm)

Application	Superordinate group	Subgroup
	Portable machine sanding	Delta sander
	Portable machine sanding	random orbital sander
	Portable machine sanding	Orbital sanders

Technical data sheet

1919 siawood +



Application	Superordinate group	Subgroup
	Manual sanding	Hand sanding with sanding block
	Stationary belt sanding	Cross belt sanding
	Stationary belt sanding	Edge belt sanding
	Stationary belt sanding	Long belt sanding
	Stationary belt sanding	Contact wide belt sanding
	Stationary belt sanding	Combined wide belt sanding
	Stationary belt sanding	Pad wide belt sanding
	Stationary machine sanding	Stationary disc sanding
	Stationary machine sanding	Drum sanding
	Stationary machine sanding	Sleeve sanding
Cut:	Dry application	

Details

No suitability for:	- Wet sanding
Sanding recommendation:	- P80 - P800: use belts wider than 1800 mm only after preliminary tests
Safety recommendation:	<p>Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety</p> <ul style="list-style-type: none"> - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask

Communication

Claim:	The benchmark for wood and lacquer sanding
Copy:	As a universal all-round product, 1919 siawood + with its outstanding properties in wood and lacquer applications meets the highest demands of the woodworking industry and trade.



Communication			
Image material:	Product Top View (PTV)	Front side:	ID
		Rear side:	ID
	Application image	Building Interior:	ID 6712
		Furniture	ID 6712
		Production:	
	Product show:		
Macro shot:			
Packaging image:			
Product group image:			ID 5652

- Main application
- Secondary application