

Thomsit K 182 Neoprene Contact Adhesive Extra

Version 1.0 Revision Date: 30.08.2022 SDS Number: 00000820080 Date of last issue: -
Date of first issue: 30.08.2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Thomsit K 182 Neoprene Contact Adhesive Extra
Product code : 000000000050505240

Manufacturer or supplier's details

Company : PCI Augsburg GmbH
Address : PICCARDSTR. 11
86159 AUGSBURG
Telephone : +4982159010
Emergency telephone : ChemTel: +1-813-248-0585
Telefax : +498215901372

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Serious eye damage : Category 2A
Specific target organ toxicity - single exposure : Category 3
Hazardous to the aquatic environment - acute hazard : Category 1
Hazardous to the aquatic environment - chronic hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.

Thomsit K 182 Neoprene Contact Adhesive

Extra

Version 1.0	Revision Date: 30.08.2022	SDS Number: 00000820080	Date of last issue: - Date of first issue: 30.08.2022
----------------	------------------------------	----------------------------	--

H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P273 Avoid release to the environment.
 P271 Use only outdoors or in a well-ventilated area.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ .? / equipment.
 P242 Use only non-sparking tools.
 P240 Ground and bond container and receiving equipment.
 P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P312 Call a POISON CENTER/ doctor/ .?/ if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P391 Collect spillage.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P233 Keep container tightly closed.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards which do not result in classification

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

**Thomsit K 182 Neoprene Contact Adhesive
 Extra**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.08.2022	00000820080	Date of first issue: 30.08.2022

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Preparation based on:
 Polymer
 resin
 solvent(s)

Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyl acetate	141-78-6	20 - 40
cyclohexane	110-82-7	25 - 40
Hydrocarbons, C6-7	92128-66-0	10 - 20
zinc oxide	1314-13-2	0,25 - 2,5
rosin	8050-09-7	0,1 - 1
n-hexane	110-54-3	0,1 - 1
Phenol, 4-methyl-, reaction products with dicyclopentadiene and isobutylene	68610-51-5	0,1 - 1
disulfiram	97-77-8	0,01 - 0,1

4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed : Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry powder
 Alcohol-resistant foam

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : Evolution of fumes/fog. In case of fire hazardous decomposition products may be produced such as:

Thomsit K 182 Neoprene Contact Adhesive Extra

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.08.2022	00000820080	Date of first issue: 30.08.2022

- Hazardous combustion products : harmful vapours
- Specific extinguishing methods : The degree of risk is governed by the burning substance and the fire conditions.
Containers may rocket or explode in heat of fire.
Keep containers cool by spraying with water if exposed to fire.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective clothing.
Breathing protection required.
- Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).
Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Pick up with suitable absorbent material.
Dispose of in accordance with national, state and local regulations.
Large spills should be collected mechanically (remove by pumping) for disposal.
-

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Sources of ignition should be kept well clear.
Take precautionary measures against static discharges.
Substance/product can form explosive mixture with air.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
- Advice on safe handling : Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Provide good room ventilation even at ground level (vapours are heavier than air).
- Further information on storage conditions : Keep container tightly closed and in a cool place.
- Recommended storage temperature : 0 - 30 °C

Thomsit K 182 Neoprene Contact Adhesive Extra

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.08.2022	00000820080	Date of first issue: 30.08.2022

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

- | | | |
|--------------------------|---|---|
| Respiratory protection | : | Respiratory protection in case of vapour/aerosol release. Suitable respiratory protection for higher concentrations or long-term effect:
Gas filter for gases/vapours of organic compounds (boiling point <65 °C, f.e. EN 14387 Type AX) |
| Hand protection | | |
| Remarks | : | Suitable chemical resistant safety gloves (EN 374) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN 374): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Manufacturer's directions for use should be observed because of great diversity of types. |
| Eye protection | : | Safety glasses with side-shields (frame goggles) (e.g. EN 166) |
| Skin and body protection | : | Body protection must be chosen based on level of activity and exposure. |
| Protective measures | : | Do not inhale dust/fumes/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended. |
| Hygiene measures | : | No eating, drinking, smoking or tobacco use at the place of work.
Handle in accordance with good industrial hygiene and safety practice. |

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | |
|------------------------|---|---|
| Appearance | : | liquid |
| Color | : | yellow |
| Odor | : | according to the solvent present in the product |
| Odor Threshold | : | not determined |
| pH | : | substance/mixture is non-soluble (in water) |
| Flash point | : | < -10 °C |
| Flammability (liquids) | : | Highly flammable liquid and vapor. |
| Self-ignition | : | not self-igniting |
| Vapor pressure | : | No data available |

**Thomsit K 182 Neoprene Contact Adhesive
Extra**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.08.2022	00000820080	Date of first issue: 30.08.2022

Density	:	0,83 - 0,93 g/cm ³ (23 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	not determined
Decomposition temperature	:	Vapors may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	6.000 - 7.000 mPa.s (20 °C) Method: Brookfield
Explosive properties	:	Not explosive
Oxidizing properties	:	not fire-propagating

10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge. Avoid heat. See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Thomsit K 182 Neoprene Contact Adhesive Extra

Version 1.0 Revision Date: 30.08.2022 SDS Number: 00000820080 Date of last issue: -
Date of first issue: 30.08.2022

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information

Product:

Remarks : No data is available on the product itself.
Information given is based on data on the ingredients and the toxicology of similar products.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Components:

disulfiram:

M-Factor (Acute aquatic tox- : 10

Thomsit K 182 Neoprene Contact Adhesive Extra

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.08.2022	000000820080	Date of first issue: 30.08.2022

icity)

M-Factor (Chronic aquatic toxicity) : 10

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements. The waste code in accordance with the European waste catalog (EWC) must be specified in cooperation with disposal agency/manufacturer/authorities. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1133
 Proper shipping name : ADHESIVES
 Class : 3
 Packing group : II
 Labels : 3

SAFETY DATA SHEET

Thomsit K 182 Neoprene Contact Adhesive Extra

Version 1.0 Revision Date: 30.08.2022 SDS Number: 00000820080 Date of last issue: -
Date of first issue: 30.08.2022

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : UN 1133
Proper shipping name : ADHESIVES
(CYCLOHEXANE)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. OTHER INFORMATION

Revision Date : 30.08.2022

Full text of other abbreviations

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-

SAFETY DATA SHEET



Thomsit K 182 Neoprene Contact Adhesive Extra

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	30.08.2022	00000820080	Date of first issue: 30.08.2022

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

UN / EN